

<u>*</u>FM 3-7

FIELD MANUAL NO. 3-7

HEADQUARTERS DEPARTMENT OF THE ARMY Washington, DC, 29 September 1994



NBC FIELD HANDBOOK

MEMORANDUM, SUBJECT: Request to Change Chemical Proponent Field Manual Distribution Restriction Statements, 6 October 2000, with 12 October 2000 e-mail endorsement.

Table of Contents

Preface

Chapter 1 - NBC Warning and Reporting System

Chapter 2 - Chemical

Chapter 3 - Protection and Decontamination

Chapter 4 - Nuclear Protection

Chapter 5 - Biological Protection

FM 3-7 Table of Contents

Chapter 6 - Smoke

Chapter 7 - Flame Field Expedients

Appendix A - Combat Orders

Appendix B - NBC Defense Equipment and Training Aids

Appendix C - NBC Signs

Appendix D - Tactical Operations

Appendix E - Conversions and Measurements

References

Glossary

Authorization Letter

DISTRIBUTION RESTRICTION: Approved for public release; distribution is unlimited.

*This publication supersedes FM 3-7, 27 September 1990.



PREFACE

This manual, FM 3-7, is designed as a guide to help the chemical soldier at battalion level and below in NBC defense. It details the NBC warning and reporting system, and how to locate, identify, and operate in and around NBC contamination. This manual is designed to be an easy-to-read, step-by-step manual depicting the manual method of calculating NBC defense procedures useful for the field soldier. A more detailed discussion of NBC defensive measures may be found in:

FM 3-3, Chemical and Biological Contamination Avoidance

FM 3-3-1, Nuclear Contamination Avoidance

FM 3-4, NBC Protection

FM 3-4-1, Fixed Site Protection

FM 3-5, NBC Decontamination

FM 3-11, Flame Field Expedients

Chemical soldiers must be familiar with and be able to apply the information in this manual.

Although this manual does not implement any particular international agreement, material presented herein complies with related international agreements. A list of related international agreements and other references can be found in the references section.

Unless otherwise stated, whenever the masculine gender is used, both men and women are included.

The proponent for this manual is HQ, TRADOC. Submit changes for improving this publication on DA Form 2028 (Recommended Changes to Publications and Blank Forms) and forward it to:

Commandant U.S. Army Chemical School ATTN: ATZN-CM-FNB Fort McClellan, AL 36205-5020.



CHAPTER 1

NBC Warning and Reporting System

The NBCWRS consists of standard NBC Reports and Strike Warnings. This system is broken down into the following areas:

- NBC threat status
- NBC warning and reporting system (NBCWRS)
- Friendly strike warnings
- NBC weather and wind messages

NBC Threat Status (STANAG 2984)

a. Serial 0 (none).

The opposing force does not possess any NBC defense equipment, is not trained in NBC defense or employment, and does not possess the capability to employ NBC warfare agents or systems.

b. Serial 1 (low).

The opposing force has an offensive NBC capability, has received training in defense and employment techniques, but there is no indication of the use of NBC weapons in the immediate future.

c. Serial 2 (medium).

The opposing force is equipped and trained in NBC defense and employment techniques. NBC weapons and employment systems are readily available. NBC weapons may have been employed in other areas of the theater.

Employment of NBC weapons is considered probable. Indicators would be:

- NBC munitions deployed to field storage sites.
- Enemy troops wearing or carrying protective equipment.
- NBC recon elements observed with conventional recon units.
- NBC decon elements moved forward.

d. Serial 3 (high).

The opposing force possesses NBC warfare agents and delivery systems. NBC defense equipment is available and training status is considered at par or better than that of the United States. NBC weapons

FM 3-7 Chptr 1 NBC Warning and Reporting System

have already been employed in the theater and attack is considered probable in the immediate future. Indicators are:

- NBC attack in progress but not in area of operation.
- NBC warnings/signals to enemy troops.
- NBC munitions delivered to firing units within range of friendly forces.
- Movement of surface-to-surface missiles to a launch site.

The threat status can be used for any size or type unit. It is possible to have a CB (chemical-biological) status of three and a nuclear status of zero.

Vulnerability Analysis

To assist field commanders in developing the NBC threat status, refer to <u>tables 1-1</u>, <u>1-2</u>, and <u>1-3</u>.

Se	Serial Number			
0	1	2	3	
-	0	0 1	0 1 2	

Use Xs to mark applicable boxes or degree of threat. Total number of Xs in each column, and use serial number with largest number as current threat status.

Table 1-2. Nuclear threat status ma	trix.			
Condition	Serial Numbe			
Condition		1	2	3
Enemy force information: • Training status • NBC equipment availability • In collective protection shelters, in positions with overhead cover, or exposed				
Nuclear weapons systems: • Availability of nuclear weapons • Nuclear weapons moved forward to firing units or launch sites? • Weather radars queued? • Decon/recon assets forward?				
Enemy nuclear policy and capabilities: • What is enemy's stated policy on nuclear weapons employment? • Can enemy produce nuclear weapons? • Has industrial output increased or changed for production of nuclear munitions or protective equipment				
Current situation: • Have nuclear weapons been used in theater? • Is weather favorable for nuclear attack? • Is terrain favorable for nuclear attack?				
Totals (circle current status)				
Use Xs to mark applicable boxes or degree of threat. Tota serial number with largest number as current threat status		umn	s and	use

		j I	Percent Ca	asualties	•
Type Munition	Target Radii (Meters)	Nonpe	rsistent	Persi	stent
		Nerve	Blood	Nerve	Blister
Bursting	150	40	10	25	10
	500	30	5	20	5
	1,000	15	2	15	2
Spray	150			45	10
. ,	500			30	5
	1,000			20	2

For more detailed discussion of chemical agents, see <u>FM 3-3</u>, Chapter 1 or <u>FM 3-4</u>, Chapter 3.

(F

Temper	ature			Agents		
C°	F°	GA/GF ¹	GB2, 3	GD2, 3	HD1	VX 2, 3
-30	-22		110.34	436.69	**	**
-20	-4	*	45.26	145.63	**	**
-10	14	•	20.09	54.11	**	**
0	32	*	9.44	22.07	••	**
10	50	1.42	4.70	9.78	12	1770
20	68	0.71	2.45	4.64	6.33	634
30	86	0.33	1.35	2.36	2.8	24
40	104	0.25	0.76	1.25	2	10:
50	122	0.25	0.44	0.70	1	44
55	131	0.25	0.34	0.51	1	25

NOTES:

For grassy terrain, multiply the number in the chart by 0.4.

2 For grassy terrain, multiply the number in the chart by 1.75.

3 For sandy terrain, multiply the number in the chart by 4.5.

* Agent persistency time is more than 1.42.

** Agent is in a frozen state and will not evaporate or decay.

*** Agent persistency time exceeds 2,000 hours.



Figure 1-1. Heavy liquid contamination on M9 paper.

Artillery

Aircraft Spray

Missile






Figure 1-2. Moderate liquid contamination on M9 paper (1 gram/square meter).

Estimate Delivery Capability



Generate Effects Information






Figure 1-3. Chemical Vulnerability and Assessment and Force Protection


Table 1-5. GB nerve agent casualties.						
Roun	ds per 100m or .	1 km	١	emper	ature °	F
BM-21/.1 km ²	152mm/.1 km ²	122mm/.1 km ²	10	32	50	68
1	2	4	10%	16%	24%	33%
2	4	7	14%	22%	30%	40%
3	6	10	19%	27%	37%	47%
4	8	14	25%	34%	43%	54%
5	10	17	31%	40%	50%	60%
			Cas	sualty F	Percent	age

Ta	Table 1-6. TGD or VX nerve agent casualties.						
	Rou	inds		1	emper	ature °	F
Msl/ 10km ²	Msl/ 1.5km ²	Bombs/ 10km ²	Bombs/ 1.5 km ²	10	32	50	68
6	1	26	4	5%	14%	20%	21%
9	2	40	6	8%	18%	25%	25%
12	2	54	8	12%	24%	31%	31%
15	2	68	10	16%	28%	36%	36%
18	3	80	12	19%	32%	40%	41%
21	3	94	14	21%	35%	42%	43%
24	3	106	16	23%	37%	44%	45%
				Cas	sualty F	Percent	age

Table 1-7. THD blister agent casualties.					
Munitions in Rounds		Protective	Posture		
152 mm/100m ²	122 mm/100m ²	MOPP Zero	MOPP 1		
4	7	17%	13%		
7	14	24%	18%		
11	20	34%	23%		
14	27	43%	28%		
18	33	51%	32%		
21	40	57%	36%		
		Casualty Percentage			

Flow of NBC Reports

NBC reports 1 through 6 move between units and higher headquarters as shown in Figure 1-4.



- * Best sent as an overlay.
- ** Sent only when requested.

*** For nuclear attacks, only designated observer units will submit reports to division NBCCs (NBC centers). All other units will be prepared to send the information, if requested.

Figure 1-4. Flow of NBC Reports.

LINE	NUCLEAR	CHEMICAL & BIOLOGICAL	REMARKS

A	Strike serial number	Strike serial number	Assigned by NBC center
В	Position of observer	Position of observer	Use grid coordinates (UTM or place).
С	Direction of attack from observer to include unit of measure	Direction of attack from observer	Nuclear: Deg magnetic north (DMN) or mills (MMN). Deg true north (DTN) or mils (MTN). Deg grid north (DGN) or mils (MGN). Chemical: Direction measured clockwise from grid north or magnetic north (state which) in degrees or mils (state which).
D	Date-time group of detonation	DTG os start of attack	Nuclear: Use Zulu time. Chemical: Designate time zone used.
E	N/A	DTG of end of attack	Designate time zone used.
F	Location of area attacked	Location of area attacked	Use grid coordinates (or place). State whether location is actual or estimated.
G	Suspected or observed event and means of delivery or kind of attack	Kind of attack	State whether attack was by artillery, mortars, rockets, missiles, bombs, or spray.
н	Type of burst	Type of agent/type of burst; P (persistent), NP (nonpersistent)	Nuclear: Specify air, surface, or subsurface. Chemical: State whether air, ground, or spray attack.

Figure 1-5. Meaning of line items in NBC reports.

LINE	NUCLEAR	CHEMICAL & BIOLOGICAL	REMARKS
I	N/A	Number of munitions or aircraft	lf known
J	Flash-to-bang time	N/A	Use seconds
к	Crater present or absent and diameter	Description of terrain and vegetation	Nuclear: Send in meters Chemical: Send in NBC 6
L	Cloud width at H + 5 minutes	N/A	State whether measured in degrees or mils
м	Stabilized cloud top or cloud bottom angle or cloud top or bottom height at H + 10 min	N/A	Nuclear: State whether angle is cloud top or cloud bottom and whether measured in degrees or mils. Chemical: State whether height is cloud top or cloud bottom and whether measured in meters or feet.
N	Estimated yield	N/A	Send as KT
ο	Reference date-time for estimated contour line when not H + 1	N/A	Use when contours are not plotted at H + 1.
Р	Radar purposes only	N/A	
РА	N/A	Predicted hazard area (coordinates)	If wind speed is 10 kmph or less, this item is 010 (the radius of the hazard area in kilometers).
PAR	Coordinates of external contours of	N/A	Six-digit coordinates. Letter R identifies

Figure 1-5. Meaning of line items in NBC reports (Continued).

LINE	NUCLEAR	CHEMICAL & BIOLOGICAL	REMARKS
РВ	N/A	Duration of hazard in the attack and hazard area	In days, hours, minutes, etcetera.
PBR	Downwind direction of radioactive cloud and unit of measure	N/A	Deg magnetic north (DGM) or mils (MLM). Deg true north (DGT) or mils (MLT). Deg grid north (DGG) or mils (MLG). Letter R identifies RADAR set.
٩	Location of reading	Location of sampling and type of sample	Nuclear: UTM or place. Chemical: UTM or place. State whether test was air or liquid.
R	Dose rate or actual value of decay exponent	N/A	State dose rate in cGyph. See sample NBC4 for terms associated with this line.
s	Date-time group of reading	Date-time group contamination detected	State time initial identification test sample or reading was taken.
т	H + 1 date-time group	Date-time group of latest contamination survey of the area	NBC 5 and NBC 6 reports only.
υ	1,000-cGyph contour line	N/A	Plot in red.
v	300-cGyph contour line	N/A	Plot in green.

1			
w	100-cGyph contour line	N/A	Plot in blue.

Figure 1-5. Meaning of line items in NBC reports (Continued).

LINE	NUCLEAR	CHEMICAL & BIOLOGICAL	REMARKS
x	20-cGyph contour line; (30-cGyph contour line is used by other NATO forces)	Area of actual contamination	Nuclear: Plot in black. Chemical: Plot in yellow.
Y	Direction of left and right radial lines	Downwind direction of hazard and wind speed	Nuclear: Direction measured clockwise from GN to the left and then right rradial lines (degrees or mils, state which), 4 digits each. Chemical: Direction: 4 digits (degrees or mils). Wind speed: 3 digits (kmph).
Z	Effective wind speed Downwind distance of Zone I Cloud radius (Include unit of measure for each category)	N/A	3 digits—effective wind speed (kmph). 3 digits—Downwind distance of zone 1 (km or nautical miles) 2 digits—cloud radius (km or nautical miles). If wind speed is less than 8 kmph, this line contains only 3-digit radius of zone 1 (km).
			Air stability (2

file:///C|/My Documents/Manuals/Military Field Manuals/FM 3-7 NBC Field Handbook/Ch1.htm (14 of 27) [29/02/2004 3:44:36 AM]

ZA	N/A	Significant weather phenomena	digits). Temperature in centigrade (2 digits). Humidity (1 digit). Significant weather phenomena (1 digit). Cloud cover (1 digit).
ZB	Used to transmit correlation factors or transmission factors	Remarks	Include any additional information.

Figure 1-5. Meaning of line items in NBC reports (Continued).

NBC 1 Observers' Initial Report.

This report is used by the observing unit to give basic initial and follow-up data about an NBC attack. It is sent by platoons and companies to battalion headquarters. Battalion and higher elements must consolidate reports and decide which NBC 1 to forward. The NBC 1 report following the first use of NBC weapons is sent with a FLASH precedence. Subsequent reports are sent with a precedence of IMMEDIATE. Only observers specifically designated by the division NBC center send NBC 1 (nuclear) reports.

Line	Nuclear	Biological (suspected)	Chemical
В	NB062634	LB206300	LB200300
С	90 deg Grid		
D	201405Z Mar 93	200410Z Mar 93	201405Z Mar 93
E		200414Z Mar 93	201412Z Mar 93
F		LB206300 Act	LB200300 Est
G	Artillery	Aerial spray	Bomblets
н	Surface	Unknown	Nerve, P, ground
J	60 Sec		
к			
ΓL.	15 Deg	1	
м			
 NOTES: 1. Line items B, D, H, and either C or F should always be reported; other line items may be used if the information is known. Transmit line item MIKE (nuclear) only when data for line item LIMA cannot be obtained. 2. Biological attacks are considered to be "suspected" until 			
	confirmed by laboratory analysis.		

Figure 1-6. NBC 1 Report.

NBC 2 Evaluated Data Report.

The NBC 2 report is based on two or more NBC 1 reports. It is used to pass evaluated data to units. Division is usually the lowest level to prepare an NBC 2 report. However, a brigade or battalion might do so, especially during independent operations.

Mar 93 DAct
) Act
ground
5
-

Figure 1-7. NBC 2 Report.

NBC 3 Warning of Predicted Contamination Report.

The NBCC uses NBC 1 reports and wind information to predict downwind hazard areas. This is disseminated as an NBC 3 report. Each unit evaluates the NBC 3 report, determines which of its subordinate units may be affected, and disseminates the report as required. This report warns commanders when they may be within a downwind hazard area so they may take protective measures.

NBC 4 Reconnaissance, Monitoring and Survey Report.

When a unit detects NBC hazards through monitoring, survey, or reconnaissance, this information is reported as an NBC 4 report. Reports from various units are plotted on the NBCC situation map to show where hazards exist. These reports are prepared and submitted by company-level organizations.

NBC 5 Actual Contaminated Areas Report.

Once the NBC 4 reports are posted on the situation map, an NBC 5 report is prepared showing the contaminated area. NBC 5 reports usually are prepared by division. The preferred method of dissemination is by map overlay.

NBC 6 Detailed Information on Chemical/Biological Attack Report.

This report, summarizing information concerning a chemical or biological attack, is prepared at battalion. It is submitted to higher headquarters only when requested. If desired, it can be sent from higher to lower for information purposes.

STRIKWARN (Friendly Nuclear Strike)

Line	Nuclear	Chemical
Α	11D024	C002
D	201405Z Mar 93	201405Z Mar 93
F	NB107186 Est	LB200300 Act
н	Surface	Nerve, P, ground
N	50	
PA		
		LB190300
		LB200312
		LB200300
PB		In attack area 2-4 days.
		In warning area 1-2 days.
Y	02720312 deg	0270 deg, 015 kmph
z	01902505	
ZB		
NOTES	 If the effective wind speed is less the NBC 3 nuclear report consists of three Zone I. If the wind speed is less than 10 km NBC 3 chemical report is 010 (the rational state) 	e digits for the radius of oph, line PAPA ALFA of the
	3. NBC 3 nuclear is used for passing in	
	predicted radiological contamination	
	4. Use other line items if information is	known.

Figure 1-8. NBC 3 Report.

Line	Nuclear	Biological	Chemical
н	NB123987	Unknown Agent	Nerve, P
٩	35	NB211603	LB200300, liquid
R S	201535Z Mar 93	201605Z Mar 93	01430Z Mar 93
10123	often as necessary. 2. Radiation dose rates above the ground. 3. In line ROMEO, desc	UEBEC, ROMEO, and SIER are measured in the open v riptive words such as "initi ," "contact," or "summary	with the instrument 1 meter al," "peak," "special,"

Figure 1-9. NBC 4 Report.

Line	Nuclear	Chemical	
Α	11D024	C002	
D	201405Z Mar 93	201405Z Mar 93	
н	Surface	Nerve, P, ground	
S	201535Z Mar 93	201430Z Mar 93	
Т	201505Z Mar 93	201500Z Mar 93	
υ			
v	NB105690		
	NB108685		
	NB105680		
w	NB104694		
	NB111685		
	NB093683		
x	NB103698	LB200300	
	NB114686	LB191291	
	NB091680	LB190300	
NOTES: 1. This report is best sent as an overlay if time and the tactical situation permit.			
	 When contamination arises from a sin to H + 1 hour, and the line item TAN 	ngle burst, the dose rate always refers GO is used. When several detonations	
		and no single H + 1 hour is possible,	
	then dose rates are reported as at a s		
	Therefore, line items OSCAR and TAN	IGO cannot both be used in the same	

report.

3. Contour lines are to be annotated with dose rates.

Figure 1-10. NBC 5 Report

Line	Multiple	Single
Α	Hot Candle	AC002
D	162025Z-162155Z	072220Z-072310Z
F1		011 NB706101
F2		025
F3	PA490650	042
	PA511671	
	PA531174	
	PA527650	
	PA575650	
н	Surface 3	
1	22	

Figure 1-12. STRIKWARN message.

Line	Chemical or Biological	
Α	C002	
D	201405Z Mar 93	
Έ	201412E Mar 93	
F	LB200300, Act	
G	Bomblets	
н	Nerve, P, Airburst	
1	Unknown	
ĸ	Mostly small houses and barns, elevation 600 meters	
м	Attack received as counterfire, from aircraft, enemy bypassed on right flank of atttack area.	
α	Liquid ground sample taken by detection team in attack area	
S	201430Z Mar 93	
T X	201500Z Mar 93	
х	As per overlay	
Y	Downwind direction 0270 degrees, wind speed 015 kmph.	
ZB	This is the second chemical attack in our area to date.	
NOTES	 This report is designed to be presented at battalion level and above and is to be submitted only when requested. This report is completed by battalion and higher NBC personnel. It is in narrative form, giving as much detailed information as possible for each line item. 	
	3. This report is also suitable for accompanying samples sent for analysis.	

Figure 1-11. NBC 6 Report.

Line Item	Meaning
A	Target number of "nickname:
*D	a. Multiple burst. Date-time attack (pulse) will start, followed by
	date-time attack (pulse) will end (ZULU time).
	b. Single burst: Date-time of attack followed by date-time after
	which attack will be cancelled (ZULU time).
•F1	a. Multiple. UTM grid coordinatesof MSD 1 box.
	b. Single. MSD in hundreds of meters followed by UTM grid
	coordinates of GZ or DGZ. (If more than one MSD is included, GZ or
	DGZ will be included only in the first FOXTROT line sent).
F2	a. Multiple. UTM grid coordinates of MSD 2 box.
	b. Single: MSD2 in hundreds of meters (followed by UTM grid
	coordinates of GZ or DGZ, if only one FOXTROT sent).
F3	a. Multiple. UTM grid coordinates of MSD 3 box.
	b. Single. MSD 3 in hundreds of meters (followed by UTM grid
	coordinates of GZ or DGZ if only one FOXTROT sent).
н	If one or more bursts has less than 99% assurance of being an
	airburst, or if it is a scheduled surface or subsurface burst, indicate
	"surface," preceded by the total number of surface and/or
	subsurface bursts. If only one burst is surface, number need not be
	sent. If all bursts are airbursts, do not transmit.
1	Number of bursts in multiple attack. If single burst, do not transmit.
* Line a	should be encoded.
	ation occurs when:
I. Auth	enticated message consisting of Line ALPHA and word "cancelled".

- 2. Single burst detonates. Multiple burst window ends.
- 3. After strike window ends.

Figure 1-13. STRIKWARN format.

Radius	Corresponding to	Zone	Requirements
< MSD ¹	Limit of negligible risk to warned and protected personnel (see note 5)	1	Evacuate all personnel (see note 4).
> MSD ¹ < MSD ²	Limit of negligible risk to warned and exposed personnel.	2	Maximum protection (see note 6) to remain.
> MSD ¹ < MSD ²	Limit of negligible risk to unwarned and exposed risk.	3	Minimum protection (see note 7) to remain.
More than MSD ³			No protection measures except against dazzle and pulse EMP.

NOTE 1. MSD means minimum safe distance.

NOTE 2. When surface bursts are used, or an intended airburst has less than a 99% assurance of no militarily significant fallout, the fallout hazard will be considered. Details will be transmitted in a subsequent NBC 3 nuclear report if fallout will be a hazard to friendly units.

NOTE 3. Commanders will be guided to safety criteria as stated in FM 101-31-1. **NOTE 4.** If a unit commander is unable to evacuate Zone I, he will immediately assume the best protection possible and report through his next higher headquarters to the releasing/executing commander.

NOTE 5. Negligible risk should not normally be exceeded unless significant advantages will be gained.

NOTE 6. Maximum protection for ground forces denotes that personnel are in "closed up" tanks or sheltered in foxholes with overhead shielding, or the equivalent.

NOTE 7. Minimum protection for ground forces denotes that personnel are prone on open ground with all skin areas covered and with an overall thermal protection at least equal to that provided by a two-layer uniform.

NOTE 8. Since the least separation distance (LSD) for light aircraft is exceeded by MSD 3, aircraft remaining beyond MSD 3 will avoid significant degration of the airframe or pilot performance (except against dazzle)severe enough to prevent mission accomplishment.

Figure 1-14. Protection requirements for friendly nuclear strike.

NBC WEATHER AND WIND MESSAGES

Effective Downwind Message (EDM)

ZULU	DDTTTT	Date-Time Group Winds Were Measured (ZULU)
ALFA	dddsss	Over 0 thru 2 KT
BRAVO	dddsss	Over 2 thru 5 KT
CHARLIE	dddsss	Over 5 thru 30 KT
DELTA	dddsss	Over 30 thru 100 KT
ECHO	dddsss	Over 100 thru 300 KT
FOXTROT	dddsss	Over 300 thru 1 MT
GOLF	dddsss	Over 1 thru 3 MT

1. The first three digits (ddd) give the effective wind direction, in degrees, from grid north.

2. The second three digits (sss) give the effective wind speed in kilometers per hour.

3. The last three digits (---) give the expanded angle in degrees (in NATO use 7th digit as follows:


- 4 = 40 degree angle 0 = 100 degree angle
- 5 = 50 degree angle 1 = 110 degree angle
- 6 = 60 degree angle 2 = 120 degree angle
- 7 = 70 degree angle 3 = more than 120 degree angle
- 8 = 80 degree angle
- 9 = 90 degree angle


4. If wind speed is less than 8 kmph, the preselected yield group line will contain only the 3-digit radius of Zone I.

Each EDM is valid for 12 hours. It is used in conjunction with the NBC 2 Nuclear Report to form a simplified fallout prediction (discussed in <u>Chapter 2</u>).

Chemical Downwind Message

- 1. Each chemical downwind message (CDM) is valid for only 6 hours.
- 2. The area affected may be a map sheet number or an area, such as I Corps.





- -----

* NOTE: Unknown weather data is represented by a dash (-).

Figure 1-15. How to read weather information in a chemical downwind message.

3. Lines WHISKEY MIKE, XRAY MIKE, and YANKEE MIKE each contain coded weather information. Line WHISKEY MIKE is valid for only the first 2 hours; line XRAY MIKE for the next 2 hours; and line YANKEE MIKE for the last 2 hours of the six covered.

Strike Serial Number (A)	Date/Time of Attack (ZULU) (D)	GZ Coordinates {Act/Est} (F}	Kind of Attck (G)	Type of Agent (H)	Remarks
C001	200945Z	LB200300 Est	Artillery	Nerve (NP) Air	

Figure 1-16. Suggested format for a chemical/biological strike serial log



CHAPTER 2

Chemical

Atmospheric Stability Charts

Temperature Gradients

Inversion Temperature Gradient (Stable-S). This condition usually exists on a clear or partially clear night when middle and low clouds cover less than 30 percent of the sky, and on early mornings until about 1 hour after sunrise when the wind Speed is less than 5 kmph--ideal for enemy employment of chemical agents.

Neutral Temperature Gradient (Neutral-N). This condition usually exists on heavily overcast days or nights at 1 or 2 hours before sunset or 1 to 2 hours after sunrise when the middle and low clouds cover more than 30 percent of the sky. Independent of cloud cover and time of day, a neutral condition may also exist when the wind speed is greater than 5 kmph. Additionally, periods of precipitation are normally accompanied by a neutral condition. A neutral temperature gradient is most favorable for enemy use of biological agents.

Lapse Temperature Gradient (Unstable-U). This condition normally exists on a clear day when the middle and low clouds cover less than 30 percent of the sky and when the wind speed is less than 5 kmph. It is the least favorable condition for the enemy to employ chemical or biological agents. When a lapse condition exists, area coverage without diffusion will be enhanced with a steady low wind speed of 3 to 7 kmph.

To obtain the air stability category, refer to <u>Table 2-1</u>. Enter <u>Table 2-2</u> with the category obtained from <u>Table 2-1</u>. Select the appropriate weather and terrain conditions from <u>Table 2-2</u>. Read across to where the columns intersect and extract the final stability category. For more information on field expedient behavior of chemical agents, see <u>FM 3-6</u> or from CDM.

Air Stability Category Basic Chart				U == Unstable N == Neutral S == Stable	
Ti	me of day ^o	Condition of Sky			
ar	and angle of sun	Less than half covered	More than half covered	Overcast	
M ≤ O	4°	S	S	N	
	•4° ≤ 32°	Ν	N	Ν	
	32° ≤ 40°	U	N	N	
G >	• 40°	U	U	N	
> E	· 46°	U	U	Ν	
V > E	>35° 46°	U	N	N	
I	>12° 35°	N	N	N	
G	>5° 12°	S	N	N	
≤	5°	S	S	N	

Table 2-2. Air stability category adjust	ment	chart.		
Air Stability Category Adjustment Chart Weather and Terrain All eight conditions given below must be checked. If		U = Unstable N = Neutral S = Stable Stability Category from Basic Chart		
Dry to slightly moist surface.	U	N	s	
Wet surface (after continuous rain or dew).	N	N	s	
Frozen surface or partly covered with snow, frost, or permafrost.	N	s	S	
Surface completely covered with snow.	s	s	s	
Continuous rainfall.	N	N	N	
Haze or mist (visibility 1 to 4 km).	N	N	s	
Fog (visibility less than 1 km).	N	S	S	
Downwind speed more than 18 kmph.	N	N	N	

Once the proper stability condition is determined, use <u>Table 2-3</u> to compute the downwind distance for Type A attacks.

Table 2-3. Downwind distance of warning area				
Means of Delivery (from line G of the NBC 1 or NBC 2)	Distance (km) from the center of th attack area along the downwind ax when the atability condition is—			
	U	N	s	
Artillery, bomblets, and mortars	10	30	50	
Multiple rocket launchers, missiles, bombs, and unknown munitions.	15	30	50	

Rate of Action	How normally disseminated	Protection required	Decon	Means of identification
rapid by tion, slower ugh skin yed through rapid ugh eyes	Aerosol or vapor	Protective mask and protective clothing	STB slurry; household bleach; 10% solution of lye or washing soda; DS2; steam and ammonia in confined area; hot, soapy water; M258-series kit; M291 kit	M256, M18A2, CAM, M8/M9 paper, M8A1 alarm
d	Aeroso! or vapor	Protective mask	None needed in field.	M256, M18A2
ers delayed s to days; effects more l. Mustard site, aand gene oxime rapid	Liquid or droplets	Protective mask and protective clothing	STB; DS2; household bleach; M258-series kit; Try lye; fire. Wash with soap and water.	M256, M18A2, CAM, M8/M9 paper

file:///C//My Documents/Manuals/Military Field Manuals/FM 3-7 NBC Field Handbook/Ch2.htm (4 of 22) [29/02/2004 3:45:16 AM]

•

Persistent

FM 3-7 Chptr 2 Chemical

Classification of chemical agents:

Plotting Chemical Agent Hazards

Table 2					
Symbol	Symptoms in man	Effects on man			
GA GB GB VX	Difficulty breathing, sweating, drooling, neusea, vomiting, convulsions, and dimming of vision	Incapacitates atlow concentration; kills if inhaled or absorbed through the skin or eyes	Very inhla throu Dela skin; throu		
АС СК	Rapid breathing, convulsions, and coma	Kills if high concentrations are inhaled	Rapi		
HD HN HL L	No early sumptons. Searing of eyes and stinging of skin Powerful irritation of eyes.	Blisters skin and respiratory tract; can cause temporary blindness. Some agents sting and form	Blist hour eye rapid lewis phos very		
	GA GB GB VX AC CK HD HN HL L	in manGADifficultyGBbreathing,GBsweating,drooling, neusea,vomiting,VXconvulsions, anddimming of visionACRapid breathing,CKconvulsions, andcomaHDNo earlyHNsumptons.HLSearing of eyesLand stinging ofskin	SymbolSymptoms in manEffects on manGADifficulty breathing, sweating, drooling, neusea, vomiting, convulsions, and dimming of visionIncapacitates atlow concentration; kills if inhaled or absorbed through the skin or eyesVXRapid breathing, convulsions, and dimming of visionKills if high concentrations are inhaledACRapid breathing, convulsions, and comaKills if high concentrations are inhaledHDNo early sumptons. LBlisters skin and respiratory tract; can cause temporary blindness.CXPowerful irritation of eyes,Some agents sting and form		

Chemical Hazard Plotting Steps

Air-Contaminating Agents--Type A

ground. Type A agents normally are dispersed as aerosols or vapor clouds with little or no contamination on the

Ground-Contaminating Agents--Type B

Type B agents normally are expected to be dispersed in liquid form to contaminate surfaces.





Figure 2-1. Flow chart. Chemical Hazard Prediction

Chemical Hazard Prediction



file:///C|/My Documents/Manuals/Military Field Manuals/FM 3-7 NBC Field Handbook/Ch2.htm (7 of 22) [29/02/2004 3:45:16 AM]

MRL'S Missiles, Bombs and Unknown	15 km	30 km	50 km
---	-------	-------	-------

Figure 2-2. Flow chart, type A attack.

Plotting Downwind Hazard

Step 4


Example (Type A, Case a) NBC 3 Chemical Report Step 1 - Attack location Step 2 - 1km Attack area circle Step 3 - 10km hazard area circle





Figure 2-3. Type A, Case a.


STEP 7




- Step 1 Attack location
- Step 2 Grid north line
- Step 3 1km attack area circle
- Step 4 Downwind direction and speed
- Step 5 Downwind distance Step 6 - Extended upwind intersection point
- Step 7 Tangent lines

Figure 2-4. Type A, Case b.

Chemical Hazard Prediction Air Burst Persistent Agent Type "B" Attack Windspeed < 10 kmph






* All Type "B" Downwind Distance is 10 km * Size of Attack Area Unknown, Use Type "B" Case "b"

Probable Time After Ground Contamination Which Personnel May Safely Remove Mask (Line Papa Bravo)				
Daily Mean Surface	Within Attack Area	Within Hazard Area		
Air Temperature	Number of Days	Number of Days		
<0 - 10* C (32 -50* F)	3 - 10 Days	2 - 6 Days		
11 - 20* C (51 -68* F)	2 - 4 Days	1 - 2 Days		
21 - >30* C (69 - 86* F)	Up to 2 Days	Up to 1 Day		

Figure 2-5. Flow chart, type B attack.




Plot the same as type A, Case b Maximum downwind distance is 10km

Figure 2-6. Type B, Case a.

STEP 6


Example (Type B Case b) NBC 3 **Chemical Report** 002 A D 27147Z F LB560750 Actual Nerve, PER, Ground Burst н PA LB556751 LB559754 LB632774 LB106694 LB568747 0105 Deg, 022 kmph Υ ZA 218242 ZB Type E Case b Coordinate Points For Lines PA



Step 1. Attack location Step 2. Grid north line Step 3. 2km circle

- Step 4. Downwind direction and distance
- Step 5. Extended upwind intersection point
- Step 6. Tangent lines


Figure 2-7. Type B, Case b.



Step 1. Attack area Step 2. 1km circles Step 3. Downwind direction lines Step 4. Downwind distance


Step 5. Tangent lines

Figure 2-8. Type B, Case c.



Step 1. Attack location Step 2. 10km circle Step 3. Attack area circle

Figure 2-9. Type B, Case d.



- Step 1. Attack area (Start/end points)
- Step 2. Start/end point 1 km circles
- Step 3. Attack area
- Step 4. Start/end point 10km circles
- Step 5. Hazard area

Figure 2-10. Type B, Case d (Special).

Adjusted Hazard Prediction

Adjust hazard predictions when:

- Windspeed change of 10 kmph or more
- Wind speed increases from less than 10 kmph to more than 10kmph or the reverse.
- Change of air stability category (Type A attacks only)
- Downwind direction change of 30° or more.




Figure 2-11. Recalculation of downwind hazard area, Type A attack, after change in downwind direction at Point B.

Persistency of Chemical Agents

<u>Table 2-5</u> shows persistency of chemical agents for moderate contamination. As a rule of thumb, cooler conditions increase the persistency of chemical agents. Persistency triples as contamination levels increase from moderate to heavy. Chemical agent persistency data in <u>Table 2-5</u> is for surface winds of 10 kmph and considers weathering only (without decon). For other surfaces use the following multiplication factors for the times given: alkyd paint = 1.3, bare soil = 4.0. Agent HL is not shown. To approximate HL, use GD persistency times. Concentrations of contamination are considered to be heavy at (10 grams per square meter. One week is considered to be 168 hours. One month (30 days) is equal to 720 hours.

Tempo	erature	GA/GF ¹	GB ^{2,3}	GD ^{2,3}	HD1	VX ^{2,3}
C.	F°					
-30	-22		110.34	436.69	• •	***
-20	-4	*	45.26	145.63	**	***
-10	14	*	20.09	54.11	••	***
0	32		9.44	22.07	* *	***
10	50	1.42	4.70	9.78	12	1776
20	68	0.71	2.45	4.64	6.33	634
30	86	0.33	1.35	2.36	2.8	241
40	104	0.25	0.76	1.25	2	102
50	122	0.25	0.44	0.70	1	44
55	131	0.25	0.34	0,51	1	25
or grassy or Sandy	terrain multi terrain multij	ply the numbe ply the numbe ply the numbe is greater that	r in the chart r in the chart	by 1.75		

Time of Arrival for Chemical Hazards

The earliest an agent can be expected to arrive at a location is determined by dividing the distance from the attack center by twice the wind speed. For example, if you are 10 kilometers from the attack center and the wind speed is 5 kilometers per hour, the earliest the agent cloud would arrive at your location would be one hour.

 $10 \text{ km} \div (2 \text{ x } 5 \text{ kmph}) = 1 \text{ hour}$

Collective Protection

Table .	2-6 Types of coll vehicles an	ective-protection d fixed facilities.	systems for
System	Description	conditions Justifying the Requirement	Example Systems
Ventilated- faceplate	Series of individual respiratory systems (or masks) serviced by a common filter.	 Clean working area subject to inadvertent entry of contamination. High work rate, reduced breathing resistence. Frequent entry and exit movements. Brief inside occupation. 	 Infantry fighting vehicles. Self-propelled howitzers.
Overpressure	A collective NBC filter and overpressure system inside a vehicle or shelter	 Critical manual dexterity skills. Limited entry and exit movements. Lengthy inside occupation. 	 Air defense. Communications. Medical. Patient evaluation vehicles. Maintenance and supply sites. Rest and relief.
Hybrid	Combination of overpressure and ventilated-facepiece system.	 Flexibility. Lenghty inside occupation. Emergency entry and exit movements. 	 Armored fighting vehicles (tanks). Helicopters. Air defense. Multiple launcher rocket system.
Total	Hybrid or overpressure plus an environmental control system. Other categories may also incorporate environmental control; for example, ventilated facepiece and microclimatic cooling.	 Same as hybrid. Extreme climates. 	• Same as hybrid.

Table 2-7. GPFU fielded systems.				
Number of GPFUs/System	System			
1	M60 Tank			
1	M60A1 Tank			
1	M60A2 Tank			
1	M60A3 Tank			
1	M728 Combat Engineer vehicle			
1	M1 Tank			
1	M1A1 Tank			




Figure 2-8. Simplified collective-protection equipment.




Figure 2-12. Entry process times.

	Set-U	Tear-Down		
System	Personnel in MOPP4	Time (min)	Personnel in MOPP4	Time (min)
Simplified Collective-Protection	2	30 ²	2	10 ³
Equipment M20 Modular Collective-Protection	2	10⁴	2	5
Equipment M51 Shelter	5	30 ⁶	5	30

⁴ Protective entrance only.

⁵ Site-prep and stake-down times not included.

Soldiers Not in Collective Protection		Soldiers in Collective Protection		
MOPP Level	MOPP Ge	ar	Ventilated Facepiece	Overpressure
Zero	Overgarment Overboots Mask & Hood Gloves	carried carried carried carried	•Assume MOPP zero.	Assume MOPP zero. Overpressure off.
1	Overgarment Overboots Mask & Hood Gloves	worn carried carried carried	•Assume MOPP 1.	 Assume MOPP zero or MOPP 1. Overpressure on.
2	Overgarment Overboots Mask & Hood Gloves	worn worn carried carried	•Assume MOPP2.	 maintain MOPP zero or MOPP1. Overpressure on. Entry exit procedures not required.
3	Overgarment Overboots Mask & Hood Gloves	worn worn worn carried	 Assume MOPP3. When mounted, connect ventilated facepiece to mask. 	 Maintain MOPP zero or MOPP1 unless interior is contaminated. Overpressure on. Exit/entry precedures required if an attack occurs
4	Overgarment Overboots Mask & Hood Gloves	worn worn worn worn	 Assume MOPP3 or MOPP4.* When mounted, connect ventilated facepiece to mask. 	 Maintain MOPP zero or MOPP1 unless interior is contaminated. Overpressure on. Entry/exit procedures required if an attack occurs



CHAPTER 3

Protection and Decontamination

	Mopp Levels						
MOPP Equipment	MOPP Zero	MOPP1	MOPP2	моррз	MOPP4		
Mask	Carried	Carried	Carried	worn*	Worn		
Overgarment	Available	Worn*	Worn*	worn*	Worn		
Chemical Protective Undergarment	Carried	Worn**	worn**	Worn**	Worn**		
Vinyl Overboot	Available	Available	Worn	Worn	Worn		
Gloves	Available	Carried	Carried	Carried	Worn		
 The jacket or hood The CPU is worn to crowman, and aviato Modification of stand mask and gloves only Chemical protective house 	inder the BE rs). Iard MOPP (/).	OU (primarily ovols is aut)	y applies to norized (for	example, m	ask only or		

Individual Protective Equipment

The BDO/CPOG becomes unserviceable if it is ripped, tom, or a fastener is broken or missing; or if petroleum, oils, or lubricants are spilled or splashed on the garment. Chemical protective glove set, greenback vinyl overboot, and chemical protective footwear covers become unserviceable if ripped, tom, punctured, cracked, or if the rubber becomes sticky. Serviceability tests for the chemical protective gloves set. Fill each glove with air and submerge in water, checking for air leaks. Fill glove with water and check for water leaks. Any leaks make the glove unserviceable. NOTE: See <u>FM 3-4</u>, Chapter 2, for detailed information.

When the commander directs his unit to go from MOPP Zero to MOPP1, the chemical officer/NCO will determine BDO/CPOG days of wear. Upon completion of the mission, the unit returns to MOPP Zero, and overgarments are returned to their vapor-barrier bag. The chemical officer/NCO at company or battalion level estimate the number of days of BDO/CPOG wear for his unit. Then uses the information on days of

overgarment wear as input for risk assessment.

Item	Not exposed to chemical agent	Exposed to chemical agent
Battledress overgarment	•30 days	24 hours
Chemical protective overgarment	•14 days	6 hours
14/25-mil glove set	• • `	24 hours
Green/black vinyl overboot	••	24 hours
Chemical protective footwear cover	••	24 hours
7-mil glove set		6 hours
 Times begin when item is removed from its a back in its vapor-barrior bag. * Will protect against liquid chemical agants - serviceable. 		

The key to effectiveness at any time during wear is serviceability.

Wear time may be extended by the commander when operationally necessary. See FM 3-4, Chapter 3, Chemical Vulnerability Assessment and force protection for detailed information.

Any operational hazards may have a degrading effect on protective capabilities (i.e., rivercrossings, moving through swampy/wat areas, heavy rain, excessive sweating by soldiers, POL spills while refueling, maneuver through areas where IPE is easily torn or ripped.

Table 3-3. BDO risk assessment.			
Days of wear Risk of injury			
<30	Negligible		
>30	(approx 5%-ID)		
>45	(approx 10%-ID)		
>60 (10%-ID)			

Filter Exchange Criteria

Filter exchange criteria for all NBC falters in the inventory-from the mask filters to the filters on the simplified collective-protective equipment (SCPE)--are based on design, physical condition, climatic conditions, and the possible agent that could be employed. The following <u>paragraphs</u> discuss peacetime, transition-to-war, and wartime exchange criteria.

Peacetime

When assessing filter exchange criteria, consider several factors. Commanders and NBC personnel must monitor replacement schedules for pieces of NBC equipment with filters. Peacetime exchange criteria for all filters is based on the following conditions:

FM 3-7 Chptr 3 Protection and Decontamination

- Physical damage occurs.
- Immersion in water, or filters have become water logged by other means.
- High resistance to airflow is observed.
- Directed by higher headquarters.
- Listed as unserviceable in SB 3-30-2.

NOTE: When filters are listed as unserviceable in SB 3-30-2, they still can be used as training filters.

Transition to War

Leaders consider NBC issues when preparing for deployment. As part of that process, commanders will determine when their units should remove their training filters and replace them with filters from unit contingency stocks. The commander's guidance should be reflected in an SOP or order. Factors for consideration on whether to exchange filters include unit location, unit readiness/deployability alert status, last time falters were exchanged, threat, time available, and stocks available. For example, a forward deployed unit commander, based on an enemy chemical capability in the area of operation, directs by SOP that his or her unit install its contingency set of filters. Alternatively, a CONUS-based unit commander determines that the basis for installing contingency falters would occur upon an increase in unit alert status for deployment to an area with an NBC threat.

Table 3-4. Wartime Filter Exchange Criteria.							
Climate Category			Hot				
Filter	Cold humid (weeks)	Warm moderate (weeks)	ate (weeks)	Hot humid (weeks)	System		
•C-2/M13A2	52	52	39	10	•M40/M17-series		
 M10A1 canister 	52	52	52	13	protective mask		
 M18 gas 	52	39	26	4	•M24/M25		
•M12A1 gas	52	39	26	4	protective mask		
•M48 gas/particulate	52	52	39	10	 Filter comp of M13 tank GPFU 		
MCPE gas/particulate	52	39	26	4	 Fixed site filter use in structure 		
•HSFC gas/particulate	52	39	26	4	and building •M1A1 task		
•M23 gas	52	39	26	4	overpressure		
•M10 gas	52	39	26	4	system		
•C-22 R1 gas	52	52	52	13	 Modular collective 		
c	limatic De	finitions			protection equipment		
Category	Mean	temp (F)	Mean relative humidity (%)		Simplified protection equipment		
Cold, humid	<	-15	<90		M20/M28		
Warm, moderate	<	60	<70		•M51 shelter		
Hot, dry		98	<	27	fixed site filter		
Hot, humid	>	96	>	76	• GPFU M46 fixed site filter		

Considerations commanders should use before initiating filter exchange include:

- Mission--What is the unit mission?
- Enemy--What is the current threat assessment with respect to use of NBC weapons? Is our unit likely to encounter attack on arrival in the operational area?
- Terrain--Where should filters be exchanged: at home station, en route, or in the operational area?

Troop Preparation

Plan Ahead

- Check NBC defense guidance on OPLAN/OPORD; anticipate projected work requirements in the next 24-48 hours.
- Ensure serviceability or shortfalls of equipment through precombat inspections of NBC equipment.
- Know the most current weather data, particularly wind direction.
- Plan work/rest cycles appropriate to the environment and the mission.

FM 3-7 Chptr 3 Protection and Decontamination

- Ensure deployment and mounting of alarms.
- Use SOPs to reduce command, control, and communication tasks.
- Keep plans simple.

Think Teamwork

- Use methods of individual identification (name tags, personal items).
- Encourage "small-talk" while in MOPP.
- Pair an experienced soldier with an inexperienced "buddy" whenever possible.
- Use the buddy system to ensure that all members of the unit are regularly checked for signs of stress and agent exposure.

Work Smart

- Provide relief from MOPP4 as soon as the mission allows.
- Use world/rest ratios, slow work rate, and minimize work intensity.
- Work in the shade whenever possible.
- Enforce command drinking to reduce dehydration and heat casualties.

REMEMBER--the most motivated soldiers and leaders are the most likely to ignore their needs for food, water, and rest.

- Use collective protection as much as possible.
- Enforce good eating, drinking, and sleeping discipline.
- Rotate jobs and people during long shifts or periods of inactivity.
- Provide relief from extreme temperatures (hot or cold) as soon as possible.
- Remember that even short breaks from total encapsulation are effective in sustainment performance.
- Augment units or divide work between two units.
- Schedule work for a cooler time of day or at night.

MOPP Analysis

Use intelligence preparation of the battlefield (IPB) to determine--

- An estimate on how many enemy fire support systems are in range, where, and what they are.
- How to support probable enemy courses of action (COA).
- Enemy's intent and capabilities.
- Enemy tactical doctrine.
- An evaluation of arms of operation and times of interest set by the commander.
- Terrain and weather.
- Threat integration (how the enemy will fight).

Prior planning based on information provided by the chemical officer will help the commander make sound decisions. Regular updates need to be provided to the commander because of rapid changes in the situation.

Using IPB, provide the commander and staff:

- Detailed information on enemy NBC capability based on the type of weapon systems that the enemy has available at that period of interest.
- How the enemy would employ chemicals.
- Areas of likely employment based on threat employment doctrine.
- Detailed analysis of terrain and weather in the unit's AO during each period of interest.
- MOPP guidance for each period of interest.
- Templates of predicted fallout data that are updated as conditions change.
- Alternative actions the commander can initiate prior to the time period in question to minimize degradation of affected units.
- Continuous monitoring of S2 message and radio traffic for any NBC-related information that could be important to the unit's mission.

MOPP System Flexibility

Flexibility is the key to providing maximum protection with the lowest risk possible while still allowing mission accomplishment. Commanders may place all or part of their units in different MOPP levels or authorize variations within a given MOPP level.

Soldiers may leave the overgarment jacket open at MOPP1, MOPP2, or MOPP3 allowing greater ventilation. Soldiers may leave the hood open or rolled at MOPP3. The various configurations of the last two MOPP levels with the hood rolled or open are referred to as "MOPP open." Commanders decide which of these variations to use based on the threat, temperature, and unit work intensity.

Units may be granted the flexibility to raise or lower their protective posture from that recommended by higher headquarters. This may be done down to platoon level and by an element that finds itself isolated. If higher headquarters specifically denies this flexibility, then protective postures may only be raised, not lowered.

WARNING

Do not use mask-only when blister or persistent nerve agents are present.

Managing Performance Problems

- heat stress
- hunger
- thirst
- discomfort
- performance degradation

- reduced ability to see and hear
- increased feelings of isolation end confusion
- frustration and claustrophobia or panic
- degraded alertness and attention

Physiological factors during sustained periods of MOPP are:

Table 3-5 provides examples that can be used as a guide in estimating the work

Table 3-5. Work intensities of military tasks.					
Work intensity In MOPP Zero-MOPP1	Activity	Work Intensity in MOPP2—MOPP4			
Very light	 Lying on ground Standing in foxhole Sitting in truck Guard duty Driving truck 	Very light			
Light	 Cleaning rifle Walking, hard surface/1m/s, no load Welking, hard surface/1m/s, 20 kg load Manual of arms Walking, hard surface/1 m/s, 30 kg load 	Light			
	 Walking, loose sand/1 m/s,no load Walking, hard surface- /1.56 m/s, no load Colisthenics 	Moderate			
Moderate	 Walking, hard surface/1.56 m/s, 20 kg load Scouting patrol Pick and shovel Crawling, full pack Digging foxholes Field assaults 	Ησανγ			
Невуу	 Walking, hard surface/1.56 m/s, 30 kg load Walking, hard surface/2.0 m/s, no load Emplacement digging Walking, hard surface/2.25 m/s, no load Walking, loose sand/1.56 m/s, no load 	The work intensity categories of this table are based on metabolic expenditures. Very light = 105 to 175 watts Light = 172 to 325 watts Moderate = 325 to 500 watts Heavy = 500 + watts Moderate = 325 to 500 watts Heavy = 500 + watts The weight of the chemical protective overboots is a primary contributor to increased work intensity in MOPP.			

The following tables will provide information necessary to calculate recommended work/rest cycles, water

·

requirements, maximum work times and recovery times.

					MOPP4 +					MOPP4 + BDU				
			MOPF	Zero			Unde				0994	+ 81		
WBGT	Ta	VL	L	м	н	VL	L	м	н	VL	L	м	н	
78	82			NL	25		30	10	5		25	10	5	
80	84			40	25		25	10			20	10		
82	87			35	20		20	5			15			
84	89		NL	30	20									
86	91			30	20	NL				NL				
88	94	NL		20	15	1								
90	96			20	10	1			na				na	
92 98 10				10	10	1	na	na			na	na		
94	100		30	10	10	1								
96	103		10								1			
98	105			na	na	na				na				
100	107	na	na											
KEY TO							IONS							
WBGT				1			provid see Ta	+					utag	
Ta - Ar	peratun			Ire			r hou							
	Bulb	,				· ·	dition							
VL · Ve	ery Lig	ht W	ork		each	hour	should	d be s	pent i	in rest	t. This	table	:	
	nsity						red us							
L - Ligh			+				EM H							
M - Mo		a wor	к				neratii							
	nsity ww.W	ork In	tensit	v	(ully hydrated, rested, and acclimated; 2) 50% relative humidity; 3) windspeed = 2m/s; 4)									
	I - Heavy Work Intensity IDU - Battle Dress Uniform												ide	
	IL - No Limit (Continuous				clear skies; 5) heat casualties <5%. This guide should not be used as a substitute for common									
	Work Possible)				sense or experience. Individule requirements									
	a - Work/Rest Cycle Not				may very greatly. The appearance of heat									
					casualties is evidence that the selected work/rest schedule is inappropriate for the									
Wor								ule is RIEM			te for	the		

	Tab	le 3-			requ (da					/rest	' cyci	les	
			мори	Zero	,			P4 + rwear		м	OPP4	+ 80	υ
WBGT	To	٧L	L	M	н	VL	L	м	н	VL	L	M	н
78	82	0.5	1.0	1,5	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
80	84	0,5	1.0	1.0	1.0	1.0	1.0	1.0		1.0	1.0	1.0	
82	87	1.0	1.0	1.0	1.0	1.0	1.0	1.0		1.0	1.0		
84	89	1.0	1.0	1.0	1.0	1.0				1.0		i -	
85	91	1.0	1.0	1.0	1.0	1.0				1.0			
88	88 94 1.0 1.5 1.0					1.5				1.5			
90						1.5			na	1.5			50
92	92 98 1.0 1,5 1.0					1.5				1.5		na	
94	94 100 1.0 1.5 1.5					1.5	na	no		1.5	na		
96	103	1.0	1.5										
98	105	1.5		80	no	na				рġ			
100	107	no	na			,							
Ta - An (Dry VL - Ve Inter L - Ligh M - Mod Inten H - Hea BDU - E NL - No Work na - Wo Feasi	- Wat peratu ibient Bulb - ry Lig isity t Wat darate isity vy Wa latila I Limit Poss rk/Res bla (S itemai	Bulb (re (°F Temp °F) ht Walk work Inter Walk ork Inter (Contrible) st Cyce co Wints in	i) beratu ork nsity c c unifo inuou ile No ster	im s t	Wate work support block stross Tabla cours to sw predic Strain restor heat of substi-	Itost s ort of tricted s), on- s, Wol 2-1.1 c of s reat. 7 ction c Modu ates in l, and lity; 3 cesual itute f granco york II	ireme ichedu sustei d war k inte Drinki ach h he ta ach he ta ach h he ta ach h he ta ach h he ta ach h he ta ach h he ta ach he ta ach he ta ach he ta ach he ta ach he ta ach	nts lis ales sp ined v horma k time msitio ng sh our to ble w lities i sumpt a 1) tre mated dspeed 5%. mmon at cas	ted an accilic rork, a l stress as unr s may ould b repla to pre of the iong u cops l ; 2) 5 d 2m/ This g sensi- cualito	re for ed in 1 and w as (un estric be a be divi ce we parad USA used in fully h 0% re s; 4) i puidan e or e: s is a	both I fable : rock til shade tod by stimal dod o ator as using RIEM n gene sydrate blativo clear s sperie vidence have	3.6 fo mes d then ed us ver it is Heat erating ed, klos; not a nce; te tha	mal ing lost 5}

.

		Tab	le 3-			aximum work times (minutes) aylight operations).								
			моря	Zero	,		MOP Unde:			MOPP4 +BDU				
WBGT	Т٥	VL	L	м	н	VL	L	м	н	VL.	L	М	н	
78	82			NL	65		177	50	33		155	49	32	
80	84			157	61		142	49	32		131	48	32	
82	87			114	56		115	47	31		110	45	30	
84	89		NL	99	53		104	45	30		100	45	30	
86	91			87	50	NL	95	44	29	NL	93	44	29	
88	94	NL	NL 7		45		85	42	28	•	83	42	27	
90	96		67 60				79	41	27		78	41	27	
92	98						75	40	26		74	40	26	
94	100		193	55	37		70	39	25		70	39	25	
96	103		101	48	33	203	65	37	23	194	65	37	23	
98	105		82	44	31	141	62	36	22	140	62	36	22	
100	107	261	70	41	28	118	59	35	21	118	59	35	21	
10010726170412KEY TO TABLE:INWBGT - Wet Bulb GlobeTheTemperature (°F)inTamperature (°F)inTamperature (°F)inUry Bulb - °F)wVL - Very Light WorkSiIntensityprL - Light Work IntensityUSM - Moderate WorkinIntensityhyH - Heavy Work IntensityreBDU - Battle Dress UniformchemicalNL - No Limit (Continuousas					This inten of mi work 5% prepa USAF in gen hydra relativ clear a sub Indivi	RUCT table ; sity (s nutes perior risk of ared us RIEM i noration ted, r skies, stitute dual r arance	arovid co Ta work d with heat feat S ng this ested, nidity the g for c euiren	es for ble 3- can t nout e causu he pro itain ! s table , and ; 3} w puidan commission	four 6), the so sus xceed alties dictio Model inclu acclim indsp co sh on se may	lovels c max tained ing a . This n cap . Assu de 1) hatized eed = ould n has or very g	dimum f in a : greate ability mptic all tro d; 2) 5 : 2m/s ot bo rexpan reatly	num! single of that of th ons us oops f 50% s; 4) used tience . The	n ood ully es	

Table	3.9	. Wa	ter r		rements for maximum work times (qt/hr) aylight operations).								
			MOP	PZero			MOP	P4 + rwear		MOPP4 = BDU			טט
WBGT	Ta	VL	L	M	н	٧L	L	м	н	٧L	L	м	н
78	82	.5	1.0	1.5	2.0	1.0	1,5	2.0	2.0	1.0	1.5	2.0	2.0
80	84	.5	1.0	1.5	2.0	1.0	1.5	2.0	2.0	1.0	1.5	2.0	2.0
82	87	1.0	1.0	1.5	2.0	1.0	1.5	2.0	2.0	1.0	1.5	2.0	2.0
84	89	1.0	1.0	1.5	2.0	1.0	1.5	2.0	2.0	1.0	1.5	2.0	2.0
86	91	1.0	1.0	1.5	2.0	1.0	1.5	2.0	2.0	1.0	2.0	2.0	2.0
88	94	1.0	1.5	2.0	2.0	1.5	2.0	2.0	2.0	1.5	2.0	2.0	2.0
90	96	1.0	1.5	2.0	2.0	1.5	2.0	2.0	2.0	1.5	2.0	2.0	2.0
92	98	1.5	2.0	2.0	1.5	2.0	2.0	2.0	1.5	2.0	2.0	2.0	
94	100	1.0	1.5	2.0	2.0	1.5	2.0	2.0	2.0	1.5	2.0	2.0	2.0
96	103	1.0	1.5	2.0	2.0	1.5	2.0	2.0	2.0	1.5	2.0	2.0	2.0
98	105	1.5	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
100	107	1.5	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.O	2.0
To • An	Wet beratum bient Bulb - ry Lig sity t Worl derate sity vy We atlle (Bulb (ro ("F Temp "F) ht Work Work Dress	nsity ensity	, m	Amou maxir work be div requit maxir troop: regard for an work predic Strain estima tosted humid 5) hor substi appeo	intensivided romen num v s will diess of extain comp clion of Mode atos in l, and lity; 3 t case tute f rance vork li	sted a work t sities t over o t is 2. water becom of amon becom of amon becom of amon becom of amon becom of amon becom of amon becom beco	ine req limes using course 0, sw absor- ne inc- ount of rest ar- ount of r	NOTE juired in Table of ea reat lo ption reasin frunk; ind reh table the U ions u pops f d; 2) d = 2 6. Thi sense pualtio	S: to sup ole 3-1 3-5. sch ho ss is during gly d leade ydrati was p ISARI sed ir ully h 50% m/s; s guid o cr ex s is e		mate ng shi water r thar our, a buid pi riod a buid buid buid buid buid buid buid buid	ould nd lan t ng es; a

.

Tabl	e 3-10.			estimates after maximum work est in the shade).
WBGT	Ta	MOPP Zero	MOPP4	KEY TO TABLE: WBGT - Wet Bulb Globe Temperature (°F) As Measured in shade (If Only Full Sun
60	68	0.25	1.0	WBGT Is Available, Subtract 5°F WBGT
66	75	0.25	1.0	Before Using This Table) Ta - Ambient Temperature (Dry Bulb -°F)
72	82	0.5	1.5	MOPP Zero - Battle Dress Uniform Only
74	84	0.5	1.5	MOPP4 - Battle Dress Overgarment and Mask (Closed)
76	86	0.5	2.0	NCP - No Cooling Possible Under These
78	88	0.5	2.0	Conditions - Seek Cooler Location and/or Remove BDO
80	91	0.5	3.0	
82	93	0.5	4.0	NOTES AND INSTRUCTIONS: This table provides the number of hours
84	95	0.5	6.0	rest in the shade that should be required after working the maximum work times
86	97	1.0	15.0	specified in Table 3-8 or 3-13. This table
88	100	1.0		was prepared using the cooling capacity equations of the USARIEM Heat Strain
90	102	1.0		Model. Assumptions used in generating
92	104	1.5	NCP	this table include 1) troops fully hydrated and acclimatized; 2) 50% relative
94	106	2.0	NCP	humidity; 3) windspeed = 2m/s; 4) no
96	109	8.0		solar load; 5) recovery of normal body temperature. This guidance should not be
98	111	NGR		used as a substitute for common sense
100	113	NCP		or experience. Individual requirements may vary greatly. USARIEM 1/11/91

•

				0,0	• 1.1.	<u></u>	<i>p</i>	le (night operations).					,				
			моря	Zero		MOPP4 + Underwear				MOPP4 + BDU							
WBGT	Ta	VL	L	м	н	VL	L	м	н	VL	L	м	н				
60	68				40			30	20			25	15				
66	75				40			25	15			25	15				
72	82				35		NL	20	15		NL	20	10				
78	88			NL	30 25 25 NL			15	10			15	10				
80	91					1		15	5			15	5				
82	93	NL	NL			NL	30	10	5	NL	25	10	5				
84	95			40	25	1	25	10			20	5					
86	97			35	20	1	15	5			10						
88	100			30	20	1											
90	102			25	15	1	na	na	na		na	na	na				
92	104			20	15	1											
94	106			15	10												
WBGT Tem Ta - An (Dry VL - Ve Inter L - Ligh M - Mo Inter H - Hee BDU - E NL - Ne Wor	88 100 30 90 102 25 92 104 20					sity (s ork pe e cond hour prepai ISARI IS	provid see Ta in hour ditions should red us EM He neration ted, ro midity ; 5) he be us cperie greatly is evid	les, fo ble 3- r in w s spec d be s sing the eat St ng this ested, r; 3) w eat ca sed as nce. h r. The fence	or four 5), the ork/re- ified. pent i he pre- rain M s table and a vindsp sualti- a sut ndivid appe- that t	r level e nun st sch The r n rest dictio dictio dodel. e inclu e clim res < 5 ostitut ual re arance he se	s of w mber o redule emain . This n cap Assu de: 1 hated; = 2m/ 5%. The for quirer c of h lected te for	of minus s taile der ol ability mptio) troop 2) 50 (s; 4) his gu comm nents eat	of ns ps ide				

Tab	le 3	-12.	Wate		quirements for work/rest cycles (qt/hr) night operations).								
			морр	Zero			MOP! Unde			MOPP4 + BDU			
WBGT	Ta	VL	L	м	н	VL	L	м	н	VL	L	м	н
60	68	0.25	0.25	0.5	1.0	0.25	1.0	1.0	1.0	0.25	10	1.0	1.0
66	75	0.25	0.25	1.0	1.0	0.5	1.0	1.0	1.0	0.5	1.0	1.0	1.0
72	82	0.25	0.5	1.0	1.0	0.5	1.0	1.0	1.0	0.5	1.0	1.0	1.0
78	88	0.25	0.5	1.0	1.0	1.0	1.5	1.0	1.0	1.0	1.5	1.0	1.0
80	91	0.5	1.0	1.5	1.0	1.0	15	1.0	1.0	1.0	1.5	1.0	1.0
82	93	0.5	1.0	1.5	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
84						1.0	1.0	1.0		1.0	1.0	1.0	
86	86 97 0.5 1.0 1.0					1.0	1.0	1.0		1.0	1.0		
88	88 100 0.5 1.0 1.0				1.0	1.0				1.0			
90	102	1.0	1.0	1.0	1.0	1.0	na	na		1.0	na	na	na
92	104	1.0	1.5	1.0	1.0	1.5				1.5			
94	106	1.0	1.5	1.0	1.0	1.0 1.5 1.5							
Ta - An (Dry VL - Ve Inter L - Ligh M - Mo Inter H - Hea BDU - E NL - No Work na - Work	Wet porate bient Bulb ry Lig sity t Wor derate sity Vy W derate sity Limit c Pose ork/Re ible (S c Tim	Bulb are (°f Tern) - °F) ht Wo k Inte e Work ork In Dress t (Con sible) st Cyo See M e in Ta	=) peratu ork nsity k tensity Unifo tinuou	/m s tm	Amo schei divid wate deter work prepa USAI in ge hydra relati solar guida or ex ovide have work	dules i ed over r as it mine times ared us RIEM I neration ted, r load; ince is perien been	sted a in Tab is los is los water sing p Heat S ng est ested, midity 5) hea ce;ap nat sa excee cycle a	are reco le 3-1 rise of t to s requi vn in redict Strain imate , and ; 3) w at cas a subs peara fe wo ided (and/or	quired 1; dri each weat. red to Table ion ca Mode s incl acclin vindsp ualtie atitute nce o rk lim that ti	to su inking hour Use supp 3-13. apabili el; assi ude 1) natized sood = for co for co f heat its {<	shoul to rep Table ort ma ties o umpti troop d; 2) ! 2 m %. Th ommo casus 5% c sected	ld be blace 3-14 aximu table f the ons u of fully 50% /s; 4) is on sen alties i asualt	to m was sed no se is

.

			моря	Zero	,		MOP: Under			MOPP4 + BDU				
WBGT	T۵	VL	L	M	н	VL	L	м	н	VL	L	м	н	
60	68				188			76	42			73	41	
66	75				119			66	39			64	38	
72	82				90		NL	58	36		NL	57	36	
78	88			NL	72			53	34			52	33	
80	91				64			50	32			50	32	
82	93	NL	NL		60	NL	206	49	32	NL	168	48	31	
84	95			139	55		144	47	31		133	47	30	
86	97			107	51		121	46	30	1	115	45	29	
88	100			82	46		100	44	28		97	43	28	
90	102			71	42		91	42	27		89	42	27	
92	104			63	39		83	41	26		82	41	26	
94	106			56	36		77	40	25		76	40	25	
WBGT Tem Ta - An (Dry VL - Ve Inter L - Ligh M - Mo Inter H - Hea BDU - E NL - No Worl	971075110082461027142104633910656360 TABLE: - Wet Bulb Globe operature (°F) mbient Temperature v Bulb + °F)INST of m sing of m sing sing than nsity ht Work Intensity work Intensity avy Work Intensity but the press Uniform o Limit (Continuous k Possible)INOT sing sing subs					table (sity (s nutes word 5% ri ared u RIEM I neration ted, r ve hus load, itute dual r arance	IONS provid to Tab of we k peric sk of 1 sing the sing the rested, midity The g for col- equire to of he	es for le 3-5 ork thi od wit heat o he pre Strain s table , and ; 3) w uidan mmor ment at ca	four i), the at can hout casual dictio Mode acclin indsp co sho sons s may sualtio	lovels maxi be si excee ties. 1 n cap il. Ass ide 1) natize ced = culd n is or c vary es is c	mum ustain ding a This ta ability umpti all tro d; 2) 2 m ot be great	numb od in great blo w of th ons u oops (50% /s; 4) used once. ly. Th ce the	a tor as sed fully no as a e at	

700	10 5	74.	1010			oper							
		1	морр	Zero			MOP			MOPP4 + BDU			
WBGT	Та	VL	L	м	н	VL	L	м	н	VL	L	M	н
60	68	0.25	0.25	0.5	1.0	0.25	1.0	1.5	2.0	0.25	1.0	1.5	2.0
66	75	0.25	0.25	1.0	1.5	0.5	1.0	2.0	2.0	0.5	1.0	2.0	2.0
72	82	0.25	0.5	1.0	1.5	0.5	1.0	2.0	2.0	0.5	1.0	2.0	2.0
78	88	0.25	0.5	1.0	1.5	1.0	1.5	2.0	2.0	1.0	1.5	2.0	2.0
80	91	0.5	1.0	1.5	2.0	1.0	1.5	2.0	2.0	1.0	1.5	2.0	2.0
82	93	0.5	1.0	1.5	2.0	1.0	1.5	2.0	2.0	1.0	1.5	2.0	2.0
84	95	0.5	1.0	1.5	2.0	1.0	1.5	2.0	2.0	1.0	1.5	2.0	2.0
86	97	0.5	1.0	1.5	2.0	1.0	1.5	2.0	2.0	1.0	1.5	2.0	2.0
88	100	0.5	1.0	1.5	2.0	1.0	2.0	2.0	2.0	1.0	2.0	2.0	2.0
90	102	1.0	1.0	2.0	.20	1.0	2.0	2.0	2.0	1.0	2.0	2.0	2.0
92	104	1.0	1.5	2.0	2.0	1.5	2.0	2.0	2.0	1.5	2.0	2.0	2.0
94	106	1.0	1.5	2.0	1.5	2.0	2.0	2.0	1.5	2.0	2.0	2.0	
WBGT Tem Ta - An	VBGT - Wet Bulb Globe A Temperature (°F) m a - Ambient Temperature s				Amo max shou	INSTRUCTIONS AND NOTES: Amounts listed are required to support maximum work times in Table 3-13; drinking should be divided over course of each hour. If water requirement is 2.0, sweat loss is greater							

Table 3-14.	Water requirements for maximum til	mes (qt/hr)
	(night operations).	


WBGT - Wet Bulb Globe
Temperature (°F)
Ta - Ambient Temperature
(Dry Bulb - °F)
VL - Very Light Work
Intensity
L - Light Work Intensity
M - Moderate Work
Intensity
H - Heavy Work Intensity
BDU - Battle Dress Uniform
NL - No Limit (Continuous
Work Possible)
USARIEM 1/10/91

than maximum water absorption during an hour, and troops will become increasingly dehydrated regardless of amount drunk; leaders should plan for an extended rest and rehydration period at work completion (see Table 3-10). This table was prepared using prediction capability of the USARIEM Heat Strain Model; assumptions used in generating estimates include 1) troops fully hydrated, rested, and acclimatized; 2) 50% relative humidity; 3) windspeed = 2 m/s; 4) no solar load; 5) heat casualties <5%. This guidance is not a substitute for common sense or experience; appearance of heat casualties is evidence that safe work limits (casualties) have been exceeded.

Table 3-15	Table 3-15. Wind speed effects on arrival time of chemical agents.								
Wind speed (kmph)	Time before agent reaches unit location (seconds)	Distance between unit and detectors (maters)							
5	108	150							
10	54	150							
15	36	150							
20 27 150									
25	22	150							

Table 3-16. Detectors required for different size unit fronts.		
Unit front size (in meters)	Number of detector units	
1-35	1	
37-372	2	
373-708	3	
709-1,044	4	
1,045-1,380	5	

Average air temperature		Maximum number of 12-hour mission	
۴F	°C	BB501/U	BA3517/U
120-90	50-32	14	6
80	27	12	8
70	21	12	8
60	15	10	5
50	10	9	3
40	4	8	2
32	0	6	1
20	-4	5	1
10	-13	3	Do not use below 20°F (-4°C)
0	-17	2	
-10 to -40	-22 to -40	1	






Figure 3-1. Fixed emplacement of M8A1 alarms.

CAM

There are eight bar indicators: one to three bars = low vapor hazard, four to six bars = low vapor hazard, four to six bars = high vapor hazard, and seven to eight bars = very high levels of vapor hazard.

Table 3-18. Co	mmon Interferents fo	or the CAM
Interferent	G bar response	H bar response
M258A1 decon kit		High
M280 DKIE		High
DS2	Low	
Insect repellant	Low-Very high	
Brake fluid	High-Very high	Very high
Cleaner, general purpose	High	
Burning kerosene		High
Breath mints	High	
Gasoline vapor	Low	Low
Burning grass	Low-High	Low
Burning gas	Low	

Unmasking Procedures

Without detection equipment

1. In a shady area, have one or two soldiers take a deep breath, hold it, and break their mask seals for 15 seconds with their eyes open.

2. Have them clear and reseal masks. Observe them for 10 minutes for symptoms.

3. If no symptoms appear, have the same soldiers break their mask seals, take two or three breaths, clear and reseal their masks. Observe them for 10 minutes for symptoms.

4. If no symptoms appear have the same soldiers unmask for 5 minutes and then remask. If no symptoms appear in 10 minutes, it is safe to give the all clear signal and unmask.

5. Continue to observe the soldiers in ease delayed symptoms develop.

With M256 or M256A1 Detector Kit

1. Test with the detector kit.

2. If the test is negative, have one or two soldiers move to a shady area if possible, and unmask for 5 minutes. Have the soldiers remask. Observe them for 10 minutes for symptoms.

3. If no symptoms appear, it is safe to give the all clear signal and unmask. The senior leader present may ask higher headquarters for permission.

4. Continue to watch soldiers for possible delayed symptoms.

Using Estimated Wait Times Before Executing Open/Unmasking Time Tables

NOTE: All tables are ICT 5 risk level (Incapacitating dosage of vapor sufficient to disable 5% of exposed soldiers).

Formula Procedure

a. Variables

P = Percent of worst case time remaining

O = Original worst case time from table

N = New worst case time from table

T = Time between original estimate and weather change

U = Updated worst case time

b. Procedure.

Read O directly from table

Weather change:

P = (O-T)/OU = PxN

Weather changes again:

Set O = USet T = time since last weather change

Repeat as required

Agent: GA/GF Terrain: Sand The numnbers in	the chart repr	esont h	ours.						
Wind Speed	Stability			Te	mpera	turo (°F)		
КМРН	Sibbility	50	60	70	80	90	100	110	120
	Unstable	60+	53	33	20	13	10	8	5
0-10	Neutral	60+	60+	45	28	18	13	8	5
	Stable	60+	60 ÷	58	38	23	15	10	8
	Unstable	13	8	5	3	3	2	2	2
11-24	Neutral	20	13	8	5	5	з	2	2
	Stable	20	13	8	S	5	3	2	2
>=25	Neutral	2	2	2	2	2	2	2	2

1. Worst case MOPP open time-information in the table indicates the time for GA/GF to weather below 5 percent incidence of incapacitation due to vapor-on-skin effects. DO NOT OPEN MOPP WITHOUT FOLLOWING MOPP OPENING PROCEDURES!

Opening the MOPP suit-unzip and/or unsnap MOPP clothing; do not remove.

3. When the actual temperature is between two listed temperatures, enter the table with the lower temperature. To get times for gress terrain, multiply numbers in the chart by 0.4. DO NOT INTERPOLATE!

4. See FM 3-8 for definition of stability categories.

Agent: GA/GF Terrain: Sand The numnbers in	the chart repr	resent h	ours,						
Wind Speed	Co-billion			Te	mperat	ture (°	F)		
кмрн	Stability	50	60	70	80	90	100	110	120
	Unstable	60+	60+	60+	55	35	25	15	13
0-10	Neutral	60 +	60 +	60 +	60 +	45	30	20	13
0.10	Stable	60+	60+	60+	60 +	55	35	23	15
	Unstable	60 +	60+	60+	38	23	15	10	8
11-24	Neutral	60+	60+	60+	43	28	18	13	10
11-24	Stable	60 +	60+	60 +	45	30	20	13	10
> = 25	Neutral	60 +	60 +	35	23	15	10	8	5

1. Worst case MOPP open time-information in the table indicates the time for GA/GF to weather below 5 percent incidence of incapacitation due to vapor-on-skin effects. DO NOT OPEN MOPP WITHOUT FOLLOWING MOPP OPENING PROCEDURES!

2. Opening the MOPP suit-unzip and/or unsnap MOPP clothing; do not remove.

3. When the actual temperature is between two listed temperatures, enter the table with the lower temperature. To get times for grass terrain, multiply numbers in the chart by 0.4, DO NOT INTERPOLATE!

4. See FM 3-6 for defination of stability categories.

Table 3-21. Estimated worst case MOPP open unmasking times.

Agent: GA/GF Terrain: CARC The numnbers in the chart represent hours.

Wind Speed	Stability			Te	mpera	ture (°F)		
КМРН	Classify	50	60	70	80	90	100	110	120
	Unstable	1.25	0.75	0.50	0.25	0.25	0.25	0.25	0.25
0-10	Neutral	1.50	1.0	0.50	0.50	0.25	0.25	0.25	0.25
0.10	Stable	1.50	1.0	0.50	0.50	0.25	0.25	0.25	0.25
	Unstable	0.75	0.50	0.25	0.25	0.25	0.25	0.25	0.25
11-24	Neutral	0.75	0.50	0.25	0.25	0.25	0.25	0.25	0.25
11-24	Stable	1.0	0.50	0.50	0.25	0.25	0.25	0.25	0.25
> = 25	Neutral	0.50	0.50	0.25	0.25	0.25	0.25	0.25	0.25

NOTES:

1. Worst case MOPP open/unmasking time—information in the table indicates the time for GA/GF to weather below 5 percent incidence of incapacitation due to vapor-on-skin and inhalation. DO NOT OPEN MOPP WITHOUT FOLLOWING MOPP OPENING PROCEDURES! DO NOT UNMASK WITHOUT FOLLOWING UNMASKING PROCEDURES

Opening the MOPP suit—unzip and/or unsnap MOPP clothing; do not remove.

3. When the actual temperature is between two listed temperatures, enter the table with the lower temperature. To get times for grass terrain, multiply numbers in the chart by 0.4. DO NOT INTERPOLATE!

4. If soldiers are working on vehicles, avoid skin contact with the vehicle.

5. See FM 3-6 for definition of stability categories.

6. For planning, ensure the following steps are taken:

a. Remove as much earth and debris as possible from the CARC painted surface and conduct operator spraydown.

 Above times are estimated weathering times for CARC painted surfaces; confine contamination-free status by using detection devices before MOPP reduction.

c. If possible, move uncontaminated equipment from the contaminated area.

 Anything not painted with CARC (such as concrete, plastics, and weapons) must be individually checked for contamination.

Agent: HD Terrain: Sand The numnbers in	the chart rep	resent h	ours.						
Wind Speed	Cashillar			Te	mpera	ture (°	F)		
КМРН	Stability	50	60	70	80	90	100	110	120
	Unstable	60+	60+	60+	60+	48	32	23	15
0-10	Neutral	60+	60+	60+	60+	60 +	43	28	20
0-10	Stable	60+	60+	60+	60+	60+	58	38	25
	Unstable	60+	60+	43	28	18	13	8	5
11-24	Neutral	60+	60+	60+	38	25	18	10	8
11-24	Stable	60+	60+	60+	40	28	18	13	8
>=25	Neutral	33	20	13	8	5	5	3	3

NOTES:

1. Worst case MOPP open time-information in the table indicates the time for HD to weather below 5 percent incidence of incapacitation due to vapor-on-skin effects. To get times for grass terrain, multiply numbers in the chart by 0.4. DO NOT OPEN MOPP WITHOUT FOLLOWING MOPP OPENING PROCEDURES!

2. Opening the MOPP suit-unzip and/or unsnap MOPP clothing; do not remove.

3. When the actual temperature is between two listed temperatures, enter the table with the lower temperature. DO NOT INTERPOLATE!

4. See FM 3-6 for definition of stability categories.

Table 3	-23. Estima	ated w	orst	Case	unm	askin	g tím	18S.	
Agent: HD Terrain: Send The numnbers in	the chart rep	resent h	lours.						
Wind Speed	Stability			Te	mpera	ture (°	F}		
KMPH	Stability	50	60	70	80	90	100	110	120
	Unstable	60+	60+	60+	60+	53	35	23	18
0-10	Neutral	60+	60+	60+	60+	60+	48	33	23
	Stable	60+	60+	60+	60+	60+	60+	45	28
	Unstable	60+	60	58	38	25	15	10	8
11-24	Neutral	60+	60+	60 +	50	33	23	15	10
11-24	Stable	60+	60+	60+	53	35	23	15	10
>=25	Neutral	53	33	20	13	8	5	5	3

NOTES:

1. Worst case unmasking time-information in the table indicates the time for HD to weather below 5 percent incidence of incapacitation due to inhalation. To get times for grass terrain, multiply numbers in the chart by 0.4. DO NOT UNMASK WITHOUT FOLLOWING UNMASKING PROCEDURES!

2. When the actual temperature is between two listed temperatures, enter the table with the lower temperature. TDO NOT INTERPOLATE!.

3. See FM 3-6 for definition of stability categories.

Table 3-24.	Estimated worst case
MOPP ope	an/unmasking times.

Agent: HD Terrain: CARC

The numnbers in the chart represent hours.

Wind Speed	Cashillion		Temperature (°F)									
КМРН	Stability	50	60	70	80	90	100	110	120			
	Unstable	11	7	5	3	2	2	1	1			
0-10	Neutral	12	8	5	4	2	2	1	1			
0.10	Stable	13	8	5	4	2	2	1	1			
	Unstable	7	5	3	2	2	1	1	1			
11-24	Neutral	8	5	3	2	2	1	1	1			
11-24	Stable	8	5	3	2	2	1	1	1			
>=25	Neutral	5	3	2	1	1	1		1			

NOTES:

1. Worst case MOPP open/unmasking time-information in the table indicates the time for HD to weather below 5 percent incidence of incapacitation due to vapor-on-skin and inhalation. DO NOT OPEN MOPP WITHOUT FOLLOWING MOPP OPENING PROCEDURES! DO NOT UNMASK WITHOUT FOLLOWING UNMASKING PROCEDURES!

2. Opening the MOPP suit-unzip and/or unsnap MOPP clothing; do not remove.

When the actual temperature is between two listed temperatures, enter the table with the lower temperature. DO NOT INTERPOLATE!

4. If soldiers are working on vehicles, avoid skin contact with the vehicle.

5. See FM 3-6 for definition of stability categories.

6. For planning, ensure the following steps are taken:

 Remove as much earth and debris as possible from the CARC painted surface and conduct operator spraydown.

 Above times are estimated weathering times for CARC painted surfaces; confine contamination-free status by using detection devices before MOPP reduction.

c. If possible, move uncontaminated equipment from the contaminated area.

Table 3-25.	Estimated worst case
MOPP ope	en/unmasking times.

Agent: VX Terrain: Sand

The numnbers in the chart represent hours.

Wind Speed	Cashillan			Te	mperat	ture (°	'F)		
КМРН	Stability	50	60	70	80	90	100	110	120
	Unstable	60 +	55	50	45	36	26	17	8
0-10	Neutral	60 +	60+	60+	60+	49	38	26	15
0-10	Stable	60+	60 +	60+	45	51	41	32	23
	Unstable	60+	55	50	45	35	25	15	5
11-24	Neutral	60 +	60+	60 +	60 +	48	35	23	10
11-24	Stable	60+	60+	60+	60 +	49	38	26	15
> = 25	Neutral	60+	60+	60+	60 +	47	34	21	8

NOTES:

 Worst case MOPP open time-information in the table indicates the time for VX to weather below 5 percent incidence of incapacitation due to vapor-on-skin and inhalation. DO NOT OPEN MOPP WITHOUT FOLLOWING MOPP OPENING PROCEDURES! DO NOT UNMASK WITHOUT FOLLOWING UNMASKING PROCEDURES!

2. Opening the MOPP suit-unzip and/or unsnap MOPP clothing; do not remove.

3. When the actual temperature is between two listed temperatures, enter the table with the lower temperature. To get times for grass terrain, multiply numbers in the chart by 0.4. DO NOT INTERPOLATE!

4. See FM 3-6 for definition of stability categories.

Table 3-26. Estimated worst case MOPP open/unmasking times.

Agent: VX Terrain: CARC The numbers in the chart represent hours.

Wind Speed	Stability			Те	mpera	ture (°F)		
кмрн		50	60	70	80	90	100	110	120
	Unstable	8.25	5.25	3.5	2,25	1.5	1	0.75	0.5
0-10	Neutral	8	5	3.25	2	1.25	1	0.75	0.5
	Stable	9.25	6	3.75	2.5	1.5	1	0.75	0.5
	Unstable	5	3	2	1.25	0.75	0.5	0.25	0.25
11-24	Neutral	5	3.25	2	1.25	0.75	0.5	0.5	0.25
	Stable	5.75	3.5	2.25	1.5	ĩ	0.75	0.5	0.25
> = 25	Neutral	3.25	2	1.25	0.75	0.5	0.5	0.25	0.25

NOTES:

1. Worst case MOPP open/unmasking time-information in the table indicates the time for VX to weather below 5 percent incidence of incapacitation due to vapor-on-skin and inhalation. DO NOT OPEN MOPP WITHOUT FOLLOWING MOPP OPENING PROCEDURES! DO NOT UNMASK WITHOUT FOLLOWING UNMASKING PROCEDURES!

2. Opening the MOPP suit-unzip and/or unsnap MOPP clothing; do not remove.

When the actual temperature is between two listed temperatures, enter the table with the lower temperature. DO NOT INTERPOLATE!

If soldires are working on vehicles, avoid skin contact with the vehicles.

5. See FM 3-6 for definition of stability categories.

6. For planning, ensure the following steps are taken:

 Remove as much earth and debris as possible from the CARC painted surface and conduct operator spraydown.

b. Above times are estimated weathering times for CARC painted surfaces; confine contamination-free status by using detection devices before MOPP reduction.

c. If possible, move uncontaminated equipment from the contaminated area.

 Anything not painted with CARC (such as concrate, plastics, and weapons) must be individually checked for contamination.

Table 3-	27. Estimate	ed wo	rst c	ase I	иорі	o ope	en tin	ies.	
Terrain: Sand The numnbers in	the chart repre	sent ho	ours.					_	
Wind Speed	Stability			Te	mpera	ture (°F}		
КМРН	Stability	50	60	70	80	90	100	110	120
0-10	Unstable	8	6	4	3	3	3	3	3
	Neutral	8	7	6	5	4	4	3	3
0.10	Stable	25	22	18	15	13	10	8	5
	Unstable	3	3	3	3	3	3	3	3
11-24	Neutral	5	4	3	3	3	3	3	3
11-24	Stable	5	4	3	3	3	3	3	3
> = 25	Neutral	3	3	3	3	3	3	3	3

NOTES:

 Worst case MOPP open time-information in the table indicates the time for TGD to weather below 5 percent incidence of incapacitation due to vapor-on-skin effects. DO NOT OPEN MOPP WITHOUT FOLLOWING MOPP OPENING PROCEDURES!

2. Opening the MOPP suit—unzip and/or unsnap MOPP clothing; do not remove.

3. When the actual temperature is between two listed temperatures, enter the table with the lower temperature. To get times for grass terrain, multiply numbers in the chart by 0.4. DO NOT INTERPOLATE!

4. See FM 3-6 for definition of stability categories.

Table 3-2	28. Estimato	ed wo	rst ca	ase U	NM/	ISKII	VG ti	mes.	
Agent: TGD Terrain: Send The numnbers in	the chart repr	esent h	ours,						
Wind Speed	Carbillar			Ter	mpera	turo (°F)		
КМРН	Stability	50	60	70	80	90	100	110	120
0-10	Unstable	60	46	32	18	14	10	6	3
	Neutral	60 +	53	47	40	33	25	18	10
0-10	Stable	60+	60+	60+	60	48	36	24	13
	Unstable	25	18	12	5	4	4	3	3
11-24	Neutral	60	45	30	15	12	9	6	3
11-24	Stable	60	45	30	15	12	9	6	3
> = 25	Neutral	18	12	7	3	3	3	3	3
NOTES:									

1. Worst case MOPP open time-information in the table indicates the time for TGD to weather below 5 percent incidence of incapacitation due to vapor-on-skin effects. DO NOT UNMASK WITHOUT FOLLOWING UNMASKING PROCEDURES!

2. When the actual temperature is between two listed temperatures, enter the table with the lower temperature. To get times for grass terrain, multiply numbers in the chart by 0.4. DO NOT INTERPOLATE!

3. See FM 3-6 for definition of stability categories.

Agent: TGD Terrain: CARC The numnbers in	the chart repre	esent he	ours.						
Wind Speed Stability Temperature (°F)									
КМРН	Stability	50	60	70	80	90	100	110	120
0-10	Unstable	1.75	1	0.75	0.5	0.25	0.25	0.25	0.25
	Neutral	1.75	1	0.75	0.5	0.25	0.25	0.25	0.25
	Stable	2	1.25	0.75	0.5	0.25	0.25	0.25	0.25
	Unstable	1	0.75	0.5	0.25	0.25	0.25	0.25	0.25
11-24	Neutral	1	0.75	0.5	0.25	0.25	0.25	0.25	0.25
	Stable	1.25	0.75	0.5	0.25	0.25	0.25	0.25	0.25
> = 25	Neutral	0.75	0.5	0.25	0.25	0.25	0.25	0.25	0.25

NOTES:

1. Worst case MOPP open time-information in the table indicates the time for TGD to weather below 5 percent incidence of incapacitation due to vapor-on-skin effects. DO NOT OPEN MOPP WITHOUT FOLLOWING MOPP OPENING PROCEDURES!

Opening the MOPP suit—unzip and/or unsnap MOPP clothing; do not remove.

3. When the actual temperature is between two listed temperatures, enter the table with the lower temperature. DO NOT INTERPOLATE!

If soldiers are working on vehicles, avoid skin contact with the vehicles.

5. See FM 3-6 for defination of stability categories.

6. For planning, ensure the following steps are taken:

 Remove as much earth and debris as possible from the CARC painted surface and conduct operator spraydown.

b. Above times are estimated weathering times for CARC painted surfaces; confine contamination-free status by using detection devices before MOPP reduction.

c. If possible, move uncontaminated equipment from the contaminated area.

 Anything not painted with CARC (such as concrete, plastics, and weapons) must be individually checked for contamination.

Agent: TGD Terrain: CARC The numnbers in	the chart tepr	esent he	ours,						
Wind Speed Stability Temperature (°F)									
КМРН	Stability	50	60	70	80	90	100	110	120
	Unstable	3.25	2	1.25	0.75	0.5	0.25	0.25	0.25
0-10	Neutral	3.25	2	1.25	0.75	0.5	0.25	0.25	0.25
	Stable	3.5	2.25	1.5	1	0.5	0.5	0.25	0.25
	Unstable	2	1.25	0.75	0.5	0.25	0.25	0.25	0.25
11-24	Neutral	2	1.25	0.75	0.5	0.25	0.25	0.25	0.25
	Stable	2.25	1.25	1	0.5	0.25	0.25	0.25	0.25
> = 25	Neutral	1.25	0.75	0.5	0.25	0.25	0.25	0.25	0.25
weather below 5 pe NOT UNMASK WITH 2. When the actuation with the lower temp	HOUT FOLLOW! I temperatura is	of incaps NG UNM botween DT INTER	citation ASKIN two lin IPOLAT	n due t G PRO Ited te IE!	o vapo CEDUR mporat	i-an-sk IES! ures, e	in offer nter th	cts. DC)

- See FM 3-6 for defination of stability categories.
- 5. For planning, ensure the following steps are taken:

 Remove as much earth and debris as possible from the CARC painted surface and conduct operator spraydown.

 Above times are estimated weathering times for CARC painted surfaces; confine contamination-free status by using detection devices before MOPP reduction.

c. If possible, move uncontaminated equipment from the contaminated area.

d. Anything not painted with CARC (such as concrete, plastics, and weapons) must be individually checked for contamination.

Decontamination Resources Available at Each Level of Organization

Individual Soldiers

- One M258Al or M291 skin decon kit.
- One canteen of water.

Operators and crews

- One onboard M11 decon apparatus or M13 decon apparatus, portable (DAP), for major pieces of equipment.
- Soap and water, M258A1 or M291 kits as needed for decon of sensitive or vulnerable surfaces.
- HTH mixture or bleach.
- M280 or M295 decon kit.

Company Level

- One 50-pound drum of STB.
- Two 5-gallon pails of DS2 or 2 M13 DAPs.
- Six long-handled brushes.
- 300 plastic garbage bags.
- Six 3-gallon buckets.
- Six large sponges.
- Two 32-gallon galvanized trash cans (from mess section).
- Two immersion heaters (from mess section).

Battalion PDDE Crews

- Power-driven decontaminating equipment (PDDE) or light weight decon system (LDS).
- Basic load liquid detergent.

Chemical Company Decon Squad

- Ten 5-gallon pails of DS2, or M13 DAPs, per M12A1 (IAW CTA 50-970).
- Twenty-six 50-pound drums of STB per M12A1 (IAW CTA 50-970).
- Power-driven decon equipment.
- Basic load of liquid detergent.

Chemical Company Decon Platoon

- 5-gallon pails of DS2 or M13 DAPs, per M12A1 or M17 LDS (IAW CTA 50-970).
- 50-pound drums of STB per M12A1 (IAW CTA 50-970).
- Power-driven decon equipment or M17 light decon system (dual purpose platoon only).
- Basic load of decontaminants.

Levels of Decontamination

There are three levels of decon: immediate, operational, and thorough.

Immediate Decon minimizes casualties, saves lives, and limits the spread of contamination. Immediate decon is carried out by individuals upon becoming contaminated. There are three immediate techniques: skin decon, personnel wipedown, and operator's spray down.

Operational Decon sustains operations, reduces the contact hazard, and limits the spread of contamination to eliminate the necessity or reduce the duration of wearing MOPP gear. Operational decon is carried by individual and/or units. It is restricted to specific parts of operationally essential equipment/material and/or working areas, in order to minimize contact and transfer hazards and to sustain operations. Further decon may be required to reduce contamination to negligible risk levels. There are two operational decon techniques: vehicle washdown and MOPP gear exchange.

Thorough Decon reduces or eliminates the need for individual protective clothing. Thorough decon is carried out by units with assistance from chemical units to reduce contamination on personnel, equipment/material, and/or working areas to the lowest possible level (negligible risk) to permit the

reduction or removal of individual protective equipment and maintain operations with minimal degradation. This may include decontamination of terrain as required. There are three thorough decon techniques: detailed troop decon, detailed equipment decon, and detailed aircraft decon.

The three levels of decon--immediate, operational, and thorough-are presented as part of this chapter to explain the seven standard decon techniques used for most decon operations. Your chemical officer or NCO advises on efficient ways to conduct operational or thorough decon operations. For example, conducting decon operations might require the use of one or a combination of the seven decon techniques.


Level	Technique	Best Start Time*	Done By	Gains	
	Skin Decon	Before 1 minute	Individual		
Immediate	Personal Wipedown	Within 15	Individual or	Stops agent from penetrating	
	Operator Spraydown	minutes	Crew		
	MOPP Gear Exchange**		Unit	Possible temporary	
Operational	Vehicle Washdown***	Within 6 hours	Battalion Crew or decon PLT (-)	relief from MOPP4. Limit liquid egent spread.	
Thorough	Detailed Equipment/Air- craft Decon	When mission allows	Decon platoon	Probable long-term MOPP	
	Detailed Troop Decon	reconstitution	Unit	reduction with minimum risk	
** Perform exceeding 6 h *** Vehicle	hniques become inc ance degredation a ours. See FM 3-4, I washdown is most r logistical reasons.	nd risk assessment BDO risk assessmen	need to be conside nt.	red when	

Operational Decontamination

Та	able 3-32.	Operationa	l decon resp	onsibilit	y matrix		
			Unit				
Pł	1850	Task	Contaminated Unit	Battalion PDDE Crew	Battalion	Brigade	
Planning	Preparation	Request	Р		S		
	Coordination			P	S		
		Site Selection	Р		S		
		Rendezvous	Р		S		
		Site Setup	S	Р			
	Execution	Site Control and Security	P				
		Processing	Р	S			
	Site	Cleanup		Р			
	Clearance	Marking and Reporting		Р			
Legend:	P = Primary r	esponsibility,	S = Supporting re	esponsibility	/		

	Table 3-33	. Sample operational decon checklist.
	Task	Procedure
1	Decon assessmnet	If the battalion has no decon assets, request assistance from the next higher headquarters for needed support.
2	Coordination	Battalion chemical section conducts coordination with contaminated unit on where to meet. The decon should be done between one to six hours after becoming contaminated.
3	Site selection	The contaminated unit chooses the decon site in coordination with the battalion. Consider the following items when selecting a site: • Off main route but easy access • Large enough area, (100 square meters per site for a squad-size element) • Good overhead concealment • water source, (plan for 100 gallons per vehicle) • Good drainage
4	Rendezvous	Ensure the battalion decon crew knows where to meet the contaminated unit, and site location for set up.
5	Site setup	Ensure the PDDE are positioned properly and ready to dispense hot, soapy water. Ensure that the contaminated unit operates the MOPP gear exchange at the same time as the vehicle washdown.
6	Site control and security	Ensure the drivers of the contaminated vehicles know when to move into position at the washdown location. Ensure the contaminated unit has provided site security.
7	Processing	Ensure the decon NCOIC is processing vehicles at a rate of three minutes per vehicle. Also ensure soldiers are going through the MOPP gear exchange, if needed.
8	Cleanup	Decon NCOIC ensures the MOPP gear exchange area is cleaned up.
9	Marking and reporting	Decon NCOIC has his team properly mark the decon site and send NBC 5 report forward.

Steps and Risks	Equipment	Procedure
Step 1. Button up vehicle/equipment. Performing this step prevents contamination from being washed or splashed into uncontaminated areas. Risks. Failure to perform this step may result in contamination being washed into uncontaminated areas, subjecting crew and maintenance personnel to hazards.	None	Equipment crew/operators close all access doors, hatches, windows, and other openings before washdown. Put muzzle covers on weapons. Nonessential personnel can dismount and begin MOPP gear exchange. They then act as "buddies" for essential crew/operators. NOTE: Ensure that vehicles equipped with over pressurized systems are operating with system on.
Step 2 Washdown wehicle/equipment. Performing this step limits spread of contamination, minimizes hazards, and enhances weathering to make detailed equipment decon easier and faster. Risks. If you do not do this step, expect casualties from contact hazards. Spreading or transferring the hazard most likely will increase. Weathering of the hazard most likely will increase. Weathering of the hazard most likely will be slowed. You will not be able to reduce MOPP level immediately because an after-vehicle washdown check for contamination is not made. (See decon in combat, Chapter 1, for when to unmask for brief periods.)	Use for all forms of contamination: • One PDDE. • Adequate fuel for water heater (if available) and pump unit. • Adequate water supply (about 100 to 150 gallons per vehicle). • Liquid detergent to mix with water (see Appendix J).	Chemical, biological, and radiological: Two soldiers from the battalion PDDE crow operates washdown equipment. A third soldier supervises. Soldiers must wear toxicological agent protective (TAP) aprons or wet weather gear worn over MOPP gear to keep MOPP gear from becoming saturated. Soldiers spray hot, soapy water (under pressure) from PDDE onto equipment surfaces. This removes, neutralizes, or destroys most of the gross contamination trapped in dirt and mud. Unheated soapy water or plain water may be used, if necessary, but is less effective than hot, soapy water. Start at the top decks of vehicles and wash downward.






Figure 3-2. Unsupported one-lane washdown.

Table 3-35. Uns	upported two	o lane washdown
Steps and Risks	Equipment	Procedures
Preaction: Unit tactically disperses in concealed marshalling area. Makes contact with control point for final orders. Control point monitors and supervises rate of movement into lanes to prevent congestion.	Watch	One soldier from the battalion decon crew. Every three minutes two vehicles will be released from the marshalling area. On signal vehicles will proceed to the decon station in their respective lane.
 Step 1. Button up vehicle/equipment. Performing this step provents contamination from being washed or splashed into uncontaminated areas. This step applies for both lanes. Risks. Failure to perform this step may result in contamination being washed into uncontaminated areas, subjecting crew and maintenance personnel to hazards. 	None	Equipment crew/operators close all access doors, hatches, windows, and other openings before washing down. Put muzzle cover on weapons. Nonessential personnel can dismount and begin MOPP gear exchange upon commander's orders. They they can act as "buddies" for essential crew/operators. NOTE:: Ensure that vehicles equipped with overpressurized systems are operating with the systems on. No MOPP gear exchange is required if crew/operators are inside vehicle and have not been exposed to any contamination.
Step 2. Wash down vehicles/equipment. Crews/drivers remain in vehicles. Sprayers use cross diagonal technique for two to three minutes, removing gross contamination. This technique avoids water splasting the crew members. Performing this step limits the spread of contamination, minimizes bazard, and enhances weathering to make detailed equipment decon easier and faster.	 Adequate fuel for water heater lif available) and pump unit. Adequate water supply (about 100 to 150 gallons per vehiclo). Liquid detergent to mix with water (see Appendix F). NOTE: Use M12 PDDA, M17 LDS, 65-GPM pump, fire-fighting equipment, and/or combination. 	Chemical, biological, and radiological: Two soldiers per lane from the battalion decon crew wash down equipment. A third soldier supervises. Soldiers must wear TAP aprons or wet weather gear over MOPP gear to keep MOPP gear from becoming saturated. Soldiers spray hot, soapy water (under pressure) from PDDE onto equipment surfaces. This removes, neutralizes, or destroys most of the gross contamination trapped in dirt and mud. Unheated soapy water or pipain water may be used, if necessary, but is less effective than hot, soapy water. Start at the top decks of vehicles and wash downward.
Step 3. Vahicles move into assembly area. MOPP gear exchange is determined by the commander		Exchange MOPP suit.




Figure 3-3. Unsupported two lane washdown

Table 3-36. S	upported two-lan	ne washdown.
Steps and Risks	Equipment	Procedures
Preaction: Unit tactically disperses in a concealed marshalling area. Make contact with control point for final instructions. Control point monitors and supervises rate of movement into lanes to prevent congestion.	Watch	One soldier from the battalion decon crew required. Two vehicles will be released from the marshalling area every three minutes. On signal vehicles will proceed to the decon station in theor respective lane.
Step 1. Button up vehicle/equipment. Performing this step provents contamination from being washed or splashed into uncontaminated areas. This step applies to both lanes. Risks. Failure to perform this step may result in contamination being washed into uncontaminated areas, subjecting crew and maintenance personnel to hazards.	None	Equipment crew/operators close all access doors, hatches, windows, and other openings before washdown. Put muzzle covers on weapons. Nonessential personnel can dismount and begin MOPP gear exchange, upon commander's orders. They then act as "buddies" for essential crew/operators. NOTE: Ensure that vehicles equipped with overpressurized systems are operating with systems on.
Step 2. Wash down vehicles/equipment. Craws/drivers remain in vehicles. Vehicles stop by the first wash. Sprayers decon half of the vehicle/equipment facing their side, for one and one-half minutes. Vehicles then move to the second wash where sprayers will decontaminate the other half of the vehicle/equipment for one and one-half minutes.	 3 M17 LDS. Adequate fuel for water heater and pump units. Asequate water supply (approximately 100 to 150 gallons per wash point per vehicle). Liquid detargents to mix with water. NOTE: Use M12 PDDE, M17 LDS, 65-GPM pump, fire-fighting equipment, and/or combination. 	Chemical, biological, and radiological: Four soldiers from the chemical decon platoon wash down equipment. A fifth soldier supervises. Soldiers must wear TAP aprons or wet weather gear worn over MOPP gear to keep from becoming saturated. Soldiers spray hot, soapy water (under pessure) from PDDE onto equipment surfaces. Start at the top decks of vehicles and wash downward.
Step 3. Vehicles move into assembly area. MOPP gear exchange is determined by the commander.		Exchange MOPP suit.




Figure 3-4. Supported two-lane washdown.

	MOPP Gear Exchange			
Step	Procedure			
1.	Decontaminate gear.			
2.	Prepare for Decontamination.			
3.	Decontaminate hood			
4.	Remove overgaments and overshoes.			
5.	Remove gloves.			
6.	Put on overgaments.			
7.	Put on overboots and gloves.			
8.	Secure hood.			

Steps and Risks	Equipment	Procedures
STEP 1 DECON GEAR. Performing this step removes gross contamination from individual gear (weapon, helmet, load-bearing equipment, and mask carrier). RISKS. If you do not do this step, you will transfer contamination from your individual gear to your new MOPP gear. You will have to change MOPP gear within 24 hours, even if you do not receive any more contamination. If chemical/biological contamination is not removed from individual gear, the weathering process will be delayed (see FM 3-4). If radiological contamination is not removed, your radiation exposure may increase over time, prolonging the time you must remain in MOPP gear.	ALL CONTAMINATION: • Four long-handled brushes. • Large piece of plastic (poncho or similar material) CHEMICAL/BIO- LOGICAL: • One 5-gallon container STB dry mix. RADIOLOGICAL: None.	CHEMICAL/BIOLOGICAL: If the personnel armor system, ground troops (PASGT) helmet is worn, remove and discard the chemical protective helmet cover. Brush or rub STB into personal equipment. Brush or rub STB dry mix onto hose if wearing the M24, M25A1, or M42 mask. Gently shake off any excess. Set aside gear on an uncontaminated surface. RADIOLOGICAL: Shake or brush contamination off.
STEP 2. PREPARE FOR DECON. Performing this step allows the soldier to remove his overgarment trousers and boots later. It also allows for the hood to be rolled easier. NOTE: A soldier can do this step by himself or with the help of his buddy.	ALL CONTAMINATION: • Cutting tool.	Unfasten the shoulder straps on the hood and pull them over the shoulder and reattach them to the Velcro ® fastener. Loosen drawcord on hood of protective mask. Remove M9 paper. Untie drawcords on trouser legs of the garment, unzip the trouser legs, and roll a cuff in each leg. Ensure that the cuff does not come over the top of the overboot. Unfaster or cut fasteners on green vinyl overboots or untie/cut the laces on the protective overboot.

Table 3-37. MOPP gear exchange (buddy team method) (Continued).					
Steps and Risks	Equipment	Procedures			
STEP 3 DECON HOOD. Performing this step removes the gross contamination from the mask and hood. The squad leader and companion or two personnel from the squad stand in the center of a circle. They supervise the other teams while they go through the technique themselves. RISKS: CHEMICAL/BIOLOGICAL CONTAMINATION. If this step is not done, small amounts of contamination may still be on the mask and hood. You will risk spreading contamination to your skin during the undressing. RISKS: RADIOLOGICAL CONTAMINATION. If you do not do this step, excessive radiation exposure could occur from contaminants on the hood and mask. You also risk spreading contamination to your skin during the undressing.		CHEMICAL/BIOLOGICAL: Using the M258A1 or M295 skin decon kit, decontaminate the hood and exposed parts of your buddy's mask. Start with the eye lens outserts, wiping from the top down. Then decon the rest of the head to the bottom of the hood. When you have finished decontaminating your buddy's mask, decontaminate your gloves in preparation for rollong your buddy's hood. (NOTE: When decontaminating the mask, do not press so hard that you break your buddy's seal). Leave the zipper on the hood closed. Grab the straps where they connect to the back of the hood and lift the hood straight up of the buddy's shoulders. Pull the hood up and over the head until the bottom of the back of the hood is to the top of the eye lens outserts, but not over. Check for contamination on the underside of the hood edges and decon if necessary. Roll your buddy's hood. Put one tuck (about two inches) on the forehead, then begin rolling at both temples simultaneously by tucking in with the thumbs as you roll toward the bottom of the zipper. M40 MASK. The contaminated soldier holds the mask firmly in place to avoid breaking the seal. Make the rolls from each side of the hood come to a point at the bottom of the zipper, forming a V. Put a half twiet in the V, forming two sides into a tail. Then tuck the tails between the upper part of the canister and mask. (Tie tail over and under the hose of the M42.) (Step 3 continues on next page.)			

Table 3-37. MOPP ge	ear exchange ((Continued).	(buddy team method)
Steps and Risks	Equipment	Procedures
STEP 3. DECON HOOD (continued)		RADIOLOGICAL: Wipe your buddy's mask and bood with sponge dipped in hot, soapy water. Rinse with sponge dipped in clean water. Dry with paper towels or rags. The buddy does his or har own gloves. Cool, soapy water is not as affective for removing contamination, but can be used if you scrub longer. Use IDK skin decon kit ONLY if no water is available. If water supply is limited, soldier may use some of his drinking water (from his canteen) with a wet sponge or cloth. Do not reverse rolls. Only your buddy's hood will be decontaminated and rolled at this time.
STEP 4. REMOVE OVERGARMENTS/OVERSHOES. Performing this step limits the spread of agents and helps prevent ogents from penetrating through to skin or undergarments. RISKS: If you do not do this step, the agent will penetrate your overgarment. The more agent on the garment, the quicker it will penetrate. If you do not do this step properly, you risk spreading the agent onto your undergarments or skin, causing cesualtics.	ALL CONTAMINATION: • Two discard containers (recommend plastic bags.)	CHEMICAL/BIOLOGICAL: Unfasten the three snaps on the back of overgarment trousers. Do this by grasping the outside overgarment jacket and unsnapping the snaps individually. Untie the drawcord at the bottom of the jacket. Unfasten the Velcro © at the wrist and unfasten. Unfasten the Velcro® closures over the zippered front of the jacket and unzip the jacket. Grasp the jacket at the shoulders. Instruct the buddy to make a fist. Pull the jacket down and away from the soldier, ensuring that the black part of the jacket ien't touched. Lay the overgarment jacket on the ground, black side up. (It will be used for the buddy to stand on later.] Carefully unfasten and unzip the trousers. Do not loosen the waist tabs. Instruct the soldier to break the seals on the overshoes by alternately stepping on the heels and pulling up his foot. Grasp the trousers and pull them down to the knees. Instruct the soldier to walk out of the trousers/GVOs, (Step 4 continues on next page.)

5

Table 3-37. MOPP gear exchange (buddy team method) (Continued).				
Steps and Risks	Equipment	Procedures		
STEP 4, REMOVE OVERGARMENTS/OVERSHOES (continued).		taking care not to step on the contaminated side of the overgarment. If wearing overboots, remove trausers first, then step out of overboots (with buddy's help) onto the black side of jacket. The soldier should step onto the jacket wearing mask, bettledress uniform (BDUs), and gloves.		
STEP 5. REMOVE GLOVES. Performing this step removes contaminated gloves and limits the spread of contamination. RISKS: If this step is not done, it is quite probable the agent will be transferred to clean overgarments (Step 6). Contamination may get on your skin because gloves, tear, rip, puncture, and wear out.	ALL CONTAMINATION: • Two discard containers (from Step 4)	Hold finger tips of the gloves and partially slide the hand out. When fingers of both hands are free, hold arms away from body and let gloves drop off.		
STEP 6. PUT ON OVERGARMENTS. Performing this step restores MOPP protection. RISKS: If you do not do this step properly, you risk contaminating your new overgarment or your skin.	ALL CONTAMINATION: • One set of chemical protective overgarments per person (correct size).	Open package containing new overgarments, but do not touch the garment. Have your buddy reach into the package and pull out the overgarment without touching the outside of the package. Your buddy puts on the trousers and jacket, festens overgarment, and leaves trouser legs open. Do not reverse roles. Only your buddy will put on clean overgarments at this time.		
STEP 7. PUT ON OVERBOOTS AND GLOVES. Performing this step restores MOPP protection. RISKS: If you do not do this step, you run the risk of becoming a casualty by touching contamination remaining on unit equipment. You risk spreading contamination to your skin or undergarments. You risk contaminating your regular combat boots.	ALL CONTAMINATION: • One set of chemical protective overboots per person. • One set chemical protective gloves per person {correct size}. • M9 paper.	Pick up a package of clean overboots and open without touching the overboots inside. Have your buddy reach into the package (without touching outside of package), remove the GVO/overboots, put them on, and fasten trousor legs. Open a package of clean gloves without touching gloves. Have your buddy remove them from package (with- out touching the outside of the package) and put them on. Put on M9 paper. Do not reverse roles. Only your buddy will put on clean overgarments at this time. Table 3-37 continued on next page.		

Table 3-37. MOPP gear exchange (buddy team method) (Continued).			
Steps and Risks	Equipment	Procedures	
STEP 8. SECURE HOOD. Performing this step restores MOPP preptection. RISKS: If you do not do this step, you risk transferring contamination to the inside of the hood.	CONTAMINATION: • One decon 1	Decontaminate your rubber gloves with M258A1 or M295 skin decon kit. Once gloves are decontaminated, unroll your buddy's hood and attach the straps and tighten neck cord. Check all zippers and ties on the hood and overgarment to ensure they are tight.	

Thorough Decon

Table 3-3	8. T	horou	igh d	econ	supp	ort n	natrix.		
					UNIT				
	DIVISION CMLO	DIVISION	BRIGADE	DISCOM	FSB	CHEMICAL UNIT	CONTAMINATED UNIT	BATTALION	SITUATION DEPENDENT
Preparation Phase Tasks									
Request	s						Р	s	
Coordination	s		s					Р	
Site Selection		So	or S			Р			
Advance Party Link-up						S	Р	s	
Site-Setup				s	s	Р	S		
	E	xecuti	on Pha	se Ta	sks				
Site Control/Security						s	Р		
Predeocn Actions						Р	S		
Processing						Р	S		
	Site	Clear	ance F	hase]	Tasks				
Cleanup						Р	Р		s
Marking & Reporting						Р			S
P = Primary Responsibility	, s	= Sup	porting	Respon	sibility				

Table 3-39. Equipment recapitulation for detailed troop decon of an average-sized company.				
Three containers (2-gallon capacity). One will hold an immersion heater,	Two books of M8 paper per squad.			
Three containers (3-gallon capacity). Four additional containers required for radiological decon.	One role of M9 paper per squad.			
Two M258A1 or M291 decon kits per person.	Four M1 chemical agent monitors (CAMs).			
Two boxes of plastic bags.	Four M8A1 automatic chemical agent alarms.			
Ten 50-pound drums of STB.	Two immersion heaters with fuel.			
One 5-pound drum of general purpose detergent.	Two shovels.			
One 1-galion container of mask sanitizing solution per ten tanks.	First aid supplies and antidotes.			
Four long-handled brushes.	One M256A1 detector kit per squad.			
Four large sponges (four additional sponges for radiological decon).	One role plastic per company.			
Four bundles of rags.	One case paper towels per company.			
Four cutting tools (scissors, knives).	Engineer tepe.			
One filter pair or filter canister per mask.	Protective mask PLL parts.			
One hood per mask.	NOTE: If only one radiacmeter is			
Three AN/PDR27 radiacmeters or AN/VDR2 (for radiological only).	available, use it at Station 5 to monitor personnel. Pile together decontaminated equipment from Station 1 and decontaminate masks from Station 7. After a squad has been monitored through Station 5, an attendant should monitor the equipment pile.			

	Table 3-40. Detailed Troop Decon personnel and equipment recapitulation.					
Station	Personnel	Equipment				
Station1 Individual Gear Decon	2 attendants 1 monitor (CAM operator)	 3 30-gallon containers 2 long-handled brushes 2 ponchos or plastic sheets 1 CAM 8 M8 detector paper 4 M256A1 kits 100 tresh bags 				
Station2 Overboot and Hood Decon	1 attendant	2 cutting tools 60 M258A1 or M295 (or one per person) 2 ponchos or plastic tarps 100 trash bags				
Station 3 Overgarment Removal	1 attendant	10 M258A1/M295 2 30-gallon containers 100 trash bags				
Station 4 Overboot and Glove Removal	1 attendant	2 30-gallon containers 100 trash bags Engineer tape Cutting tool				
Station 5 Monitor	1 attendant (CAM operator) 1 aidman (or combat lifesaver)	1 CAM 5 M8 detector paper 24 M258A1/M295				
Station 6 Mask Removal	2 ettendants	1 M8A1 chemical elerm				
Station 7 Mask Decon Point	2 attendants 1 monitor	 4 3-gallon containers 1 CAM 2 sponges 1 case paper towels 1 immersion heater w/container Mask sanitizing solution 				
Station 8 Reissue Point	Unit supply NCO Unit NBC NCO	Mask PLL				

-7

Planning Catagory	Tank	Truck	APC
Gallons of DS2	15	8	7
Minutes to apply	35	29	18

Table 3-4	Table 3-42. Preparation of decon mixtures.				
	Decon Mixtures				
Solution	1 Gallon of Water	5 Gallons of Water			
5 percent	.6 pounds STB/HTH	3.6 pounds STB.HTH			
10 percent	.75 pounds STB/HTH	4.5 pounds STB/HTH			

Table 3-43. Planning factors for the rinse station.			
Planning Catagory	Tank	Truck	APC
M12A1 Rinse (gal)	325	158	152
M12A1 Rinse (min)	12	7	9
M17 LDS (gal)*	57	42	31
M17 LDS (min)*	14	11	10
I .	* With Spray	Wands	

	nmon interferences itive readings on the	
Interferent	G-Bar Response	H-Bar response
M258A1 Decon Kit		High
M280 DKIE		High
DS2	Low	
Insect Repellent	Low-Very High	
Brake Fluid	High-Very High	Very High
Cleaner, General Purpose	High	
Burnig Kerosene		High
Breath Mints	High	
Gasoline Vepor	Low	Low
Burning Grass	Low-High	Low
Burning Gas	Low	
Green Smoke	Low	Low-High
Breakfree Oil	Low	
Ammonia	Very High	




Figure 3-5. M12A1 PDDA-equipped unit-optimum DED layout.

	5. Personnel and on num M12A1 PDD (see figu	A-equipped D	
	Personn	Equipment	
	Decon Platoon	Augmentee	Equipment
Station1 Initial Wash	1 Squad Leader 2 PODA Operators 4 Sprayers	4 Scrubbers	2 M12A1 PDDAs 2 3,000-gal Tanks 2 55-GPM Pumps 6 Long-Handled Brushes B TAP Aprons Liquid Detergent
Station 2 DS2 Application	1 Squad Leader 3 Appliers	9 Appliers	18 Long-Handled Brushes 9 MOps with Extra Mop Heads 3 30-gal Containers 9 M13 OAPs Sufficient DS2
Station 3 Wail/Interior Decon	1 NCO	2 Interior Decon Assistants	2 AN/VDR2 or AN/PDR27 () 3 TAP Aprons 6 30-gal Containers 10 M8 Detector Paper 30 Sponges 8 M256A1 50 Trash Begs 1 Clipboard w/Pen 1 Stopwatch
Station 4 Rinse	1 Squad Leader 1 PDDA Operator 2 Pump Operators	2 Sprayers	1 M12A1 PDDA 1 3,000 gal Tank 3 65 GPM Pumps 2 TPU 2 TAP Aprons
Station 5 Check	2 NCO/CAM Operations		2 CAM 10 M256A1 20 M8 Detector Paper 2 AN/VDR2 or AN/PDR27 2 M8A1 Chem Alarms
C2	1 Platoon Leader 1 Platoon Sergeant		1 HUMMWV/CUCV w/Radio 3 NBC Marking Kits
Total Personnel	20	17	




Figure 3-6. An Alternate DED layout for an M12A1 PDDA-equipped unit.

	Personnel and equip hate M12A1 PDDA-eq (see figure 3	
	Personnel	Equipment
Station 1 Initial Wash	1 NCOIC* 2 PDDA Operators* 4 Sprayers 2 Scrubbers	2 M12A1 PDDAs 2 3,000-Gallon Tanks 2 65-GAL Pumps 4 Long-Handled Brushes 6 TAP Aprons Liquid Detergent
Station 2 DS2 Application	1 NCOIC* 8 Appliers	14 Long-Handled Brushes 8 Mops with Extra Mop Heads 3 30-Gallon Containers 8 M13 DAPs Sufficient DS2
Station 3 Wait/Interior Decon	1 NCO* 2 Interior Decon Assistants	2 AN/VDR2 or AN/PDR27 3 TAP Aprons 6 30-Gallon Containers 10 M8 Detector paper 30 Sponges 8 M256A1 50 trash Bags 1 Clipboard w/Pen 1 Stopwatch
Station 4 Rinse	1 NCOIC* 1 PDDA Operator* 2 Sprayers	1 M12A1 PDDA 1 3,000-Gallon Tank 1 65-GPM Pump 1 TPU 2 TAP Aprons
Station 5 Check	2 NCO/CAM Operators*	2 CAMs 10 M256A1 20 M8 Detector Paper 2 AN/VDR2 or AN/PDR27 2 M8A1 Chem Alarms
C2	1 Platoon (Decon Platoon) 1 Platoon Sergeant (Decon Platoon)	1 HUMMWV/CUCV w/Radio 3 NBC Marking Kits
Total Personnel	29 (Minimum of 11 soldiers from the decon platoon)	




Figure 3-7. Optimum DED layout for an M17 LDS-equipped unit.

	Personn		. Equipment
Station 1 Initial Wash	Decon Platoon 1 Squad Leader 4 Sprayers 2 Scrubbers	Augmentee 2 Scrubbers	3 M17 LDS 3 1,500-gal Tanks 3 65-GPM Pumps 6 Long-Handled Brushes 8 TAP Aprons Liquid Detergent
Station 2 DS2 Application	1 Squad Leader 3 Appliars	9 Appliers	18 Long-Handled Brushes 9 MOps with Extra Mop Heeds 3 30-gel Containers 9 M13 DAPs Sufficient DS2
Station 3 Wall/Interior Docon	1 NCO 2 Interior Dacon Assistants		2 AN/VDR2 or AN/PDR27 3 TAP Aprons 6 30-gal Containers 10 M8 Datactor Paper 30 Sponges 8 M256A1 50 Trash Begs 1 Clipboard W/Pen 1 Stopwatch
Station 4 Rinse	1 Squad Leador 4 Sprayers		3 M17 LDS 3 1,500 gal Tank 3 65 GPM Pumps 4 TAP Aprons
Station 5 Check	2 NCO/CAM Operations		2 CAM 10 M256A1 20 M8 Detector Paper 2 AN/VDR2 or AN/PDR27 2 M6A1 Chem Alarms
C2	l Platoon Leader 1 Platoon Sergeant		1 HUMMWV/CUCV w/Radio 3 NBC Marking Kits
Total Parsonnel	24	11	




Figure 3-8. An Alternate DED layout for an M17 LDS-equipped unit.

.

Table 3-48	8. Personnel and equi alternate M17 LDS (see figure 3	-
	Personnel	Equipment
Station 1 Initial Wash	1 NCOIC* 4 Sprayers 4 Scrubbers	3 M17 LDS 3 1,500-Gallon Tanks 3 65-GAL Pumps 4 Long-Handled Brushes 8 TAP Aprons Liquid Detergent
Station 2 DS2 Application	1 NCOIC* 8 Appliers	14 Long-Handled Brushes 8 Mops with Extra Mop Heads 3 30-Gallon Containers 8 M13 DAPs Sufficient DS2
Station 3 Wait/Interior Decon	1 NCO* 2 Interior Decon Assistants	2 AN/VDR2 or AN/PDR27 3 TAP Aprons 6 30-Gallon Containers 10 MB Detector paper 30 Sponges 8 M256A1 50 trash Bags 1 Clipboard w/Pen 1 Stopwatch
Station 4 Rinse	1 NCOIC* 4 Sprayers	2 M17 LDS 2 1,500-Gallon Tank 2 65-GPM Pump 4 TAP Aprons
Station 5 Check	2 NCO/CAM Operators*	2 CAMs 10 M256A1 20 M8 Detector Paper 2 AN/VDR2 or AN/PDR27 2 M8A1 Chem Alarms
C2	1 Platoon (Smoke/Decon Platoon) 1 Platoon Sergeant (Smoke/Decon Platoon)	1 HUMMWV/CUCV w/Radio 3 NBC Marking Kits
Water Resupply	2 Drivers*	2 TPUs
Total Personnel	32 (Minimum of 10 soldiers from the smoke/decon platoon)	
* These individuals s	hould be from the decon plato	on




Figure 3-9. Layout for a patient decontamination station and a clean treatment area without Collective Protection Shelter (CPS).

Chemical Patient Decontamination Procedures

- Step 1. Decontaminate the patient's mask end hood.
- Step 2. Remove gross contamination from the patient's overgarment.
- Step 3. Remove patient's protective overgarment and personal effects.
- Step 4. Remove patient's battledress uniform.

FM 3-7 Chptr 3 Protection and Decontamination

Step 5. Transfer the patient to a decon litter.

Step 6. Decontaminate skin (M291/M258A1 kit or 0.5% chlorine solution).

Step 7. Transfer the patient across the shuffle pit.




Figure 3-10. Field expedient NBC casualty tag.

Table 3-49	. Standard Dec	ontaminants.	
Decontaminant	Chemical	Biological	Nuclear
DS2	x	×	
STB	x	×	
Mask sanitizing solution	X	x	
Soap and detergents	x	×	x

Table 3-50. Natural Decontaminants.					
Decontaminant	Chemical	Biological	Nuclear		
Weathering	x	×	x		
Absorbents (earth, sawdust, ashes, rags)	x				
Sealants (concrete, asphalt, earth, paint)	×	х	x		
Water	x	x	x		
Steam	x	x	х		
Fire	×	x			

Vehicle	DS2 Reg (gal)	Water	Req (gal)
Venicie	002 Net (gai)	M17	M12A1
Tank	8.5	57	215
Truck	4,9	42	157
APC	3,8	31	151

Table 3-52. Nonstandard Dec		Biological	Nuclear
Decontaminant	Chemica	Biological	Muclear
Oxidizing agents (potassium permanganate, potassium or sodium dichromate, nitric acid, or aqua regia			X
Complexing (chelating) agents (citric acid, tertaric acid, sodium tartrate), kerosene, segestarene, sodium citrate, oxalic acid, sodium oxalate, or orthophosphoric acid			×
lodine water purification tablets		X	
Disinfactent, chlorine, food service		×	
Formalin (formaldehyde)		x	
Peracetic acid (PAA)		х	
Ethylene oxide		x	
Carboxide		x	
Hyamine (benzathonium chloride)		x	
Sodium hypachlorite solution (household bleach)	x	x	
Calcium hypochlorite (HTH) (high-test bleach (HTB), or high-test hypochlorite)*	x	x	
2-Propanone (acetone)	x		
Diethyl athar	x		
Ethylene glycol	x		
Solvents (gasoline, JP4, diesel fuel, kerosene)	x		
Sodium hydroxide (caustic soda or lyc)	×	x	
Sodium carbonate (washing soda, soda ash, sal soda, or laundry soda)	×		
Potassium hydroxide (caustic potash)	X	X	

file:///C|/My Documents/Manuals/Military Field Manuals/FM 3-7 NBC Field Handbook/Ch3.htm (63 of 70) [29/02/2004 3:46:17 AM]

Hexachloramelamina	x	
Ammonia or ammonium hydroxide (household ammonia)	x	
Perchloroethylene (tetrachloroethylene)	x	
Dichloramine-B and Dichloramine-T	x	
Acids (sulturic acid, hydrochloric acid, acetic acid, or oxalic acid)		X
*A S percent solution hypochlorite solution is an effective chemical and biological agants. This solution can be used provided it is followed by a soap-and-water wash. Calcium supply system.	effectively for :	skin decon

Decontamination of Specific Items

The following <u>table</u> lists more than two dozen specific surfaces or materials, and it explains briefly how to best decontaminate each for chemical, biological, and nuclear contamination. The best method for decon of a particular surface or material in a given situation could be any of those listed for that surface or material.

The order in which the methods are listed does not indicate preference of one over another. You should choose the beat method for decon of a particular item. For a more in-depth understanding of the decon methods, refer to FM 3-5.

Table 3-53. Decontamination of Specific Items.

Surface	Type of Contamination			
or Material	Chemical	Biological	Nuclear	
Asphalt: Roads (Applicable to small vital areas only)	 Flush with water. Spray with slurry from PDDE. Cover with STB; when liquid contamination is visible and personnel are nearby, use dry mix. Weather. Cover small areas or paths across roads with 10 cm (4 inches) of earth. 	 Weather. (Remain masked.) Wet with water (will help prevent secondary serosols, but does not decon). Apply 2% household bleach solution. Spray with slumy from PDOE. Pour, spray, or spread oil on surface (will help prevent secondary serosol, but does not decon). 	 Brush or sweep. Flush with water (this may drive some of the contamination into the surface; waste must be controlled). Vacuum cleaning. 	
Roote	Same as for asphalt roads.	e Same as for asphalt roads. • Apply detrochlorite (leave on at least 30 minutes, then flush with water.)	Same as for asphalt roads.	
Brick & Stone: Roads (Applicable to small vital areas only)	 Weather. Spray with slurry from PDDE or apply with brushes and brooms. Lat remain 24 hours, then flush with water. Wash with soapy water, preferably hot. Cover small areas or pathe across roads with 10 cm (4 inches) of earth. 	Same as for asphalt roads.	 Same as for asphalt roads. Abrasion (sand blasting). This provides direct and complete removal of contaminated dust; however, sand and equipment being used becomes contaminated. 	
Buildings	 Spray with slurry from PDDE or apply with brushes and brooms. Let remain 24 hours, then flush with water. Use STB or dry mix around build ings where waste water runs. Wash with soapy water, preferably hot. Weather. 	 Same as for asphalt roads. Apply STB alway to vertical surfaces by manual means or PDDE. Slurry may be left on exteriors 	Same as for brick and stone roads.	
Concrete: Roads (Applicable to smalt vital areas only)	 Spray with slurry from PDDE. Cover with STB or dry mix. Weather. Cover small areas or paths across roads with 10 cm (4 inches) of earth. 	Same as for asphalt roads.	Same as for brick and stone roads.	
Buildings, bunkers, gun emplace- ments, tank obstacles	Same as for brick and stone buildings.	Same as for brick and stone buildings.	Same as for brick and stone buildings.	

Table 3-53. Decontamination of Specific Items (continued).

Surface Type of Contamination					
or Material	Chemical	ſ	Biological		Nuclear

file:///C|/My Documents/Manuals/Military Field Manuals/FM 3-7 NBC Field Handbook/Ch3.htm (65 of 70) [29/02/2004 3:46:17 AM]

FM 3-7 Chptr 3 Protection and Decontamination

Each:	a Bernunith share from DOOF	. Serne as for asphalt roads	· Earthmoving (removal).
Earth: Roads (Applicable to small vital areas only), gun emplace- ments, trivouac areas, path- ways, bomb oraters	 Spray with sharry from PDDE. Cover with STB; when liquid contermination is visible and personnel are nearby, use dry mix. Weather. Burn (may present downwind vapor hazard). Cover small areas or paths across soads with 10 cm (4 inches) of earth. Sorap layer of contaminated earth to side or road. 	• Serne as for aspnalt roads	 Contaminated dust should be controlled. Equipment may become contaminated. Waste disposal must be considered. Sealing (with earth). No waste disposal problem; however, equipment may become contaminated.
Fabrics: Canves, covers, tarpaulins, tentage, mask carriers, web gear, clothing	Cotton • Immerse in boiling soapy water for 1 hr (1 ib soap to 10 gal water; stir. • Use S% solution of sodium carbonate for G agents. • Immerse in boiling water for 1 hr. • Launder by standard methods. • Use slurry. • Weather (except for V agents). Woolan (DS2 not recommended) Immerse in warm (100°F, soapy water for 1 hr or longer with light agitation; dry items slowly (fabric may shrink))	Colton e boil in water for 15 minutes. e Autoclave for 45 minutes at 123°C (253°F). e immerse in 2% household bleach solution for 30 minutes, rinse immediately. e Launder (destroys or inactivates all but highly realistant spores). Woolen (DS2 not recommended). Launder (labric mey shrink).	Cotton and Woolen (DS2 not recommended for wollen). • Brushing (removes contaminated dust, but presents dust hazerd top personnel). • Laundering (most practical procedure; waste must be controlled; fabric may stvink).
Leather: Boots, glaves, and other items	e serub with hot, soapy water and since. • Immerse in soapy water at 120°F for 4 hrs and rince. • Use 5% sodium carbonate solution for G agents. • Air.	e immerse in 2% household bleach solution. Fines. e Immerse in 2% persostic add for 10 minutes, rinse, and air for 10 to 50 minutes. e Wipe with 2% persostic add, remove excess, and air 10 to 15 minutes.	e Brushing e Flushing with water or scapy water.
Glees: Windows	 Dépan kit, individual equipment. M258A1 or M280 kit. DS2. Wash with hot, soapy water. Weah with plear water or organic solvent. Blot off surface. Air. Weather 	e M258A1 or M280 kit. • Wash with scap and water. • Wipe with disinfectant solution or 2% persoatic acid (see similar procedures below for mess gear).	e M258A1 or M280 kH. e Wash with detergent. e Flush with water. e Wipe with solvents.
Lonses	 M258A1 or M280 kit. Serve as for windows (DS2 may damage lens coatings). Decon kit, individual equipment. 	e M258A1 or M280 kit. e Wipe with soap and water. e Wipe with alcohol or household bleach.	e M258A1 or M280 kit. e Brush or wipe (cars must be exercised to prevent soratching of lens). e Use compressed air to blow contamination from surface.
Grasa Ind Low /egetation: Fields, open errain	 Burn. Spray with elurry from PODE. Cover with STB or dry mix. Explode drums of STB. Clear paths through area by use of detonating cord or other detonating devices. 	e Burn. e Same as for asphalt roads.	Same as for earth.

Table 3-53. Decontamination of Specific Items (continued).

Surface	Type of Contamination			
or Material	Chemical	Biological	Nuclear	
Metals (unpainted): Ammunition	e Wipe with scapy water. e Wipe with organic solvent and dry. e Air	e Wipe with soapy water. e Wipe with 2% household bleach solution. e Air.	e Brush or wipe.	
Machinery	e Use DS2. • Same as for ammunition.	e Use DS2, e Wipe with 2% peracetic acid, rinee, and air for 10 to 15 minutes.	e Brush or wipe. e Wash with detergent. e Fluch with water.	
Mess peer and canned rations	e Immerse in bolling, soapy water for 30 minutes and rinse. e Immerse in bolling water for 30 minutes. e Spray with DS2. e Wash in hot, soapy water, rinse, and air.	 Wash with scop and water, then immerse in disinfectant solution (disinfectant, chlorine, food service, or 1/3 canteen sup of household bleach per 10 gal water). Boil in water 15 minutes. (Not effective on toxins and bacterial spores.) Immerse in 5% sodium carbonate (4 lb washing soda to 10 gallons water), rinse with potable water. Immerse in household bleach solution (1/2 gal bleach to 25 gal water) for 30 minutes, then rinse and air for 10 to 15 minutes. Immerse in HTH solution (1/2 lb to 25 gal water) 30 minutes, then rinse. Immerse in STB solution (1 lb to 25 gal water) for 30 minutes, then rinse. Immerse in 2% personatio sold for 10 minutes, rinse, and air for 10 to 15 minutes. 	e Wash with soap and water, rinse. e Brush, wipe contamination from surfaces and containers.	
Metale (painted): Vehicles, weapons, equipment	 DS2 (may soften paint). Wash with hot, scapy water and rinse. Spray with slurry from PDDE, remove from surface in 1 hour and oil surface. Weather. Air. M291 kit may be used for individual weapon decon. M280 (DKIE) decon kit, individual equipment. 	 Wash with detergent and high-pressure water stream. Apply detrochlorite. Leave on 30 minutes, then remove by washing with a stream of water. Steam clean, using detergent. Use household bleach solution. Use 2% peracetic acid. 	 Brush or wipe. Wash. Use organic solvents, caustics (not on aluminum or magnesium surfaces), complexing agents (of small value on weathered surfaces) or abrasives. 	
Plastics (opaque): Insulation, telephones, panel boards.	 DS2 (may soften or damage some plastics. Wash with hot, soapy water and rinse. Weather. Air. 	Same as for lenses	e Wash with delergents. e Flush with water. e Wipe or brush.	
Plastics (transparent): Eyspieces, airplane	 Wash with hot, soapy water and rinse. Weather. Air. 	Same as for lenses.	Same as for plastics (opaque).	

Table 3-53. Decontamination of Specific Items (continued).

Surface	Type of Contamination				
or Material	Chemical	Biological	Nuclear		
Pubber (Imperme- able): Aprona, sulta, and other items	 Spray with DS2 and rinse after 30 minutes. Immerse in hot, soapy water (just below boiling point) for 1 hour; do not agitate. Pinse with clear water and hang up to dry. For G agents, use 10% sodium car- bonate solution, rinse, and air. Apply hot, soapy water with brushes and rinse. Spray with slumy from PDDE. After a few minutes, wash off with olear water. 	Same as for leather.	e Brushing. e Scrubbing or flushing with water or soapy water.		
Rubber (natural and synthetic): Gloves, boots	 Spray with 10% mixture of HTH and rinse. Immerse in slurry solution for 4 hours, rinse, and air. Use the M291 kit in emergencies. AIR. 	Same as for leather.	Same as for impermeable rubber.		
Mask facepieces and other rubber articles corning in direct contact with the skin.	 USE the M291 kit in emergencies. Wash with warm, soapy water. Use decon kit, individual equipment, M290. 	 Wash in warm, soapy water; rinse in clear water, and dry at room temperature Wipe with 2% paracetic acid; wipe off excess immediately, and air 10 to 15 minutes. 	e Wipe or brush off. e Wipe off with water and detergent (evoid wetting mask filters).		
Tires, hoses, mats, insula- tion.	 Spray with 10% mixture of HTH and rinss. Apply sturry pasts. Allow sturry to remain at least 30 minutes, then flush with clear water (may be left on tires). Apply hot soapy water. Air. Weather. 	Use same methods used for chemical decon.	Same as for impermeable rubber.		
Sand (Applicable to small vital areas only): Beaches, deserts.	 Flush with water, Spread STB or spray slurry over surface. Weather, Cover paths with roofing paper. Scrape off 5 to 10 cm (2 to 4 inches) of contaminated top layer. 	 Burn. Wet with water (will help prevent secondary aerosols, but does not decon). Apply 2% household bleach solution. Apply slurry of 7 parts STB and 93 parts water (by weight). Apply sodium hydroxide. 	Same as for earth.		
Undergrowth and tall grass: Meadows,	• Burn (downwind vapor hazard). • Spray slurry from PDDE. • Weather. • Evaluate downs of STR	e Burn. e Same as for send.	To extent possible, use same proce- dures as for earth.		

FM 3-7 Chptr 3 Protection and Decontamination

(unpainted): or	pply slurry with PDDE, brooms.	. Apply detrachiorite. Leave on at	e Planning.
vehicle the bodies, e So boxes, crates, rim	r swabs. Let slurry remain 12 to 24 ours; flush and repeat application, hen flush again. crub with hot, soapy water and nse. Veather.	least 30 minutes; flush with water. • Apply STB slurry to versical surfaces. Sturry may be left on interiors. • Weather (sun and rain eliminate most microorganisms within one day). • Burn.	 Wash exterior with large amounts of water (some contamination may soak into surfaces.

Table 3-53. Decontamination of Specific Items (continued).

Surface	Type of Contamination					
or Material	Chemical	Biological	Nuclear			
(painted or aurlace): ho (DS2 may e Sc soften paint). DS	 Apply slurry with PDDE, brooms, or swabs. Let slurry remain 12 to 24 hours, then rinse off with water. Scrub with hot water and rinse. Use DS2 and rinse. Weather. 	Same as for wood buildings and boxes as previously indicated .	 Wash exterior with large amounts of water. Wipe contamination from surface. 			
Water	Decon of water should only be under- taken by trained water purification per- sonnel.	 Boil small amounts 15 minutes. Chlorinate using chlorination kit. Add lodine water purification tablets to small amounts of water. 	 Flocoulation (requires special chamicals to remove suspended matter in water). Ion exchange (removes radicions from solution). 			
Food:Not canned or protected by impermeable container	Food known or suspected to be contaminated with chemical agents should not be consumed until approved by veterinary personnel.	 Boil in water 15 minutes. Cook thoroughly. Immerse in or spray with 2% household bleach solution. (Pack – aged food or food which is peeled or pared may be immersed or soraved.) 	Wash or trim contamination from un- packaged food.			

file:///C|/My Documents/Manuals/Military Field Manuals/FM 3-7 NBC Field Handbook/Ch3.htm (69 of 70) [29/02/2004 3:46:17 AM]

	1		
Food: Canned, Dittied, or protected by impermeable container	See mess gear and canned rations.	See mess gear and canned rations.	See mess gear and canned rations.
Personnel	 Use M291 kit on exposed skin known or suspected to be con - taminated; decon kit, individual equipment, M280. Bathe with scap and water if readily available. 	 Bath with scap and hot water; decon- luit individual equipment, M280. Use the M291 kit. 	e Brush or wipe from skin and hair. e Bathe with scap and hot water.



Chapter 4

Nuclear Protection

There are three types of radiation:

ALPHA--Travels only a few centimeters, internal hazard only.

BETA--Travels a few meters in air, limited penetrating power, external and internal hazard.

GAMMA--Travels speed of light, cannot be totally shielded.

Actions Before an Attack:

The best defense against a nuclear attack is to dig in. Unit defensive positions, which vary from soldier's foxholes to improved defensive positions, should be prepared whenever the tactical situation permits.

Foxholes: A deep, round foxhole with overhead cover offers the best protection from blast, thermal radiation, initial nuclear radiation, and fallout.

Field shelters: Well-constructed fighting positions and bunkers provide excellent protection against all the effects of a nuclear detonation.

Tunnels, caves, culverts, and storm drains provide good shelter.

Armored personnel earners, infantry fighting vehicles, and tanks (in a hull-down defilade) give excellent protection.

Weapons, individual equipment, clothing, and other items should be secured in their foxholes. Supplies, explosives, and flammables should be dispersed and protected or shielded. If left unsecured, these may become lethal weapons from the blast wave.



Figure 4-1. Tracked vehicle as expedient overhead cover.




Figure 4-2. Section views of shelters.




Figure 4-3. Expedient cover against blast and thermal effects.




Figure 4-4. Shelter in a building.

Table 4-1. Shielding values of earth cover for a 2,400-centigray free-in-air dose.					
Soldier in	Radiation Protection Factor	Resultant Dose cG			
Open	one				
Open foxhole, 4' deep	8	300			
Same with 6" earth cover	12	200			
Same with 12" earth cover	24	100			
Same with 18" earth cover	48	50			
Same with 24" earth cover	96	25			

Table 4-2. Radiation protection factors of sand-or clay-filled sandbags.					
Soldier In	Radiation Protection Factor	Resultant Dose cGy			
Open	None	2,400			
Open foxhole, 4' deep	8	300			
Same with 1 layer (4 inches)	16	150			
Same with 2 layers (8 inches) Same with 3 layers (12	32	75			
inches)	64	38			

Table 4-3. Comparison of blast casualties from a 10-kiloton fission weapon.								
Range (meters)	200	300	400	700	800	900	1,000	1,400
Personnel in open (percentage)	100	80	41	11	8	5	4	0
Personnel in wheeled vehicle (percentage)	10	100	100	99	80	62	43	1

Actions During an Attack

- Immediately drop face down.
- Close eyes.
- Protect exposed skin.
- Wait until blast wave passes and debris stops falling.
- Stay calm, check for injury.
- Check weapons and equipment.
- Prepare to continue the mission.




Figure 4-5.Recommended body positions in a foxhole.




Figure 4-6. Protection from blast flow into shelters.

Actions After an Attack

- Begin continuous monitoring.
- Organize survivors.
- Secure and organize equipment.
- Cover mouth with handkerchief.
- Assist casualties.
- Send NBC 1 report.
- Improve protection against possible fallout.
- Conduct damage assessment and restoration of combat power.

Simplified Fallout Prediction (M5A2)

- 1. Information required: NBC 2 nuclear report and effective downwind message (EDM).
- 2. Record date-time of burst, GZ, and wind direction on M5A2.
- 3. Determine Zone I from the nomogram printed on the M5A2, draw arc on M5A2, and label.

FM 3-7 Chptr 4 Nuclear Protection

- 4. Zone $II = 2 \times Zone I$; draw an arc, and label.
- 5. Draw tangents from cloud radius to end of Zone I.
- 6. Darken the perimeter.
- 7. Draw time-of-arrival arcs and label.
- 8. Orient azimuth on predictor with grid north.

Significance of Predicted Fallout Zones

Exposed, unprotected personnel may receive the following doses from fallout:

Zone I--Immediate operational concern. More than 150 centigray (cGy) within 4 hours.

Zone II--Secondary hazard. Less than 150 cGy within 4 hours. More than 50 cGy within 24 hours.

Outside the predicted area--No more than 50 cGy in 24 hours. No more than 150 cGy for an indefinite period.

Detailed Fallout Prediction (Unit Level)

1. Obtain a valid NBC 3 report.

2. Determine scale at which the prediction will be drawn (must be the same as the map on which it will be displayed.)

3. On overlay paper, mark GZ.

With Line YANKEE (from NBC 3 report):

4. Mark grid north.

5. Extend radial lines at their proper azimuths from GZ (from line YANKEE).

6. Using GZ as center, draw Zone I arc (from line ZULU) between radial lines.

7. Using GZ as center, draw Zone II arc (2 x Zone I) between radial lines.

8. Using GZ as center, draw circle with radius equal to the cloud radius (from line ZULU).

9. Draw two tangent lines from the GZ circle to the points of intersection of the two radial lines with the Zone I arc.

10. Using GZ as center, draw dashed time-of-arrival arcs (from line ZULU). No arcs are drawn beyond the end of Zone II.

- 11. Label zones, times of arrival.
- 12. Add marginal information:
 - a. Strike serial number (from line ALFA).

- b. Date-time of attack (from line DELTA).
- c. GZ coordinates (from line FOXTROT).
- d. Scale.

Without Line YANKEE:

- 4. Using GZ as center, draw Zone I circle (the only 3 digits on line ZULU).
- 5. Using GZ as center, draw Zone II circle (2 x Zone I).
- 6. Label zones and GZ.
- 7. Add marginal information:
 - a. Strike serial number (from line ALFA).
 - b. Date-time of attack (from line DELTA).
 - c. GZ coordinates (from line FOXTROT).
 - d. Scale.

NOTE: If you need more detailed information on fallout prediction, see <u>FM 3-3-1</u>. Figure 4-6. Four parts of completing a fallout prediction.

Marginal Information

- Map designation
- Grid reference data
- Nuclear burst ground zero identification
- H-hour
- Reference time
- Decay rate (exponent)
- Time of preparation
- Validity time
- Source of contamination (fallout, neutron-induced, or radiological agents)
- Dose rate information

Radiological Monitoring

Periodic monitoring (readings at least once every hour) is done when--

- Intelligence indicates a threat of nuclear war.
- Nuclear war has been initiated or NBC threat status (nuclear) is Serial 3.
- Continuous monitoring falls below 1 centigray per hour (cGyph).

Continuous monitoring is done when---

FM 3-7 Chptr 4 Nuclear Protection

- A nuclear detonation is seen, heard, or reported.
- Periodic monitoring records 1 cGyph or higher.
- Ordered by the unit commander.
- A warning of expected contamination (NBC 3) is received.

Automatic NBC 4 reports are--

- Initial report.
- Peak report.
- Special reports--send when a condition exists that warrants the commander's attention--for example, when the commander's operational exposure guidance (OEG) is exceeded.

Additional directed reports are--

- Series reports.
- Summary reports.
- Verification reports.

Radiological Survey Briefing

- 1. Situation: Enemy and contamination situation
- 2. Mission: Who, what, when, where, and why
- 3. Execution:
 - a. Concept of operation
 - b. Assignments
 - c. Coordinating instructions:
 - (1) Time of departure
 - (2) Primary and alternate routes
 - (3) Coordination required
 - (4) OEG, turn-back dose (D_{tb}) , turn-back dose rate (R_{tb})
 - (5) Actions on reaching D_{tb} or R_{tb}
 - (6) Areas requiring marking
 - (7) Debriefing when, where, by whom
- 4. Service Support: Forms, equipment, POL, decontamination, and so forth
- 5. Command Signal:
 - a. Command. Location of control party

b. Signal:

- (1) Reporting requirements
- (2) SOI
- (3) Codes and call signs
- (4) Primary and alternate communication means

Aerial Radiological Survey Briefing

Control party briefing includes--

- Time of departure.
- Course legs and routes.
- Tentative height.
- Coordination required.
- OEG.
- Actions on reaching D_{tb} or R_{tb} .
- Debriefing: when, where, by whom.
- Height of aircraft (150 meters AGL [above ground level] maximum, 60 meters AGL optimal).
- Ground speed (53 knots [98 kmph] maximum; slower is more accurate).
- Establishment procedures for the air-ground correlation factor (AGCF).
- Time interval between readings (500 meters maximum).

To use the below <u>table</u> to find the downwind distance of Zone I, enter the left-hand column with the yield as indicated on line NOVEMBER of the NBC 2 nuclear report. Read across the top to locate the nearest wind speed (always round UP to safe-side). Where the two columns intersect is the Zone I distance Distances are in kilometers.




Figure 4-7. Downwind distance of Zone I (km).

Time of arrival (TARR) =
$$\frac{Distance From GZ (KM)}{Effective Wind Speed (kmph)}$$

Transmission factor =
$$\frac{Indise Dose or Dose Rate (ID)}{Outside Dose or Dose Rate (OD)}$$

Inside dose or dose rate = Outside dose or dose rate x transmission factor

Outside dose or dose rate = $\frac{inside \ Dose \ or \ Dose \ Rate}{Transmission \ Factor}$

Radiological Calculations* (For use with pocket calculator)

Decay

Kaufman Equation: $R_1 = R_1 \times t_n$ $R_1 = R_1/t_n$ $t = \frac{R_1}{t_n}$

 R_1 = Dose rate measured at H + 1.

 R_t = Dose rate measured at time (t) after burst (other than H + 1)

t = Time that Rt was measured (in H +m-hours after burst).

n = Decay exponent (use 1.2 if unknown).

Total Dose**

Use if $T_e \le H + 25$: $D = (R_I/1-n)(T_x1-n - T_e1-n)$ Use if $T_e > H + 25$: $D = R_{Te} \ge T_s$ D = Total dose. $T_x = Time of exit from area (in H + number of hours after burst).$ $T_e = Time of entry into area (in H + number of hours after burst).$ $T_s = Time of stay in area (hours).$

Decay Rate of Fallout (n)

 $n = Log (R_a/R_b) / Log (T_b/T_a)$

 R_a = Dose rate measured at time a (T_a) (after peak dose rate).

 R_b = Dose rate measured at time b (T_b) (last dose rate).

 $T_a = time (in H + number of hours after burst) that R_a was measured.$

 $T_b = time (in H + number of hours after burst) that R_b was measured.$

Validity Time for Decay Rate (TP)

 $T_p = 3 (T_b - T_a) + T_b$

FM 3-7 Chptr 4 Nuclear Protection

 $T_a = Time (in H + number of hours after burst) that R_a was measured.$

 $T_b = Time (in H + number of hours after burst) that R_b was measured.$

TIME AFTER			DECAY EX	PONENT (n)				
BURST	0.600	0.800	1.000	1.200	1.400	1.600	1.800	2.000
10 min	0.341	0.238	0.167	0.116	0.081	0.057	0.040	0.028
20 min	0.517	0.415	0.333	0.268	0.215	0.172	0.138	0.111
30 min	0.660	0.574	0.500	0.435	0.379	0.330	0.287	0.250
40 min	0.784	0.723	0.667	0.615	0.567	0.523	0.482	0.444
50 min	0.896	0.864	0.833	0.803	0.775	0.747	0.720	0.694
1 hr 0 min	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
1 hr 10 min	1.090	1.130	1.160	1.200	1.240	1.280	1.320	1.360
1 hr 20 min	1.180	1.250	1.330	1.410	1.490	1.580	1.670	1.770
1 hr 30 min	1.270	1.380	1.500	1.620	1.760	1.910	2.070	2.250
1 hr 40 min	1.350	1.500	1.660	1.840	2.040	2.260	2.500	2.770
1 hr 50 min	1.430	1.620	1.830	2.070	2.330	2.630	2.970	3.360
2 hr 0 min	1.510	1.740	2.000	2.290	2.630	3.030	3.480	4.000
2 hr 15 min	1.620	1.910	2.250	2.640	3.110	3.660	4.300	5.060
2 hr 30 min	1.730	2.080	2.500	3.000	3.600	4.330	5.200	6.250
2 hr 45 min	1.830	2.240	2.750	3.360	4.120	5.040	6.170	7.560
3 hr 0 min	1.930	2.400	3.000	3.730	4.650	5.800	7.220	9.000
3 hr 15 min	2.020	2.560	3.250	4.110	5.200	6.590	8.340	10.560
3 hr 30 min	2.120	2.720	3.500	4.490	5.770	7.420	9.530	12.250
3 hr 45 min	2.210	2.870	3.750	4.880	6.360	8.280	10.790	14.060
4 hr 0 min	2.290	3.030	4.000	5.270	6.960	9.190	12.120	16.000
4 hr 20 min	2.410	3.230	4.330	5.810	7.790	10.440	14.000	18.770
4 hr 40 min	2.520	3.420	4.660	6.350	8.640	11.760	16.000	21.770
5 hr 0 min	2.620	3.620	5.000	6.890	9.510	13.130	18.110	25.000
5 hr 20 min	2.730	3.810	5.330	7.450	10.410	14.560	20.350	28.440
5 hr 40 min	2.830	4.000	5.660	8.010	11.340	16.040	22.690	32.110
6 hr 0 min	2.930	4.190	6.000	8.580	12.280	17.580	25.150	36.000
6 hr 20 min	3.020	4.370	6.330	9.160	13.250	19.170	27.720	40.110
6 hr 40 min	3 120	4.560	6.660	9.740	14.230	20.800	30.410	44.440
7 hr 0 min	3.210	4.740	7.000	10.330	15.240	22.490	33.200	49.000
7 hr 20 min	3.300	4.920	7.330	10.920	16.270	24.230	36.100	53.770
7 hr 40 min	3.390	5.100	7.660	11.520	17.310	26.020	39.110	58.770
8 hr 0 min	3.480	5.270	8.000	12.120	18.370	27.850	42.220	64.000
9 hr 0 min	3.730	5.800	9.000	13.960	21.670	33.630	52.190	81.000
10 hr 0 min	3.980	6.310	10.000	15.840	25.110	39.810	63.090	100.000
11 hr 0 min	4.210	6.800	11.000	17.760	28.700	46.360	74.900	121.000
12 hr 0 min	4.440	7.300	12.000	19.720	32.420	53.290	87.600	144.000

Table 4-4. Normalizing Factors (NFs) (Correlation to H + 1 Hour)

1. Use next higher time if time falls in between.

2. Interpolating NF of odd decay rates will be approximations only.

Normalizing Factor Formulas

For H + 1: NF = (T²) or H + 48: NF = (T²/48) T2 = Elapsed time after burst n = Decay Exponent $R_1 = R_t \times NF$ FM 3-7 Chptr 4 Nuclear Protection

Aerial Survey Calculations

Minimum number of readings $= \frac{leg \text{ or route length } (km)}{.5 \text{ km}} + 1$

Time between readings (see) = <u>Leg or Route Length (km) x 3,600 (see/hr) x (no. readings - 1)</u> Windspeed of Aircraft (kmph)

Distance between readings (km) = <u>Time Between Readings (sec) x Aerial Aircraft Speed (kmph)</u> 3.6 ^(seq/hr)

Plotting interval between readings (km) = $\frac{Leg \text{ or Route Length (km)}}{no. Readings - 1}$

Turn-back dose (D_{1b}) = $\frac{OEG}{2}$

Turn-back dose rate (R_{tb}) = $\frac{2 \times OEG \times Speed (kmph)}{Distance (km)}$

M1 tank	.04
M60 tank	.04
M2 IFV	.2
M3 CFV	.2
M93 NBC Recon (Fox)	.2
M113 APC	.3
M109 SP howitzer	.2
M88 recovery vehicle	.09
M548 cargo vehicle	.7
M577 carrier; command post	.3
M551 Armored Recon Airborne Assault Vehicle	.2
M728 Combat Engineer Vehicle	,04
M9 ACE	.3
Grader	8,
Bulldozer	.5
Scraper	.5
HMWWV	.6
CUCV	.6
21/2-ton truck	.6
4- to 7-ton truck	.5
Multistory building	
Top floor	.01
Lower Floor	.1
Frame house	
First floor	.6
Basement	.1
Urban area (in open)	.7 *
Woods	.8*
Underground shelter (3-foot earth cover)	.0002
Foxholes	.1

* These factors do not apply to ground survey dose rates. Note: The above TFs are for planning purposes only.Calculate the actual TF for a given shelter using the following transmission factor formulas.

$$TF = \frac{ID (Inside Dose Rate)}{OD (Outside Dose Rate)} |D = OD \times TF$$

P

Shielding	Location of Survey Meter	Correlation Factor	
M1 tank (Abrams)*		20.0	
M60 tank	Turret, rear top	25.0	
	Turret, front	53.0	
	VDR2 mount, left of driver intercom box	23.0	
M2 IFV (Bradley)	AN/VDR2 mount on hull wall	9.1	
M3 CFV	AN/VDR2 mount on hull wall	9.1	
M113 APC	AN/VDR2 mount on hull wall by heater	3.6	
M109 SP howitzer	Near driver, left side	9.1	
	Rear right side	3.5	
M88 recovery vehicle	Commander position	3.4	
M577 command post	AN/VDR2 mount above TC's intercom	6.9	
Carrier	box		
551 armored recon	Near driver, right side	2.5	
airborne assault vehicle		4.6	
HUMMWV family (M998)	AN/VDR2, by radio mount	1.7	
21/2-ton truck		1.7	
4- to 10-ton truck		2.0	
M1008 CUCV Series	AN/VDR2 mount on cab floor	2.0	
Multistory building			
Top floor		10.0	
Lower floor		2.0	
Frame house			
First floor		2.0	
Basement		10.0	
Underground shelter		5,000.0	
(3-foot earth cover)		,	
Foxholes		10.0	

* These CFs are for planning purposes only. Calculate the actual CF for a given shelter, using the following correlation factor formulas.

$$CF = \frac{OD (Outside Dose Rate)}{ID (Inside Dose Rate)}OD = ID \times CF$$

Table 4-7. AN/VDR2 Attenuation Factor DIP Settings.				
	Row G	Row H	Row J	
M577	0	4	0	
M60 Tank	2	3	0	
M1 Tank	2	0	0	
M113	0	3	6	
M2/M3	0	9	1	
M151	0	1	3	
M880/M1008	0	2	0	
M998	0	1	7	

Table 4-8. Dose Criteria for Placing a Unit in a Radiation Exposure Status Category.				
Radiation Exposure Status	Numerical Criteria Total Cumulative Dose (cGy			
RES Zero	O (no exposure)			
RES1	> 0- <u>≤</u> 70			
RES2	> 70 - <u><</u> 150			
RES3	>150			

Table 4-9. Nuclear radiation degree-of-risk exposure.				
Radiation status category (See A&B)	Total past cumulative dose (cGy) (See C)	Possible exposure criteria for a single operation that will not result in exceeding the dost criteria for the stated degree of risk (cGy) (See D&E)		
RES-0 Units	No explosure	Negligible risk: ≤ 50 Moderate risk: ≤ 70 Emergency risk: ≤ 150		
RES-1 Units	More than 0, but less than or equal to 70	Negligible risk: ≤ 10 Moderate risk: ≤ 30 Emergency risk: ≤ 110		
RES-2 Units	More than 70, but less than or equal to 150	Any further exposure is considered to exceed a negligible or moderate risk. Emergency risk: ≤ 40		
RES-3 Units	More than 150	All further exposure will exceed the emergency risk.		

NOTES:

A. Radiation status categories are based on previous exposure to radiation.

B. Reclassification of units from one radiation status category to a less serious one is made by the commander, upon advice of the surgeon, after ample observation of actual set of health of exposed personnel.

C. All exposures to radiation are considered total body and simply additive. No allowance is made for body recovery from radiation injury.

D. Risk levels are graduated within each status category to provide more stringent criteria as the total radiation dose accumulated becomes more serious. The exposure criteria given for RES-1 and RES-2 units should be used only when the numerical value of a unit's total past cumulative dose is unknown.

E. Each of the degrees of risk can be applied to radiation hazards resulting from enemy or friendly weapons, or both, and from initial nuclear radiation resulting from planned friendly supporting fire.

Radiation Injury

Immediate Injury but Delayed Effects

Since a radiation injury victim does not show symptoms immediately after exposure, except for nausea and vomiting, these initial symptoms are not reliable by themselves to evaluate casualties or treat patients. Currently, the only available method to quickly estimate the radiation injury to a soldier is with a personnel dosimeter. Without this dosimetry, many days must pass before definitive diagnostic techniques of the secondary radiation exposure symptoms can provide an accurate estimate of radiation injury.

Tolerance:

IM93 \pm 10% certified and leak checked IM147 \pm 10% certified and leak checked DT236 \pm 30% or \pm 30 cGy, whichever is less, with 95% confidence after 24 hours

Self-aid and Buddy Aid

Key Factor in Nuclear Combat

Nuclear detonations can produce large numbers of blast, burn, and projectile injuries that initially must be managed by individual soldiers trained in critical frost-aid procedures.

Critical Period

The great physical damage to the surrounding area as a result of a nuclear detonation will increase delays in medical assistance and evacuation. Quality self-aid and buddy aid will improve casualty survival rates and conserve medical resources. Prompt stabilization will ensure casualties can better withstand evacuation to appropriate medical treatment facilities.

Radiation Guidance

Radiation guidance is the advice by the medical staff officer to the commander concerning the medical effects of predicted and actual radiation received by a unit. Commanders use medical advice and information to weigh the options of retaining soldiers with radiation injury (with the possibility of increasing lethality) versus entry into the medical support system.

Importance of Fitness and Wellness

The percentage of deaths that will occur from a given exposure is not a constant value, and it is, in fact, changed by many conditions. For healthy soldiers, LD + 50 is estimated to be about 450 cGy if no medical care is provided, if there are no other injuries, and if they are required to perform little physical labor. If, however, soldiers with no other injuries are worked to exhaustion or are in poor general health, LD + 50 is be reduced to approximately 300 cGy. Soldiers in good health, promptly evacuated to a CONUS hospital, and provided extensive medical care are expected to have their LD + 50 increased to 600 cGy. Soldiers' fitness and health are, therefore, critical factors for survival on a nuclear battlefield.

Dose* Range (cGy)	Initial Symptoms**	Time of Initial Symptoms (approx)	Performance Capability (mid-dose range)	Final Disposition				
0 to 70	None to slightincidence of transient headache and nauses, vomiting in up to 5% of personnel in upper part of range	6—12 hours	Combat effective	Duty				
71 to	Transient mild nausea and vomiting in 5%—30% of personnel, vomiting	220 hours	Combat effective	Duty. No deaths.				

150	in up to 5% of personnel in upper part of range.						
151 to 300	Transient mild to moderate nausea and vomiting in 20%—70% of personnel, mild to moderate fatigue and weakness in 25%—60% of personnel.	2 hours to 2 days	DT: PD from 4 hours until recovery. UT: PD from 6 hours until 1 day. PD: 6 weeks until recovery.	Duty; less than 5% deaths at low end of exposure range; death may occur in 10% of personnel.			
301 to 500	Transient moderate nausea and vomiting in 50%—90% of personnel, moderate fatigue in 50%—90% of personnel.	2 hours to 3 days	DT: PD from 3 hours until 2 weeks, for death or recovery. UT: PD from 4 hours to 2 weeks until death or recovery.	Duty at low end of exposure range; less than 10% deaths. At high end of exposure range, death may occur in more than 50% of personnel beginning after 4 weeks.			
501 to 800	Moderate to severe nausea and vomiting in 80%—100 of personnel.	Within 1 hour	DT: PD from 2 hours until 3 weeks. Cl from 3 weeks until death.	At low end of exposure range death may occur in more than 50% of personnel beginning after 4 weeks. At high end of exposure range 99%, beginning after 3 weeks.			

Dose* Range (cGy)	Initial Symptoms**	Time of Initial Symptoms (approx)	Performance Capability (mid-dose range)	Final Disposition
801	Moderate to severe fatigue and weakness in 90%—100% of personnel.	2 hours to 6 weeks	DT: PD from 2 hours to 2 days and 7 days until 4 weeks.	
to 1,500	Moderate to severe nausea, vomiting, disorientation, and dizziness in 100% of personnel; moderate fluid loss in 80% of personnel.	45 minutes to 2-1/2 daγs	DT: PD 1 hour until 6 hours and 1-1/2 days until 1 week. CI: 6 hours until 1-1/2 days and 1 week until death. UT: PD 1-1/2 hours until 8 days. CI: 8 days until death.	1,000 cGy; death in 1 to 3 weeks.

Doses are free-in-air dose values.

** Vomiting and nausea from tension or fear was reported by 20% of US combat troops in a survey of WWII veterans, particularly in the presence of horrible sights and smells. Extreme fatigue and weakness are also common symptoms of combat stress (battle fatigue). Therefore, none of these symptoms alone are a reliable indicator of the amount of radiation exposure a person may have received.

The effects listed in Table 4-10 represent a continuous exposure spectrum broken into dose range segments. When looking at symptoms/performance, the high end of one segment is very close to the low end of the next segment.

ge r Parked pters	Light Observ	600	800	1,100	1,300	1,600	1,900	2,600	2,800	3,400	3,700	4,100	4,500	5,700	6,200	7.100	sr yield.	
Jama	domly lelico	o Bu	400	89	700	860	000	1,200	1,500	1,800	1,900	2,200	2,500	2,700	3,200	3,700	3,800	h large

Category	Yield (KT)	0.1	0,6		20 10 10 10 10 10			10	11	20	30	4	54	10	20	30	NOTES:	1. Radii li	2. HOB u	3. To obt
* For neutron induced radiological calculations, use nomograms	ttron ind	luce	d ra	Idio	log	ical	ca	lcul	latic	ons,	us	e na	ome	ogra	Ims		FN	in <u>FM 3-3-1</u>	မှ	
file:///C /My Documents/Manuals/Military Field Manuals/FM 3-7 NBC Field Handbook/Ch4.htm (23 of 24) [29/02/2004 3:47:32 AM]	uals/Military	Field	Manu	uals/F	-M 3-	7 NB	°C Fi	eld H	andb	ook/	Ch4.h	ntm (23 of	: 24)	[29/0	2/20	04 3	:47:3	\$2 A	<u>≤</u>

*
Fo
or neutr
oni
For neutron induced radiological calc
d rac
adiolog
ogical
calcu
calculations,
use
culations, use nomograms in <u>FM 3-3-1</u> .
ams
in
FM 3
-3-1.

				Table	9 4-11. I	Radii of	Vulnerab	oility.			
Category		Pere	onnel In-				Moderate	Damage		Se	vere (
outegoty			n governin			Wheeled	vehicles	Tanks	Towed	Supply	Ran H
Yield (KT)	Open	Open Foxholes	APC	Tanks	EARTH Shelter	Exp	Shld	Tanks	Arty	depot	Car Tra
0.1	700	600	600	500	300	200	160	100	100	100	
0.5	900	800	800	700	450	300	250	200	200	200	-
1	1,200	900	900	800	500	400	350	300	250	260	
2	1,700	1,000	1,100	900	600	500	450	400	300	300	
3	2,000	1,100	1,200	1,000	700	600	500	500	400	450	
6	2,500	1,200	1,250	1,100	800	700	600	600	500	600	
10	3,200	1,300	1,300	1,250	900	800	700	700	600	600	
15	3,700	1,400	1,400	1,300	850	900	800	800	700	700	
20	4,000	1,500	1,450	1,400	1,000	1,000	900	900	800	800	
30	5,000	1,600	1,500	1,500	1,100	1,200	1,100	1,000	900	950	
40	5,500	1,700	1,600	1,600	1,200	1,400	1,250	1,100	1,000	1,200	
50	6,000	1,800	1,700	1,700	1,300	1,700	1,500	1,200	1,200	1,400	-
100	8,000	1,900	1,800	1,800	1,400	2,200	1,900	1,300	1,300	1,700	
200	12,000	2,000	1,900	1,900	1,500	2,600	2,000	1,500	1,500	1,900	
300	14,000	2,100	1,950	1,950	1,600	3,000	2,100	1,600	1,600	2,000	

listed are distances at which a 5 percent incidence of effect occurs.

used is 60W 1/3 meters.

3. To obtain a radius of vulnerability, enter the Yield Column of the nearest listed yield. If exactly halfway between yields, enter with Data listed in table above is for training use only. Use the data in FM 101-31-2 (S) whenever possible.

4. All values have been rounded up to the next 10 meters.

** When decay constant n = 1, use 1.000001 for the above equation.



CHAPTER 5

Biological Protection

Actions Before An Attack:

- Up-to-date immunizations
- Good hygiene
- Area sanitation
- Physical conditioning

Biological Attack Indicators:

- Mysterious illness (large number of soldiers)
- Large number of insects or unusual insects
- Large number of dead wild and domestic animals
- Artillery shells with less powerful explosions
- Aerial bombs that pop rather than explode
- Mist or or fog sprayed by aircraft

Actions During Suspected Attack:

- Wear protective mask
- Keep clothing buttoned up
- Consider any known biological agent cloud as a chemical attack

Actions After An Attack:

- Send NBC 1 Report
- Identify casualties (from symptoms they exhibit)
- Isolate soldiers with symptoms

Biological Hazard's Prediction

Suspect A Biological Attack When

- There are indications of a chemical attack, but no immediate effects
- A presumed chemical attack has occurred, but the agent has not been identified

Three Types Of Biological Attacks Are:

• Type A Case a--Point-source attack (example aerosol generator, bomb) or an area attack (as in

FM 3-7 Chptr 5 Biological Protection

artillery or bomb let attack). This type of attack includes toxins.

- Type A Case b--A spray line.
- Type B--Large, liquid drop/ground contaminating attack

Biological Calculations

Maximum Downwind Hazard (MDWHD) = 4 X windspeed (kmph) X cloud duration $\underline{*}$ of greatest effects (Zone I)

Example of MDWHD Computation: Time of attack: 0130 BMNT: 0430 Wind direction: 150 grid Windspeed: 13 kmph Cloud duration = 5 hrs MDWHD = 4 X 15 X 5 = 300 km (3 hrs from time of attack to BMNT + 2 = 5 hrs)

Cloud Duration of the Greatest Effects (Zone I) Daytime (from BMNT to sunset) 8 hours Nighttime (from sunset to BMNT) # of hours from time of attack to BMNT + 2 (max of 8 hours) Cloud Arrival Time (CAT) = Time of Attack (TOA) + $\frac{Distance (km) From Attack Area}{Windspeed (kmph)}$

Simplified Downwind Hazard Prediction for Biological Agents

Downwind hazard prediction for biological agents is very similar to the procedure for chemical agents. The resulting prediction provides a minimum estimate of the danger zones for biological agents in general. After employment, actual sampling will produce a better indication of areas affected.

Indications of a Biological Attack

The NBCC will issue an NBC 3 chemical report to alert units in the immediate downwind hazard area. The NBC 3 chemical report equates to approximately 50% of Zone I of the simplified biological downwind hazard prediction. This warning will be adequate for the first 1 to 5 hours (depending on wind speed) units in the remainder of Zone I and Zone II of the biological hazard will need to receive NBC 3 biological reports for adequate warning.

The hazard area prediction will be less reliable as the distance and time from the point of attack increases. (If the wind changes, follow the same procedures for recalculation as for chemical hazard prediction.

Cloud Exposure Time = (CET) = $\frac{Distance (km) From Attack Area}{3 x Windspeed (kmph)}$

The NBC 3 chemical report equates to approximately 50 percent of Zone I of the simplified biological downwind hazard prediction. This warning will be adequate for the first 1 to 5 hours (depending on wind speed). Units in the remainder of Zone I and Zone II of the biological hazard will need to receive NBC 3 biological reports for adequate warning.

All attacks during daytime and all toxin attacks must be presumed to have a cloud duration of the greatest effects of 8 hours. Only for night attack is it necessary to compute this duration.

The 8-hour maximum for cloud duration is based upon agent decay by environmental conditions, particle fall, and cloud dissipation. The actual effectiveness to minimum hazard levels may extend to as much as 32 hours. (Four times the cloud duration of greatest effects.)

Meaning of Zones for Biological Areas

Zone I--More than 20% to 30% casualties.

Zone II--20% to 30% casualties, gradually decreasing to 1% to 3% casualties.

Outside the predicted area--No more than 1% to 3% casualties.

	Table 5	5-1. Pasquil	l Stability	Classes		
Class	Definition					
Α	Extremely un	nstable				
в	Moderately u	Instable				
с	Slightly unst	able				
D	Neutral					
E	Slightly Stab	le				
F	Moderately S	Stable				
		Cond	itions			
Daytime			Nighttime			
Surface wind speed m/sec	Strong	Moderate	Slight	Cloudy	Clear	
< 2	8	A-B	в			
2-3	A-B	В	С	E	F	
3-4	В	B-C	С	D	E	
4-6	с	C-D	D	D	D	
>6	с	D	D	D	D	

Type A Case a (Point Source Attack)

1. Derive the location of the attack from NBC 1 chemical report and plot the location on a map or template.

file:///C|/My Documents/Manuals/Military Field Manuals/FM 3-7 NBC Field Handbook/Ch5.htm (3 of 10) [29/02/2004 3:48:02 AM]

FM 3-7 Chptr 5 Biological Protection

2. Draw a 1-km radius circle around the point of attack.

3. Determine the maximum downwind hazard.

MDWHD = 4 x windspeed (kmph) x cloud duration of greatest effects $\underline{*}$ (Zone I)

4. Draw a line from the point of attack along the representative downwind direction, equal in length to the MDWHD.

5. Draw a line perpendicular to the representative wind direction, intersecting the point of the MDWHD.

6. Extend the line along the representative wind direction for a distance twice the radius of the circle around the attack area from GZ, in the direction behind the attack area.

7. From the rear endpoint of the representative wind direction line, draw two lines that intersect this point, are tangent to the attack area circle, and intersect the line of MDWHD.

8. Erase the area behind the attack area circle. The remaining area constitutes the Zones I and II hazard area. The points shown on the diagram define the hazard area. Indicate these points on line PA of the NBC 3 Report.

9. Divide the MDWHD by 4. Plot this distance along the representative wind direction line. Draw a line perpendicular to the representative wind direction and which intersects both tangent lines at this point. The area within this smaller plot is the Zone I hazard area.

10. Report the two points at which the Zone I hazard line intersects the tangent lines on line ZB of the NBC 3 biological report.

Time of attack: 0330 BMNT: 0530 wind speed: 13 kmph wind direction: 90 deg grid MDWHD = $4 \times 13 \times 4 = 208$ km (2 hours from time of attack to BMNT + 2 hours = 4)

Type A Case a (area attack)

1. Derive the location of the attack from NBC 1 chemical report and plot it on the map.

2. Plot a circle with a radius of 1 km, unless the attack area radius is known to be more than 1 km. If the attack area is known to be greater than 1 km, plot a circle with a radius equal to the radius of the attack area around the center of the attack area. The circle must have a minimum radius of 1 km.

3. All subsequent procedures are exactly as outlined in the Type A, Case a point-source sample.

Time of attack: 2230 BMNT: 0700 wind speed: 15 kmph wind direction: 60 deg grid MDWHD = 4 x 15 x 8= 480 km (maximum 8 hours BMNT) Type A, Case b (linear spray)

1. Derive the location of the attack area from NBC 1 chemical report. (A number of reports may need to be evaluated). Plot the attack area or spray line on the map.

a. Draw a line through the attack area from the start point to the end point.

2. Draw 1-km-radius circles around the beginning point and endpoint of the spray line.

3. Determine the MDWHD, as in <u>Case a</u>.

4. From each endpoint of the spray line, draw a line equal in length to the MDWHD along the representative downwind direction.

5. Draw a perpendicular line intersecting the MDWHD point on the representative wind direction line drawn from the attack area endpoint furthest downwind. This is the line of maximum downwind hazard.

6. Extend each representative wind direction line 2 km behind each endpoint of the spray line.

7. Draw a line from each point 2 km behind the endpoints tangent to the outer side of each circle, until it intersects the MDWHD line.

8. Draw a line tangent to the rear of both attack circles. Erase the area behind the attack circles. This figure encompasses the Zone II hazard area. Report the points delineating this area.

9. Divide the MDWHD by 4. Plot this distance from the attack area endpoint furthest downwind on the representative wind direction line. Draw a line perpendicular to this point and which intersects both tangent lines. This smaller figure is the Zone I hazard area. Report the point of intersection with the tangent lines as Zone I on line ZB of the NBC 3 biological reports.

Time of attack: 0930 BMNT: 0700 wind speed: 2 kmph wind direction: 90 deg grid spray length: 10 km MDWHD = 4 x 12 x 8 = 384 km

Type B (large, liquid drops, ground contaminating attack)

1. Derive the location of the attack area from NBC 1 biological report, and plot it on the map.

2. Draw a circle with a radius equal to the radius of the attack area. This circle should have a minimum radius of 5 km.

3. Report the hazard area as three digits on line PA of the NBC 3 biological report.




Table 5-2. Potential Biological Warfare Agents.

Table 5	2. Potential Biologi	cal Warfare A	gents.		
rganism	Mode of Transmission	Incubation Period (Days) ²	Mortality Rate (Percent)2	Vaccine (³)	Trea
	A, D ⁹ , I	1-7	5-1005	+	
mia)	A, D ⁹ , I A, D ⁹ , I, V	1-10	< 30	+ +	
	A, V	2-6	25-1007	+++	l
	1	1-5	15-90	+++	
(Diptheria)	A, D ⁹	2-5	5-12	+++	
ever)	I	6-21	7-14	+++	<u> </u>
rs group)	v	6-15	10-40	+++	
borne typhus)	v	6-14	2-5	N	
spotted fever)	v	3-10	30 (approx)	N	
	A, I	14-21	<1	++	

psol-A, direct contact-D, ingestion-I, and/or vector-V.

tality rates vary according to a number of factors (such as ability of the host to resist infection, infective dose f the microorganism).

ble but of questionable value; + + indicates vaccine available, but mainly used in high risk individuals; + + + /; N indicates no vaccine available.

tent available; N indicates no specific treatment.

when the agent enters through the skin; higher when it enters through the respiratory tract.

d in the earliest stage of the pulmonary form to be effective.

mortality due to bubonic form; 100 percent represents mortality due to pneumonic form.

be the primary vectors, but this has not been proven.

ing bitten by a rabid animal, which is the usual means of transmission, or coming into contact with a rabid ani

ical Warfare Agents (continued). Mortality le of Incubation Vaccine (³) Rate Treatment (4) Period (Days)² nission (Percent)2 4-24 60 (Approx) N Ν 4-24 <1 Ν + + uito) 5-15 10-80 N 3-40 7-14 N uito) 3-6 5-40 + + + N uito) 4-10 <1 N 7-16 10-25 Ν + + + uito) <1 4-6 Ν Ν 3-7 uito} fly) 3-6 or vector-V.

factors (such as ability of the host to resist infection, infective dose, portal

es vaccine available, but mainly used in high risk individuals; + + + indicates

tment.

higher when it enters through the respiratory tract.

rm to be effective.

nt represents mortality due to pneumonic form.

een proven.

usual means of transmission, or coming into contact with a rabid animal.

-	
	Microo
Ba Fr Ye Vi C	acteria acillus Anthracis (Anthrax) ancisella Tularensis (Tulare ersinia Pestis (Plague) ibrio Cholerae (Cholera) orynebacterium Diptheriae almonella Typhi (Typhoid Fe
Ri Ri Ri	ickettsiae ickettsia SPP (Spotted feve ickettsiae (Endemic or flea- ickettsia (Rocky Mountain a oxiella Burnetii (Q fever)
2 3 4 5 6 7	Transmission can be by aero Incubation periods and mor of entry, and virulence o + indicates vaccine availat vaccine used extensively E indicates effective treatm The mortality rate is lower Treatment must be initiated The 25 percent represents Mosquitoes are thought to Direct contact refers to bei

T-41- C 0 Potential Biolog

Table 5-2.	Ρ
Microorganism	
Viruses Eastern Equine Encephalitis (EEE) Venezuelan Equine Encephalitis (VEE)	
Japanese B Encephalitis Russian SpringùSummer Encephalitis (RSSE)	
Yellow Fever Dengue Fever	
Pox Virus Variloa Virus (Smallpox)	
Hantaan Virus (Hemorrhagic Fever with Renal Syndrome) Phlebovirus (Rift Valley Fever)	
Nairovirus (Crimean-Congo Hemorrnagil Fever) Bunyavirus (LA Crosse) Phlebovirus(Sandfly)	
¹ Transmission can be by aerosol-A, direct contact ² Incubation periods and mortality rates vary acc	ct co

¹Trans t-D, ingestion-I, and/c ² Incut ording to a number of of entry, and virulence of the microorganism).

+ indicates vaccine available but of questionable value; + + indicate vaccine used extensively; N indicates no vaccine available.

⁴ E indicates effective treatment available; N indicates no specific trea ⁵ The mortality rate is lower when the agent enters through the skin; I 6

Treatment must be initiated in the earliest stage of the pulmonary fo 7

The 25 percent represents mortality due to bubonic form; 100 perce 8 Mosquitoes are thought to be the primary vectors, but this has not b

9 Direct contact refers to being bitten by a rabid animal, which is the u

otection ∋quired	Decontamination
tective sk and tective thing	Soap and water, bleach, M258-series kit, STB and DS2
ne as ve	Same as above
ne as ive	Same as above

Mod Transn

٧⁸

٧⁸

V (Mosq

V (Tick)

V (Mosq

V (Mosq

V (Mosq

V (Tick)

V (Mosq

V (Sand

A, D⁹

A, V

Table 5-3. Threat Toxins.

Symptoms in Man	Effects on Man	Rate of Action	How Normally Disseminated	Prc Re
Vomiting, eye and skin irritation, dizziness, bloody diarrhea, and blisters.	Can incapacitate or kill, depending on concentration.	Rapid	Dusts, droplets, aerosols, smokes, or covert means	Prot mas prot clot
Severe vomiting and diarrhea, painful cramps, and weakness	Primarily incapacitates, assuming proper first aid is conducted	Same as above	Same as above	San abo
Double vision, weakness, difficulty in speech and swallowing, and respiratory paralysis	Kills	Delayed	Same as above	Sar abc

_

Type of Toxin	Means of ID
Mycotoxins	None
Enterotoxins	None
Botulinum Toxin	None

* The cloud duration is a measure of the length of time a biological agent is likely to remain effective end aerosolized in the environment.



CHAPTER 6

Smoke

Smoke in the Offense

Battlefield applications of smoke include--

- Obscuring
- Screening
- Protecting
- Marking

Friendly forces use projected, generated, and self-defense smoke to--

- Mark targets.
- Obscure enemy gunners and surveillance.
- Degrade enemy command, control, and communications.
- Conceal passage of lines, movement to contact, and hasty and deliberate attacks.
- Conceal landing zones (LZs), drop zones (DZs), or pickup zones (PZs). (For friendly LZs, DZs, and PZs the smoke is placed to restrict enemy observation without interfering with friendly operations.)
- Conceal river-crossing operations and reduction of obstacles.
- Conceal logistics operations (for example, fast refuel sites).
- Signal.
- Support deception plans.
- Degrade enemy laser designators, range finders, and weapons.
- Enhance the effectiveness of artillery-delivered minefield by concealing their visual indicators.
- Support MOUT operations.

Smoke in the Defense

In the defense, forces use smoke primarily to increase survivability and counter enemy reconnaissance, surveillance, and target acquisition. Forces use smoke in the defense to--

- Obscure enemy direct-fire gunners and artillery forward observers.
- Disrupt enemy movement and command and control.

- Conceal obstacle emplacement, preparation of battle positions, and movement to alternate positions.
- Conceal reconstitution, holding, and staging areas.
- Conceal MSR activities.
- Signal.
- Mark targets.
- Deceive the enemy as to areas of main effort and battle positions.
- Reduce the effectiveness of enemy directed-energy weapons.
- Enhance air defense by degrading nap-of-earth flight patterns and forcing the enemy to fly higher.
- Silhouette targets.
- Support MOUT operations.

Tactical Countermeasures

- Disperse laterally and in-depth to increase lines-of-sight.
 - Position forward observers outside anticipated coverage.
 - Position laser designators to front or flanks to avoid preplanned smoke.
 - Position visual air defense systems on high ground.
 - Position thermal/MMW air defense systems in smoke.
- Use obstacles to disrupt enemy timing.
 - Use electronic jamming to preclude adjustments of smoke.
 - Use remote sensor systems to track enemy progress.
 - Engage at choke points with indirect or preaimed direct fire.
- Deceive the enemy about unit location.
 - Prepare positions and alternates in friendly smoke.
 - Conduct rigorous counter-reconnaissance.
 - Use decoys.
- Use helicopters to identify and fire through gaps in coverage. Use remote piloted vehicle (RPV) to look down through smoke.
- Employ scatterable mines in friendly or enemy smoke to slow an attacking enemy.
- When moving in smoke, plan for tighter formations, slower speeds, and easily recognized routes.
- In the defense, prepare and rehearse movement to alternate and subsequent positions. Use range cards, T&E mechanisms, and multiple lines-of-sight for paired weapons. Plan for target hands-off.
- Smoke coordination and reconnaissance checklists for smoke unit leaders are outlined below.

Smoke Planning Process

- Each echelon of command plans for smoke employment to support current and future operations.
- Integrate smoke into the overall tactical plan.
- Synchronize smoke use with key events or decision points.
- Base smoke planning on the same factors as the tactical plan--
 - Mission
 - Enemy situation
 - Terrain
 - Weather
 - Troops available
 - Time
 - Distance
- Mission considerations include--
 - Types of smokes and obscurants available.
 - Unit capabilities.
 - Detailed planning and preparation.
 - Employment techniques.
 - Communications.
 - Intelligence.
 - Whether the unit has successfully operated in smoke previously
- Chemical staffs must coordinate with other staff sections to--
 - Develop estimates that define enemy capabilities and our own courses of action.
 - Analyze smoke targets.
 - Prioritize smoke resources.
 - Recommend courses of action to the commander.
- When the commander approves the staff estimates, the staff prepares orders that combine smoke with combat power.

Situation and Target Development

Targeting begins with the commander's guidance and continues through the development of a prioritized list specifying what targets to attack and when to attack these targets (DECIDE), plus acquiring high-payoff targets (DETECT), and what will defeat these targets (DELIVER).

Intelligence Preparation of the Battlefield

- For smoke planners
 - Evaluation of area of interest and operation.

- Terrain analysis
- Weather analysis
- Threat evaluation
- Threat integration

Smoke Estimate

- Chemical officer, in coordination with the G3/S3, FSO, and smoke unit commander/platoon leader prepares the smoke estimate.
- Estimate goes to the S2 and targeting officer for inclusion into the target value analysis (TVA) for fire support planning, and to the S3 and chemical staff for smoke target planning.

Smoke Support Plan Development

- Prepared simultaneously with the smoke estimate.
- Obtain the restated mission/commander's intent.
- Obtain required fire and smoke planning information.
- Recommend smoke support coordinating measures.
- Update status displays.
- Brief smoke support plan to obtain concurrence from commander (or G3/S3 as required by local policy).
- Coordinate fire support plan changes with the commander or S3 and with the FSO.
- Coordinate the smoke support plan with adjacent units.
- Brief smoke unit leader(s) on the smoke annex to the OPORD.

Smoke Support Plan Execution

- Use covered and concealed maneuver techniques.
- Time smoke delivery with decision points, IPB, and human feedback.
- Use unobscured weapons to overwatch.
- Do not let your smoke silhouette your own forces.
- Plan to engage through or around the smoke.
- Plan for enemy countermeasures.
- Plan for additional maneuver time under smoke.
- Verify enemy locations (responsibility of recon).

Smoke Support Plan Execution

- The impact of smoke on tactical operations mandates close coordination, control, and planning for contingencies.
- Command/staff supervision are essential to ensure the use of smoke enhances rather than degrades

mission success.

- Commanders must control smoke in their areas of operation.
- Smoke unit leader monitors the communications nets for the supported unit and internal nets.
- Plan to minimize friendly force degradation from our use of smoke.

Smoke Mission Coordination Checklist for Smoke Unit Commanders or Leaders

- Grid coordinates of the smoke target area.
- Tactical or operational missions to be supported.
- Visibility criteria required in the smoke target area?
- Type of screening smoke (haze, blanket, or curtain).
- Type of smoke unit support for logistics, security, and fire support available or needed.
- Will weather and terrain influence the mission?
- Anticipated duration of the mission.
- Direction of known or suspected enemy forces.
- Supported units' frequencies, call signs, and brevity codes.
- Signals for starting, stopping, shifting, or continuing the smoke mission.
- Tactical situation in the proposed smoke area of operations concerning enemy contact, obstacles, etcetera.
- Actions taken should the smoke unit make enemy contact.
- Grid coordinates of supported unit TOCs/CPs.
- Challenge/password and code weds.
- Fog oil and fuel (both diesel and gasoline) resupply.
- Maintenance support and recovery provided.
- Projected requirement for Class V.
- What aviation assets will be available to supported and supporting units?
- Where are LZs, and FARPs?

Smoke Recon Checklist for Smoke Unit Leaders

- Locate selected target areas.
- Determine supported and subordinate unit positions.
- Designate subordinate unit smoke positions and/or lanes.
- Locate smoke control point(s).
- Designate supply routes, access routes, fuel resupply points, and/or fuel/fog oil forward prestock points if required.
- Determine local weather and terrain conditions. (While it is important to note local weather conditions at the time of the recon, the unpredictable nature of weather necessitates that the smoke

unit leader consider all possibilities when drafting the operations order.)

• Determine security support requirements and internal smoke unit defense measures.

		e Generator Unit Ca	
Type of Organization	Point Sources	Average Screen Width* Visibility at 50 Meters (Min-Max)	Average Screen Width* Visibility at 50—Meters (Min-Max)
Chemical Company (SG) (Mtr) (M151) M3A4) One Platoon	48 24	1.00 km—3.4 km 0.50 km—1.7 km	2.0 km—6.8 km 1.0 km—3.4 km
Chemical Company (SG) (Mtr) M998) (M3A4) One Platoon	48 24	0.50 km—1.7 km 0.50 km—1.7 km	1.0 km—3.4 km 0.1 km—3.4 km
Chemical Company (SG) (Mtr) M1037) (M157) One Platoon	24 12	0.50 km—1.7 km 0.25 km—.85 km	1.0 km—3.4 km 0.5 km—1.7 km
Chemical Company (Smk/Decon) (M151) M3A4) One Platoon	48 12	1.00 km3.4 km 0.30 km9 km	2.0 km—6.8 km 0.5 km—1.7 km
Chemical Company (Hvy Div/Mech) Smoke Platoon (M1059) (M157)	6	0.20 km6 km	0.4 km—1.1 km
Chemical Company (SG) Mech (M1059) (M157) One Platoon	21 7	0.60 km—2 km 0.30 km—.7 km	1.1 km—3.7 km 0.5 km—1.3 km

be used as minimums for mobile employment.

Table 6-2. Wind Speed Estimation.		
Observed Conditions	Wind	Speed
Observed Conditions	Kmph	MPH
Smoke, vapor from breath, or dust raised by vehicles or personnel rises vertically. No leaf movement.	0-2	0-1
Smoke, vapor from breath, or dust raised by vehicles or personnel moves slightly in direction of wind. Leaves move slightly and intermittently.	3-5	1-3
You can feel slight wind on your face. Leaves rustle.	6-10	4-7
Leaves and small twigs in constant motion.	11-14	7-12
Wind raises dust from ground. Loose paper and small branches move.	15-25	13-18
Small trees with leaves sway. Coastal wavelets form on inland waters.	26-32	19-24

Generators	Mission (Hours)								
	1	2	3	4	6	8	10	12	
1	3	6	9	12	18	24	30	36	
2	6	12	18	24	36	48	60	72	
3	9	18	27	36	54	72	90	108	
4	12	24	36	48	72	96	120	144	
6	18	36	54	72	108	144	180	216	
8	24	48	72	96	144	192	240	288	
10	30	60	40	120	180	240	300	360	
12	36	72	108	144	216	288	360	432	
14	42	84	126	168	252	336	420	504	
18	54	108	162	216	324	432	540	648	
24	72	144	216	288	432	576	720	864	
36	108	216	324	432	648	864	1,080	1,296	
48	144	288	432	576	864	1,152	1,440	1,728	
Formula	Gallons o generator				ion (hou	rs) times	number	of	

Genererators	Mission (Hours)								
	1	2	3	4	6	8	10	12	
1	1	2	3	4	6	8	10	12	
2	2	4	6	8	12	16	20	24	
3	3	6	9	12	18	24	30	36	
4	4	8	12	16	24	32	40	48	
6	6	12	18	24	36	42	60	73	
8	8	18	24	32	48	64	80	96	
10	10	20	30	40	60	80	100	120	
12	12	24	36	48	72n	96	120	144	
14	14	28	42	56	84	112	140	16	
18	18	36	54	72	108	144	180	21	
24	24	48	72	96	144	192	240	28	
36	36	72	108	144	216	288	360	43	
48	48	96	144	192	208	384	480	576	

Table 6-4. Fog Oil Consumption (Number of 55-gallon drums)	1
(For general planning M3A4 EM157)	

	Table 6	5. Smoke	Pot Ch	aracteri	stics.	
Type of Smoke Pot	Burning Time (Minutes)	Ignition	Chain Ignition	Floating	Weight (Pounds)	Fuel Filler
M5	12-22	Manual or electrical	Yes	No	33	HC (solid)
, M4A2	10-15	Manual	No	Yes	38	HC (solid)
XM8 (Training only)	5-7	Manual	No	No	33	TA (solid)

Wind	Speed	Temperature	Terrain	1	Spacing sters)	Distance Smoke Line
Kmph	Mph	Gradient	Description	Haze	Blanket	from Target (Meters)
1-14	1-9	All: Stable	Open/Water	50	25	250
		Unstable or Neutral	Wooded	60	30	300
1				70	35	350
25-15	9-16	All	Open/Water	40	20	200
			Wooded	50	25	250
26-32	16-20	All	Open/Water	30	15	150
			Wooded	40	20	200

CLASSIFICATION
 Grid coordinates of the smoke mission (target location): Start and stop date/time/event of smoke mission: START Date/Time/Event: STOP Date/Time/Event:
3. On/off-station date/time for the smoke unit(s): ON-STATION date/time: OFF-STATION date/time:
4. Type of visibility in the smoke required:
5. Enemy location(s)/activity:
6. Communications: (a) Supported unit's frequencies and callsign: Primary Frequency: Alternate: Callsign:
(b) Supporting unit's frequencies and callsigns:
Primary Frequency: Alternate: Callsign:
CLASSIFICATION

Figure 6-1. Sample smoke mission coordination checklist.

CLASSIFICATION
7. Supporting unit's command relationship to the supported unit (DS, GS, attached, OPCON):
 Supported units' responsibilities to the supporting unit (for example, maintenance, transportation, fuel, and feeding):
9. Required staff coordination for the mission: (Check applicable staff sections.): S2 S3 S4 FSE ALO ENG
10. Location of supported unit's TOC:
11. Challenge, password(s), and code word(s):
12. Coordination effected with subordinate units, DATE/TIME:
13. Coordination effected with adjacent units, DATE/TIME:
14. Designate supply route(s) in/out of area:
15. Determine local weather conditions and peculiarities:
16. Determine any additional security requirement (for example, supporting unit requirement(s) for security forces):
17. Liaison Information (between supported unit and supporting unit):
18. Smoke operation overlay:
19. After action report (AAR) to division NBCC:
Date/Time Mission Started:
Duration of Mission: Fog Oil/MOGAS Consumption:
Mission Issues/Problems:
Mission Results (success or failure):
CLASSIFICATION

Figure 6-1 (cont'd). Sample smoke mission coordination checklist



CHAPTER 7

Flame Field Expedients

Flame Field Expedients (FFE) Checklists

Location of Fuel Mixing Site


- No fire hazards
- Firm, well-drained terrain
- Convenient to supply delivery
- Central location
- Well-ventilated and outdoors
- Posted with NO SMOKING signs

Employment in the Offense

- Raids
- Ambushes
- Low-intensity conflicts
- MOUT operations

Employment in the Defense

- Reinforce obstacles
- Augment final protective fires
- Cover dead spaces and gaps in the defense
- Illuminate critical areas of the battle



Safe Handling and Minimum Safe Distance for Explosives

Safe Handling

Handling, transport, and storage of explosive items must conform to AR 385-63 and local regulations.

Responsibility for preparing, placing, and firing of charges must not be divided. Supervising all phases of the mission must rest with one person.

Personnel handing explosives, blasting caps, and demolitions must--

- Follow safety rules.
- Observe post regulations.
- Adhere to local unit SOPs.

Minimum Safe Distance for Missile Hazard

The MSD table gives distances at which personnel in the open are relatively safe from missiles created by bare charges placed in or on the ground, regardless of type or condition of the soil. See AR 385-63 and FM 5-250 for further details.

Table 7-1. Minimum Safe Distances (MSDs).				
Pounds of Explosives	MSD (in meters)			
1-2	300			
30	311			
35	327			
40	342			
45	356			
50	369			

Fire and Burn Safety

Thickened flame fuel--

Burns much longer than raw gasoline.

Sticks to objects and continues to burn.

Cannot be stamped out with a boot, it will only spread and continue to burn.

Burning Fuel on Personnel

If burning fuel splashes on an individual, he or she must react as follows:

- DO NOT run (running can result in extensive and severe burns).
- React quickly to extinguish the fire.
- Fall to the ground, face down, if burning fuel is on the front.
- Fall to the ground, face up, if burning fuel is on the back.
- Remain motionless.
- Smother the flame by depriving it of oxygen.

Soldiers not affected by the flame must--

- React quickly to help smother the flame.
- Use soil, sand, canvas, or CO₂ fire extinguishers (in training).
- Use BDU garments, poncho liners, or shelter halves (in combat).

Burning Fuel on Equipment

If FFE fires are on equipment, personnel must use either standard Army CO_2 fire extinguishers or expedients (water, sand, soil, other nonflammable dry substances).

Detection of Water in Gasoline

Water in gasoline is one of the chief causes of poor or unsatisfactory flame fuel. When mixing flame fuel, assume that all gasoline contains water unless it has just been removed.

Water in gasoline is most easily detected by sampling the liquid at the bottom of the container with an aspirator.

Removing Water from Gasoline

Siphon

Tilt the drum and allow it to stand for several minutes. Water will accumulate in the lowest portion of the drum. Insert a flexible tube or hose and siphon off the water. See FM 3-11 for additional methods.

Fuel Mixing Procedures

1. Determine quantity of M4 thickener needed.

Rule of thumb: Number of ounces of M4 thickener = gals of gasoline x 3 (constant)

Example M4 = 50 gallons of gasoline x 3 M4 = 150 ounces of my fuel thickening compounds = 3 3/4cans (2 1/2 pounds each) of M4 thickener to be added to the gasoline.

- 2. Add unclotted M4 thickener to gasoline while stirring.
- 3. Mix until applesauce texture is achieved (5-10 minutes).

4. Allow the fuel to age for 6 to 8 hours (can be emplaced while aging). Although aging is desirable, newly mixed fuel may be fired with acceptable results.

Unthickened Fuel

When M4 (or MI) fuel thickening compound is not available, an acceptable alternative fuel can be prepared using a 60% - 40% combination of MO GAS and oil. (NOTE: Any kind of oil will work, such as standard 30 weight motor oil, fog oil, or crank case drainings.) The best oil to use is 90 weight oil. Example: In a 55-gallon drum, 30 gallons of MOGAS should be mixed with 20 gallons of oil. Join the two substances and shake or stir vigorously for a minute or two. The fuel is now ready for use.

Exploding Flame Devices


See <u>FM 3-11</u> for step-by-step instructions.

Vertical Flame Mine with Detonating cord

Area coverage is approximately 50 to 80 meters in diameter. Each 55-gallon flame land mine requires the following:

FM 3-7 Chptr 7 Flame Field Expedients

- One 55-gallon container.
- Fifty gallons of gasoline.
- One hundred feet of detonating cord.
- Two electric blasting caps.
- One hundred and fifty ounces of M4 thickening compound.
- One M49 trip flare or (in combat) M34 WP grenade.
- Six or seven sandbags.



SAFETY NOTE: It is vital that electrical cap-up procedures are accomplished correctly and in the proper sequence.

NOTE: During entire cap up process, radio transmitters in the area (within 50 meters of the cap) must be turned off.

Figure 7-1. Sample vertical flame mine with detonating cord.

The illustration <u>below</u> shows a horizontal exploding 55-gallon flame device (detonating cord).




Figure 7-2. Example of a horizontal flame mine.

Area coverage is approximately 80 to 10 meters in diameter. Each horizontal 55-gallon flame land mine requires the following:

- One 55-gallon container.
- Fifty gallons of gasoline.
- One hundred feet of detonating cord.
- Two electric blasting caps.
- One hundred and fifty ounces of M4 thickening compound.
- One M49 trip flare or (in combat) M34 WP grenade.
- Two 1.25-pound blocks of composition C4 or two 1-pound blocks of TNT.

5-Gallon Flame Device

The illustration <u>below</u> shows a 5-gallon fragmentation exploding flame device (explosive charge or M4 burster). Area coverage is approximately 20 to 25 meters.




Figure 7-3. Fougasse made with a 55-gallon container.

Each 5-gallon flame device requires the following:

- One 5-gallon container.
- Five gallons of gasoline.
- Twenty-five feet of detonating cord.
- Two electric blasting caps.
- One M4 field incendiary burster.
- Fifteen ounces of M4 thickening compound.

55-Gallon Flame Fougasss Container

Area coverage is approximately 150 to 200 meters in diameter.

Each 55-gallon flame fougasse device requires the following:

- One 55-gallon drum.
- Fifty gallons of gasoline.
- One hundred feet of detonating cord.
- Two electric blasting caps.
- Two 1.25-pound blocks of composition C4 or two 1-pound blocks of TNT.

FM 3-7 Chptr 7 Flame Field Expedients

- One hundred and fifty ounces of M4 thickening compound.
- One M49 trip flare or (in combat) M34 WP grenade.
- Fifty to eighty sandbags.

One ammunition-can flame bunker bomb requires the following eight items:

- One small-arms ammunition container.
- One gallon of gasoline.
- Fifty feet of detonating cord.
- One nonelectric blasting cap.
- One M60 fuse igniter.
- Seven and a half feet of M700 time fuse.
- Three ounces of M4 thickening compound.
- One M49 trip flare or (in combat) M34 WP grenade.

Area coverage is approximately 5 to 10 meters in diameter. The bunker bomb is designed as a portable FFE device to be used during mobile defensive operations or raids into enemy rear areas during deep operations. This device is ideally suited for use in built-up areas during mobile operations in urban terrain.




Figure 7-4. Example of bunker bomb made from an ammunition

Propellant Charge Container

Area coverage is approximately 30 to 45 meters in diameter. Each propellant charge fougasse requires the following:

- One metal cylinder or propellant charge container.
- Three gallons of gasoline.
- One hundred feet of detonating cord.
- Two electric blasting caps.
- Nine ounces of M4 thickening compound.
- One M49 trip flare or (in combat) M34 WP grenade.
- One 1.25-pound block of composition C4.
- Twenty to thirty sandbags.

The 155 powder charge Fougasse has a range of approximately 30 to 40 meters.






Figure 7-5. Example of a propellatit citarye tougasse.

Flame Illuminators

The Husch-type flare is a sealed, metal container (powder canister) 3/4 full of thickened fuel with a 1/8 to 3/16th-inch hole in the bottom. The container is placed with cap end down in half of a 55-gallon drum 3/4 full of thickened fuel. A reflector assembly made from 24-inch culvert should extend about 24 inches above the top of the drum half rim (figure below). When the fuel in the drum half is ignited, the heat from the burning fuel produces vapor in the powder canister, this vapor is expelled as a burning jet through the hole in the canister.




Figure 7-6. Cutaway showing composition of a Husch flare.

A Husch-type flare will illuminate an area of about 50 meters radius for 4 to 5 hours.

Methods of Firing

Exploding flame devices can be wired to fire electrically on an individual basis, in groups, or with simultaneous ignition. Also, they may be rigged with trip wires for immediate or delayed firing.

NOTE: Electric and nonelectric blasting caps can be used with various bursters or igniters.

An exploding or illuminating FFE device can be constructed, emplaced and camouflaged by 3 trained soldiers in less than an hour, provided all necessary equipment is on hand and the selected shot sites

designated in advance.

Alternative explosive charges

Although M4 field incendiary bursters are designed specifically for field expedient flame weapons, this does not mean they are the only charge to be used. Alternative explosive charges, such as composition C4, TNT, claymore mines or detonating cord, may be used in lieu of M4 bursters to produce a powerful explosion.



APPENDIX A

Combat Orders

Combat orders are written or oral communications used to transmit information pertaining to combat operations.

Warning Order

A warning order gives advance notice of a contemplated action or order which is to follow. Although a warning order has no prescribed format, all known elements should be included. <u>Figure A-1</u> represents a suggested format.

WARNING ORDER—Stated to alert recipients ADDRESSEES—To whom the order pertains SITUATION—A short, concise statement of the friendly and enemy situation TIME/NATURE OF OPERATION—Type of mission EARLIEST TIME OF MOVE TIME/PLACE FOR OPORD ISSUANCE SPECIAL INSTRUCTIONS—Details of early coordination to be made, rehearsals, and special equipment requirements. ACKNOWLEDGE

Figure A-1. Warning order - essential elements

Operation Order (OPORD)

The operation order sets forth the organization for combat (task organization), the situation, the mission, the commander's decision and plan of action, and the details of the execution needed to ensure coordinated action by a unit. The standard OPORD format is shown in Figure A-2.

CLASSIFICATION

OPORD NO.

file:///C|/My Documents/Manuals/Military Field Manuals/FM 3-7 NBC Field Handbook/Appa.htm (1 of 11) [29/02/2004 3:52:27 AM]

REFERENCES. List any maps or documents needed to understand the order or that were used in the preparation of the order.

TIME ZONE USED THROUGHOUT THE ORDER:

TASK ORGANIZATION:

1. SITUATION

- a. Enemy forces
 - (1) Situation (enemy, weather, and terrain)
 - (2) Capabilities
 - (3) Probable course of action
- b. Friendly forces
 - (1) Mission of your parent unit
 - (2) Mission of unit providing your support
 - (3) Mission and/or route of adjacent units that may affect your operation
- c. Attachments and detachments
- 2. MISSION

Who, what, when, where (coordinates), and why

- 3. EXECUTION
 - a. Concept of operation. The overall plan (scheme of maneuver) for the unit and plan for fire support (refer to annex).
 - b. Commander's intent. How commander views the upcoming operations.
 - c. Sub-unit missions. For sections, teams and individuals.
 - d. Coordinating instructions
 - (1) Time schedule
 - (2) Formations and order of movement
 - (3) Route (primary and alternate)
 - (4) Movement within friendly front lines
 - (5) Rally points and actions at rally points
 - (6) Actions on enemy contact at danger areas and at the objective
 - (7) Nuclear, biological, and chemical (NBC) safety instructions and mission-oriented protective posture (MOPP) level and Priority intelligence requirements (PIR)
 - (9) Fire support (if not already discussed)
 - (10) Rehearsal and inspections
 - (11) Debriefing (including essential elements of information (EEI), other intelligence requirements (OIR), time, and place
 - (12) Annexes (other actions may be covered separately)

CLASSIFICATION

CLASSIFICATION

4. SERVICE SUPPORT

a. Supply

- (1) Rations
- (2) Uniforms
- (3) Arms and ammunitions
- (4) Captured material
- b. Transportation
- c. Medical evacuation
- d. Personnel
- e. Prisoners of war

5. COMMAND AND SIGNAL

a. Command

- (1) Commander leader location
- (2) Chain of command.
- b. Signal
 - (1) Frequencies and call signs
 - (2) Pyrotechnics and signals
 - (3) Challenges and passwords
 - (4) Code words

NOTES:

- 1. The OPORD heading items may be omitted depending on the situation.
- Details under subparagraphs should be tailored to provide all relevant and essential information.
- Items covered by standing operating procedures (SOP) need not be covered in the OPORD.

CLASSIFICATION

Figure A-2. Format for an operation order (continued).

(Class	sifica	tion)
--------	--------	-------

(Change from oral orders, if any)

Copy ____ of ____ copies Issuing Headquarters Place of issue (may be in code) Date-time Group of signature Message Reference Number

ANNEX __ (CHEMICAL SUPPORT) TO OPERATION ORDER NO

References: Map, charts, and other relevant documents.

1. SITUATION.

a. Enemy Forces. Information should include:

- See annex _____ (Intelligence) to OPORD
- Capabilities of enemy NBC weapon systems (munitions/agents).
- Decontamination/reconnaissance assets.

b. Friendly Forces. Information concerning NBC decontamination, reconnaissance, and smoke assets, not covered by the operation order, that are available in higher, adjacent, supporting, and reinforcing units.


- c. Attachments and Detachments. List the NBC decontamination, smoke, and reconnaissance units attached to or detached from the issuing headquarters.
- d. Assumptions (OPLAN Only). Include information on the ability of friendly forces to conduct chemical operations and defend against NBC attack. Include assumptions as to the probability of enemy use of NBC weapons. Include assumptions of vulnerability of civilian population to NBC attack.
- 2. MISSION. See basic OPORD.
- 3. EXECUTION.
 - a. Concept of Operations. The concept for employment of NBC decontamination, reconnaissance, and smoke assets should be described.

Priorities for NBC reconnaissance, decontamination, and smoke support established.

- b. In subsequent, separate lettered subparagraphs, state the specific tasks to be accomplished by NBC decontamination, smoke, and reconnaissance assets.
- c. Fire Support. See appendix ____ (Chemical Fire Support Plan) to annex ____ (Fire Support) to OPORD

(Classification)

Figure A-3. Model Chemical Support Annex.



- d. Coordinating Instructions.
 - (1) Operational exposure guidance.
 - (2) Troop safety criteria.
 - (3) MOPP level.
 - (4) Location of decontamination sites.
 - (5) Directions for rendering assistance to local populace.
 - (6) Other coordination or control measures applicable to two or more elements of the command.

4. SERVICE SUPPORT.

- a. General. Division installations remain in present locations. Annex H (Service Support).
- b. Material and Services. Information pertaining to availability, procedure for distributing, prestock points, location of decontamination sites, and transportation of NBC defense supplies, materiel, decontaminants, and chemical munitions.
- 5. COMMAND AND SIGNAL.
 - a. Command. Location of primary and alternate NBC defense units.
 - b. Signal.
 - (1) Procedures for requesting NBC defense support.
 - (2) Emergency NBC attack signal, if different from that specified in the SOP.
 - (3) Designate NBC 1 (nuclear) observers.

Acknowledgment instructions.

Last name of commander

Rank

Authentication:
Appendixes:
Distribution:

(Classification)

Figure A-3. Model Chemical Support Annex. (continued).

(Classification)

Copy ___ of ___ copies Issuing Headquarters Date-time Group Message Reference Number

ANNEX __ (SMOKE SUPPORT) to OPLAN/OPORD

References: Map, charts, smoke overlays, and other relevant documents. Time zone used throughout the order:

1. SITUATION.

- a. Enemy Forces. See Annex __ (Intelligence) to OPLAN/OPORD NO
- b. Friendly Forces. Include information concerning smoke assets, not covered by the operation order, that are available in higher, adjacent, supporting, and reinforcing units.
- c. Attachments and Detachments. List assets supporting the smoke mission, attached to, or detached from the issuing headquarters.
- 2. MISSION. State the smoke mission, including deception operations.

3. EXECUTION.

(Commander's intent).

- a. Concept of Operation. From next higher headquarters commander.
 (Describe the concept for employment of smoke assets, to include priorities. Cover the role of smoke in support of the division deception plan.)
- b. (In subsequent lettered subparagraphs, give the specific tasks to be accomplished by smoke assets.)
- c. Coordinating Instructions. (State coordination or control applicable to two or more elements of the command.)
- 4. SERVICE SUPPORT.
 - Material and Services. (Include information pertaining to availability, procedure for distribution, prestock points, and transportation of smoke generator fuel and other supplies.)
 - b. Miscellaneous

(Classification)

Figure A-4. Model Smoke Support Annex.

(Classification)

5. COMMAND AND SIGNAL.

- a. Command. (State procedures for control of smoke assets, and location of primary and alternate command posts.)
- b. Signal. CEOI reference.

(COMMANDER)

(AUTHENTICATION)

1 ENCLOSURE (Operation overlay is enclosed) Describe enclosure (if there is one) DISTRIBUTION:

(Classification)

Figure A-4. Model Smoke Support Annex (continued).

Fragmentary Order

A fragmentary order is used to change or modify the OPORD. It normally follows the OPORD format but only includes the items to be changed or modified.

(Classification) (Change from oral orders, if any) Copy of copies Issuing Headquarters Place of issue (may be in code) Date-time Group of signature Message Reference Number FRAGO References: 1. SITUATION a. Enemy forces. b. Friendly forces. c. Attachments and detachments. 2. MISSION 3. EXECUTION Intent: a. Concept of operations. b. Tasks to maneuver units. c. Tasks to CS units. d. Coordinating instructions. 4. SERVICE SUPPORT
Copy of copies Issuing Headquarters Place of issue (may be in code) Date-time Group of signature Message Reference Number FRAGO References: 1. SITUATION a. Enemy forces. b. Friendly forces. c. Attachments and detachments. 2. MISSION 3. EXECUTION Intent: a. Concept of operations. b. Tasks to maneuver units. c. Tasks to CS units. d. Coordinating instructions.
Issuing Headquarters Place of issue (may be in code) Date-time Group of signature Message Reference Number FRAGO References: 1. SITUATION a. Enemy forces. b. Friendly forces. c. Attachments and detachments. 2. MISSION 3. EXECUTION Intent: a. Concept of operations. b. Tasks to maneuver units. c. Tasks to CS units. d. Coordinating instructions.
References: 1. SITUATION a. Enemy forces. b. Friendly forces. c. Attachments and detachments. 2. MISSION 3. EXECUTION Intent: a. Concept of operations. b. Tasks to maneuver units. c. Tasks to CS units. d. Coordinating instructions.
 SITUATION Enemy forces. Friendly forces. Attachments and detachments. MISSION EXECUTION
 a. Enemy forces. b. Friendly forces. c. Attachments and detachments. 2. MISSION 3. EXECUTION intent: a. Concept of operations. b. Tasks to maneuver units. c. Tasks to CS units. d. Coordinating instructions.
 3. EXECUTION Intent: a. Concept of operations. b. Tasks to maneuver units. c. Tasks to CS units. d. Coordinating instructions.
Intent: a. Concept of operations. b. Tasks to maneuver units. c. Tasks to CS units. d. Coordinating instructions.
A SERVICE SUPPORT
4. DERVICE DOIT ON
5. COMMAND AND SIGNAL
(Classification)
ACKNOWLEDGE: NAME (Commander's last name) RANK (Commander's rank)
OFFICIAL:
ANNEXES: DISTRIBUTION: (Classification)

Figure A-5. Format for Fragmentary Order.

file:///C|/My Documents/Manuals/Military Field Manuals/FM 3-7 NBC Field Handbook/Appa.htm (9 of 11) [29/02/2004 3:52:27 AM]

(Classification)

Copy ___ of ___ copies Issuing Headquarters Place of issue (may be in code) Date-time Group of signature Message Reference Number

SITUATION REPORT NO

Period covered: (date and time to date and time). References: Maps (series number, sheet(s), edition, scale).

1. ENEMY

- a. Units in contact.
- b. Enemy reserves that can affect local situation.
- c. Brief description of enemy activity during period covered by report.
- d. Brief estimate of enemy strength, materiel means, morale, and his probable knowledge of our situation.
- e. Conclusions covering courses of action open to enemy.

2. OWN SITUATION

- a. Location of forward elements.
- b. Location of units, headquarters, and boundaries.
- c. Location of adjacent units and supporting troops.
- d. Brief description and results of operations during periods of report.
- e. Noneffective units.

3. ADMINISTRATION

General statement of the administrative situation, if other than normal, as it directly affects the tactical situation.

4. GENERAL

Information not covered elsewhere.

5. COMMANDER'S EVALUATION

To be completed when directed by higher authority.

Authentication:

Commander

Annexes:	
Distribution:	

(Classification)

Figure A-6. Format for Operational Situation Report. (Based on STANAG No. 2020. Operational Situation Reports) (NOTE: Omit subparagraphs not applicable.)



APPENDIX B

NBC Defense Equipment and Training Items

Table B-1. NBC Defense Equipment.		
Item/Components/Repair Parts	NSN	Reference
Adapter, Oxygen Supply, ABC M8	4240-00-848-6074	
Adhesive, Rubber Type II	8040-00-117-8738	
Alarm Unit, M42	6665-00-859-2215	
Antifreeze Bottle, 1 gallon	6685-00-181-7929	
Antiglare Eyelens, Outsert, M2	4240-00-961-1062	
Antiseize Compound	8030-00-087-8630	
Apparatus, Decon, Portable, ABC M11	4230-00-720-1618	3-4230-204-12&P
Area Predictor, Radiological Fallout, M5A2	6665-00-106-9595	FM 3-3-1
Atom Sign	9905-12-132-2579	
Bag, NBC Storage	8465-01-216-6259	
Bag, Waterproof, CB Mask, M1	4240-00-377-9401	
Battery, BA3090	6135-01-063-1978	
BA 3030		
Battery, CAM	6665-99-760-9742	
Battle Dress Overgarment		
XXX Small	8415-01-137-1700	
XX Small	8415-01-137-1701	
X Small	8415-01-137-1702	
Small	8415-01-137-1703	
Medium	8415-01-137-1704	
Large	8415-01-137-1705	
X Large	8415-01-137-1706	
XX Large	8415-01-137-1707	
Bio Sign	9905-12-132-2578	
Bolt, Machine, Hex HD, Steel	5306-00-206-4931	
Bracket, Mounting	4230-00-776-4385	
Brush, Window	7920-01-136-8892	
Btry Assy, BB501/U	6140-00-134-0850	
Btry, BA3030	6135-00-930-0030	
Btry, Dry Med Dty, BA3517/U	6135-00-450-3528	
Btry, Nonchargeable, Lithium S02, BA-5800/U	6665-99-760-9742	
Buckle	5340-00-961-5547	
Button Flap, Long	4240-00-602-2210	

file:///C|/My Documents/Manuals/Military Field Manuals/FM 3-7 NBC Field Handbook/Appb.htm (1 of 7) [29/02/2004 3:53:13 AM]

Button Flap, Short	4240-00-602-2209	
Cable Assy, M168	5995-00-179-9053	
Calculator Set, ABC-M28A1	6665-00-130-3616	3-6665-303-10
Calipers	5120-00-229-3049	
CANA	6505-00-137-5891	FM 3-4
Canister, Insert Filter	4240-01-177-2675	
Carrier, Headpiece, Hosp, M12	4240-00-368-6361	
Carrier, M17	4240-00-476-2541	
Carrier, M15A1, for M17	4240-00-933-2533	

Table B-1. NBC Defense Equipment (continued).		
Item/Components/Repair Parts	NSN	Reference
Carrier, Smoke Generator, M1059	2350-01-203-0188	3-1040-279-12
Charger, RADIAC Detector, PP1578	6665-00-542-1177	TB SIG 226-8
Chemical Agent Monitor, CAM	6665-01-199-4153	TM 3-6665-331-10
Clamp, Hose	4730-00-269-3760	
Clamp, Wire	4240-00-580-6423	
Clip and Buckle Assembly	4240-00-602-2207	
CM Agent, Auto Alarm Sys, M8A1	6665-01-105-5623	3-6665-312-12
Confidence Sample, CAM	6665-99-225-3523	
Container, Decon	4230-01-136-8891	
Container, Fluid Assy (for tng)	4230-01-136-8889	
Container, DS2, 14 liter	6850-01-136-8888	
Corrosion Prev Compd	8030-00-838-7789	
Coupling, Canister: M1	4240-00-300-6457	
Coupling Half, Quick Disconnect	4230-00-903-4573	
Cover, Helmet, CP	8415-01-111-9028	
Cover, Voicemitter, Assy	4240-00-903-3606	
Cylinder, Nitrogen	4230-00-775-7541	
Decon agent, calcium hypochlorite, HTH,		
99-lb barrel	6810-01-065-2410	
Decon agent, DS2, 1-1/3 quart	6850-00-753-4827	
Decon agent, DS2, 5-gallon	6850-00-753-4870	TB CML 113
Decon agent, STB, I50-pound drum	6850-00-297-6653	
Decon Apparatus, M12A1	4230-00-926-9488	3-4230-209-12
Decon Apparatus, M17	4230-01-251-8702	3-4230-228-10
Decon Apparatus, Portable, M13	4230-01-133-4124	3-4230-214-12&P
Decon Kit, Skin, M258A1	4230-01-101-3984	3-4240-216-10
Decon Kit, 291 SDK	4230-01-276-1905	
Detector, Air Filter	6665-01-071-0716	
Detector Kit, CM Agent, ABC-M18A2	6665-00-903-4767	3-6665-254-12
Detector Kit, CM Agent, M256	6665-01-016-8399	3-6665-307-10
Detector Kit, CM Agent, M256A1	6665-01-133-4964	
Detector Unit, M43A1	6665-01-081-8140	
Disk, Valve	4240-01-104-0965	
Disk, Valve, Outlet	4240-00-712-6090	
Disk, Valve (Inlet, Nosecup)	4240-01-104-0965	
Dist. Mater Managementality Oralist	4340 01 713 6000	I

file:///Cl/My Documents/Manuals/Military Field Manuals/FM 3-7 NBC Field Handbook/Appb.htm (2 of 7) [29/02/2004 3:53:13 AM]

Disk, Valve, Non-metallic Outlet	4240-01-712-0090	1
Eyelens, Outserts	4240-00-678-0731	
Faceform Blank	4240-01-032-6050	
Fallout Prediction Plotting Scale ML556/UM	6675-00-868-8094	FM 3-3-1
Ferrule	4240-01-178-8094	
Filter Canister, M20 SCPE	4240-01-178-9936	
Filter, C2, M40 Mask	4240-01-161-3710	
Filter Element, CB Mask, M13A2	4240-00-165-5026	
Filter, GP, M56/M59/M84 MCPE	4240-01-067-5605	
Filter, M48	4240-01-161-3710	
Filter Unit, Canister, M10A1	4240-00-127-7186	
Fog Oil, SGF2	9150-00-261-7895	
Funnel, Common Lab	6640-00-889-7023	
Gas Sign	9905-23-132-2580	
Generator, Smoke, M3A3	1040-00-587-3618	3-1040-202-12
Generator, Smoke, M3A4	1040-01-143-9506	3-1040-276-10

Item/Components/Repair Parts	NSN	Reference
Gloves, CM Protective		TM 10-277
X-Small	8415-01-144-1862	
Small	8415-01-033-3517	
Medium	8415-01-033-3518	
Large	8415-01-033-3519	
X-Large	8415-01-033-3520	
Glove Insert, White Cotton		
Small	8415-00-268-8354	
Medium	8415-00-268-8353	
Harness, Canister	4240-00-831-2184	
Harness, Head: C15	4240-00-961-1064	
Harness, Head, *8R1)	4240-00-690-8765	
Headpiece, GP, Hosp, M13A1	4240-00-763-2464	
Helmet Cover	8415-01-111-4029	
Hood, CB Mask, Tank, ABC-M5	4240-00-860-8987	3-4240-223-15
Hood, CB Mask, Aircraft, ABC-M7	4240-00-021-8695	3-4200-219-15
Hood, CB Mask, Field, ABC-M6A2	4240-00-999-0420	
Hose, Air Duct	4240-00-829-2761	
Hose Assy, Nonmetallic	4720-01-136-9028	
Inhibitor, Corrosion, vapor	6850-00-865-2916	
Maintenance Kit, M273	5180-01-108-1729	3-6665-312-12
Marking Crayon	7510-12-120-9355	
Marking Rod	9905-12-133-0113	
Mask, CB Aircraft ABC-M24		3-4240-280-10
Small	4240-00-808-8799	
Medium	4240-00-776-4384	
Large	4240-00-808-8798	
Mask, CB, M17A1/M17A2		3-4240-279-10

FM 3-7 Appendix B

Mask, CB, M40/M42	1	3-4240-400-10
M40—Small	4240-01-258-0061	
Medium	4240-01-258-0062	
Large	4240-01-258-0063	
M42-Small	4240-01-258-0064	
Medium	4240-01-258-0065	
Large	4240-01-258-0066	
Mask, CB, Tank, ABC M25A1		3-4240-280-10
Small	4240-00-994-8751	
Medium	4240-00-994-8750	
Large	4240-00-994-8752	
Mask, M43		
Type I, Small	4240-01-208-6966	
Medium	4240-01-208-6967	
Large	4240-01-208-6968	
X-Large	4240-01-208-6969	
Type II, Small	4240-01-265-2677	
Medium	4240-01-265-2679	
Large	4240-01-265-2678	
X-Large	4240-01-265-2680	
Microphone, Carbon (M25/A1)	5965-00-988-8770	
Microphone, Dynamic (M24)	5965-00-900-8102	
MK1 Antidote (NAAK) Kit	6505-01-140-6455	FM 3-4

Table B-1. NBC Defense Equipment (continued).		
Item/Components/Repair Parts	NSN	Reference
MK1 Antidote (NAAK) (Pkg of 30)	5505-01-140-6455	
M12A1 Gas Filter, M8A3	4240-00-289-7978	
M13 Particulate Filter, M8A3	4240-00-368-6291	
M14 GPFU, AR Ambulance	4240-00-010-5267	
M18 Gas Filter, 10 CFM, M13	4240-00-838-3952	
19 Particle filter, M13 GPFU	4240-00-866-1825	
M17A1-X-Small	4240-01-106-0485	
Small	4240-00-926-4199	
Medium	4240-00-926-4201	
Large	4240-00-926-4200	
M17A2—X-Small	4240-01-143-2017	1
Small	4240-01-143-2018	
Medium	4240-01-143-1019	
Large	4240-01-143-2020	
Mount, VDR2, MT6123	5340-01-222-1374	
N-Amyl Acetate	6810-00-123-7047	
NATO Adapter	6665-01-077-2986	
NBC Marking Set, M274	9905-12-124-5995	3-9905-001-10
Nozzle, Spray Head	4730-00-873-1720]
Overboots, CM Protective	8430-01-021-5978	NA
Querhoate Vinul Size 2	8430-01-048-6305	NA

file:///C|/My Documents/Manuals/Military Field Manuals/FM 3-7 NBC Field Handbook/Appb.htm (4 of 7) [29/02/2004 3:53:13 AM]

FM 3-7 Appendix B


Radiac Set, AN/VDR2	6665-01-222-1425	
IM174B/PD	6665-01-056-7422	
IM174A/PD	6665-00-999-5145	11-6611-232-12
IM174/PD	6665-00-856-8037	11-6665-213-12
IM93/UD	6665-00-752-7759	11-6665-214-10
Radiacmeter		
Pyridostigmine Bromide Tablets	6505-01-178-7903	fm 3-4
Pump, Manual	4320-01-136-8894	
Probe, M8A1 Alarm	6665-01-177-9252	
Primer Coating	8010-00-082-1714	
Polyurethane Coating	8010-08-128-6958	
Pin, Temple	4240-00-602-2208	
Particle Filter, MCPE	4240-01-066-3266	
Paper, CM Agent Detector, M9	6665-01-226-5589	3-6665-311-10
Paper, CM Agent Detector VGH ABC-M8	6665-00-050-8529	
Paint, Vellow	8010-00-844-1306	
Paint, OD	8010-00-297-0560	
Packing, Preformed, Nitro Seal	5330-00-804-7767	
Packing, Preformed, Hd and Cont.	5330-00-180-9903	
Overboots, Vinyl, Size 13	8430-01-049-0887	NA
Overboots, Vinyl, Size 12 Overboots, Vinyl, Size 13	8430-01-049-0886	NA
Overboots, Vinyl, Size 11 Overboots, Vinyl, Size 12	8430-01-049-0885	NA
Overboots, Vinyl, Size 10	8430-01-049-0883 8430-01-049-0884	NA
Overboots, Vinyl, Size 9	8430-01-049-0882	NA
Overboots, Vinyl, Size 8	8430-01-049-0881	NA
Overboots, Vinyl, Size 7	8430-01-049-0880	NA
Overboots, Vinyl, Size 6	8430-01-049-0879	NA
Overboots, Vinyl, Size 5	8430-01-049-0878	NA
Overboots, Vinyl, Size 4	8430-01-048-6306	NA
Overboots, vinyi, Size S	0400-01-040-0000	

Table B-1. NBC Defense Equipment (continued).		
Item/Components/Repair Parts	NSN	Reference
Radiac Set, AN/PDR27-Series		
J Model	6665-00-543-1435	11-6665-209-10
L Model	6665-00-856-3456	11-6665-209-10
P Model	6665-00-975-7222	11-6665-224-15
Q Model	6665-00-017-8903	11-6665-209-10
R Model	6665-00-961-0846	11-6665-230-12
S Model	666501-080-4418	11-6665-249-14
Recon system NBCRS, XM93	6665-01-323-2582	
Ring, Retaining, Extension	5365-00-282-1633	
Sampling Kit, CB Agent, M34	6665-00-776-8817	3-6665-268-10
Shoestrings	8335-01-107-6998	
Stud Assembly	4240-00-962-4512	
Suit, CM Protective		TM 10-277
X-X-X-Small	8415-010070-1880	
X-X-Small	8415-01-070-1879	
X-Small	8415-00-407-1060	
Small	8415-00-177-5007	
Medium	8415-00-177-5008	
LargeX-Large	8415-00-407-1062	
XX-L	8415-00-407-1063	
Large	8415-00-407-1064	
TAP Apron, S	8415-00-281-7813	
TAP Apron, M	8415-00-281-7814	
TAP Apron, L	8415-00-281-7815	
Tape, Pressure Sensitive	7510-00-890-9872	
Thickener, Fuel, M4	DODAC K917	FM 3-11
Tool, Closing, Wire Clamp	9505-00-368-6336	
Valve, Inlet, CBR Mask	4240-00-893-3697	
Vest, Microclimate	8415-01-217-5634	
Wand, Brush Half	4710-01-136-8893	
Wand, Pump Half	4710-01-136-8890	3-4230-214-12&p
Water Purification Kit	6810-01-266-6979	5-4250-214-12ap
Water Test Kit, M272	6665-01-134-0885	3-6665-319-10
Winterization Kit, ABC-M4	4240-00-065-0139	3-0005-319-10
Winterization Kit, M253	6665-00-169-1455	3-6665-225-12
Winterization Kit, Tank CB Mask, ABC-M3	4240-00-066-0181	3-4240-202-14
Wire, Safety Sea	5340-00-835-9815	3-4240-202-14
Wool, Metallic: Steel Wool	5350-00-242-4403	
Yellow Rayon Ribbon		
Tellow Rayon Ribbon	8315-12-132-2577	

Table B-2. Training Items		
Nomenclature	NSN	
AN/TDQ-T1, Large Area Radiac Training Set (TSC Local)	6930-01-060-1627	
Atomic Explosion Simulator, M142	FSC-DODIC 1370-L605	
Gloves, Neoprene, Training, Small	8415-01-081-8314	
Medium	8415-01-081-8315	
Large	8415-01-081-8316	
X-Large	8415-01-081-8317	
Grenade, Hand, Riot, CS, M7A3 (16 ea)	FSC-DODIC 1330-G963	
Polyethylene Glycol-200 (PEG 200), 55 Gal	6810-01-074-9719	
Refills, Training Kit, M58A1	6910-01-113-2434	
Riot Control Agent, ABC, CS Capsule (50 ea)	FSC-DODIC 1365-K765	
Simulator, Projectile, Airburst, Liquid (SPAL) M9	1370-01-047-3479 L595	
Talc, Tech, T3, 8 lb	6810-00-142-9849	
Training Kit, M58A1	6910-01-101-1768	
Adapter, Sampling	6910-01-113-3754	
Decontaminating Kit, Skin, M291 (Dual Purpose)	4230-01-276-1905	
Simulator, Automatic Alarm, M81 (Local TSC)	6665-01-088-4789	
Detector Kit Training, M256	6665-01-112-1644	
Training Device Diazepam Injection Automatic	6910-01-275-4833	
Applicator, Disposable	6510-00-3030-8250	
Brush, Acid	7920-00-514-2417	
Brush, Cleaning	1005-00-494-6602	
Brush, Dusting	7920-00-205-0565	
Brush, Scrub	7920-00-061-0037	
Calcium, Hypo	6810-00-242-4770	
Cleaning Compound	6850-00-592-3283	
Cheesecloth	8305-00-222-2423	
Alcohol, Rubbing	6505-00-655-8366	
Knife, Pocket	5110-00-162-2205	
Lacquer, Black	8010-00-085-0559	
N-Amyl Acetate (Banana Oil) Pint Container	6810-00-123-7047	
Pail, Utility	7240-01-094-4305	
Paint, Face Camofl.	6850-00-161-6203	
Polish, Plastic	7930-00-935-3794	
Spoon, Measuring	7330-00-875-6912	
Drafting Set, Plotting		
Goggles		
Riot Control Agent, ABC, CS Capsule (50 ea)	FSD-DODIC 1365-K765	
Talc, Tech, T3, 8 lbs.	6810-00-142-9849	




APPENDIX C NBC Signs




CHEMICAL


Yellow Background With Red Lettering



Name of Agent (If Known) Date and Time of Detection



Name of Agent (If Known) Date and Time of Detection




Dose Rate Date and Time of Reading Date and Time of Burst (If Known)

Surface of Marker Facing Away From Contamination (Front)




BIOLOGICAL

Blue Background With Red Lettering



RADIOLOGICAL

White Background With Black Lettering



Surface of Marker Facing Contamination (Back)







Red Background With Yellow Lettering and Stripe



Chemical Agent in Mine Date of Emplacement Surface of Marker Facing Minefleld (Back)

Surface of Marker Facing Away From Minefield (Front)

Figure C-1. NBC contamination marking signs.

Warsaw Pact Markers



Background; Red Lollering: Block

Rectangle on the feft side contains contamination symbol.

PB = Nuclear

b = Biological

OB - Chemical

An Arrow (dotted line on sign) indicetes direction of conteminated area. A set of lines indicates a decontominated path through the area. A number to the right of the lines indicates the width of this path.





At the boltom of the sign YEPE3 (which means across, over, or through) is followed by a number that indicates the distance across the contaminated area.

If HEPE3 is crossed out and replaced by O65E3A (detour),

-через - 2600м

Soviet Contamination Markers




Figure C-2. Threat Markers. Former Warsaw Pact.



APPENDIX D

Tactical Operations

MEDEVAC Request

- 1. Location of pick-up site.
- 2. Radio frequency, call sign, suffix.
- 3. Number of patients.
- 4. Special equipment required.
- 5. Number of patients by type of casualty (litter, walking wounded).
- 6. Security of pick-up site.
- 7. Method of marking of pick-up site.
- 8. Patient nationality and status.
- 9. NBC contamination (omit if NA).

Troop-leading Procedures

- 1. Receive the mission.
- 2. Issue the warning order.
- 3. Makes tentative plan.
- 4. Conduct coordination.
- 5. Make a reconnaissance (map, physical).
- 6. Complete the plan.
- 7. Issue the order.
- 8. Inspect/supervise/refine.

Declination Diagrams

The declination diagram (usually located in the lower right margin of a map) graphically illustrates the relationships between grid north (symbolized by the letters GN), true north (symbolized by a star), and magnetic north (symbolized by a half arrowhead). Typical declination diagrams are shown in the <u>figure</u> D-1.




Figure D-1. Typical declination diagram.

Of particular interest to the military user is the relationship of grid north to magnetic north, since this defines the relation of azimuth directions on the map (grid) to an Azimuth obtained with a compass (magnetic). This relationship (the GM angle), is expressed in degrees and minutes and accompanies the declination diagram. Some maps also contain a note for converting from grid to magnetic azimuth and from magnetic to grid azimuth as shown. When the note is not given, conversion must be determined based on the declination diagram.

NOTE: Declination diagrams and GM Angles vary from map to map. Users should exercise extreme care to insure that the proper conversions from grid to magnetic azimuth or magnetic to grid azimuth are used.

To convert a magnetic azimuth to a grid azimuth, subtract the GM angle.

To convert a magnetic azimuth to a grid azimuth, add the GM angle.

To convert a grid azimuth to a magnetic azimuth, add the GM angle.

To convert a grid azimuth to a magnetic azimuth, subtract the GM angle.

Combat Preparations

Tactical Road Marches

Movement Order

Movement order of briefing should include as a minimum the following:

• Enemy and friendly situation.

FM 3-7 Appendix D

- Destination.
- Start, critical, release, and rally points.
- Rate of march and catch up speed.
- Support (indirect, direct, and medical) and communications.
- Actions on contact.
- Order of march.
- Route/alternate route.
- Distance between vehicles (day 50 meters; night 25 meters).
- Departure time.
- Location of commander.
- Lead vehicle (security/reconnaissance).

Spot Report
1. Size
2. Activity
3. Location
4. Unit/Uniform
5. Time
6. Equipment

March security

Each vehicle must be assigned a sector of fire. Vehicle crew maintains a 360-degree observation and an air guard.

Halts

Security is first priority on any scheduled, unscheduled, or disabled vehicle halt.

Defense Planning Considerations

- 1. Establish Security (OP/Patrols/PEWs, M8)
- 2. Position Key Weapons:
 - a. Coordinate w/units on left and right
 - b. Establish FPF or PDF for MG.
 - c. Mutual support between MG.
 - d. Cover armor approaches with antiarmor systems.

- e. Establish fire control measures.
- 3. Prepare Positions:
 - a. Cheek sectors of fire.
 - b. Check overhead cover and view
 - c. Position in depth and achieve support between positions.
 - d. Select/Prepare alternate and supplementary positions.
- 4. Integrate indirect fires, CAS and obstacles with direct and indirect fires.
- 5. Check commo and establish emergency signals.
- 6. Designate ammo, supply, PW, and casualty points.

Table D-1. Maximum effective range in meters of weapons.		
Type Max EFF Range (
M16	460	
M79/M203	560	
M60mg	560	
mg, 50 Cal	560	
LAW	560	
SAW	560	
90-mm RCLR	560	
106-mm RCLR	560	
60-mm	560	
81-mm	560	
4.2-in.	560	
TOW	560	
TOW II	560	
DRAGON	560	
105-mm	560	
105-mm Tank	560	
120-mm Tank	560	
25-mm BIFV	560	
155-mm BIFV	560	
M198	560	
8-in How	560	

STANDARD RA	IGE CAND
For use of this form one fill 7-34. The prop	west agrecy is TMAD 00
яар <u>157</u> р.т. <u>157</u> со <u>В</u>	
RT 157	
∞_ <u>_</u> B	MAGNETIC

	1	*		4	
	1)525m	DEAD/SPA		t ax	Bar Or
DATA SECTION					
POSITION IDEN	TIFICATION GL	08451038			JULY
WEAPON			EACH CIRCLE	EQUALS	100
NO.	DIRECTION/ DEFLECTION	ELEVATION	RANGE		DESCRIPTION
1	L035	0/24	400		PDF (WOODGORJ)
2	x 375	-50/15	625		BARN
3	R175	-50/40	725		HEO GE ROW
REMARKS: DA Form 5517-R	0 TW 30/R	7			

Figure D-3. Example of completed DA Form 5517-R.

PP

k

FM 3-7 Appendix D




Figure D-4. Example of a platoon sector sketch.

Table D-2. Final Protective Fires.		
60-mm	70m (W) 30m (D)	
81-mm	100m (W) 35m (D)	
4.2 in	200m (W) 35m (D)	
105-mm	200m (W) 30m (D)	
155-mm (Plt)	200m (W) 50m (D)	
(Btry)	400m (W) 50m (D)	

Bivouac and Assembly Areas

Area must be organized to provide a continuous 360-degree perimeter security. When any element leaves the perimeter, either shrink the perimeter or redistribute the perimeter responsibilities. Crew-served weapons are the basis for the unit defense. Individual weapons provide security for the crew-served weapons and must have overlapping sectors of fire.

Section characteristics are:

- Concealment.
- Cover from direct and indirect fire.
- Defendable terrain.
- Drainage and a surface that will support vehicles.
- Exits and entrances, and adequate internal roads or trails.
- Space for dispersion of vehicles, personnel, and equipment.
- Suitable landing site nearby for supporting helicopters.

Quartering party responsibilities are:

- Reconnoiters the area.
- Checks the area for NBC hazards.
- Checks the area for obstacles and mines, then marks or removes them.
- Marks platoon and squad sectors.
- Selects a command post location.
- Selects a company trains location.
- Provides guides for the incoming unit(s) to accomplish immediate occupation.

Recommended priority of work:

- Post local security (LP/OP).
- Position crew-served weapons (combat engineer vehicle (CEV), antitank (AT) weapons, and machine guns) and chemical alarms.
- Assign individual fighting positions.

FM 3-7 Appendix D

- Clear fields of fire, prepare range cards and camouflage vehicles.
- Prepare hasty fighting positions.
- Install/change to land line communication.
- Emplace obstacles and mines.
- Construct primary fighting positions.
- Prepare alternate and supplementary fighting positions.
- Stockpile ammunition, food, and water.

Recommend actions at the bivouac and assembly area are:

- Reorganization.
- Weapons check.
- Maintenance.
- Distribution of supplies.
- Rest and personal hygiene.
- Consumption of rations.

Fire Support Procedures and Characteristics

Call for Fire Elements

Identification

Call signs.

Warning order

Type mission, adjust fire, fire for effect, immediate suppression. Method of target location: grid, polar, shift from known point.

Target location

Grid: six-digit grid (degrees (roils, or cardinal directions) direction

Polar: direction (degrees, roils, or cardinal directions) distance vertical correction (fire direction center must know observer location)

Shift: right/left from known point add/drop from known point vertical correct from known point (fire direction center must have known point)

Target description

Size, number, type, degree of protection, status.

Method of engagement (optional)

Ammunition/fuze desired, sheaf corrections, high angle, danger close.

FM 3-7 Appendix D

Method of tire and control (optional)

At my command, time on target, request splash.

Adjustments

The adjustments that may be needed to obtain round on target arc spotting, lateral, and range.

Spotting

Is where round lands in relation to target, such as short or long and number of roils right or left of target. Example of spottings: short 40 right or long 50 left.

Lateral correction (right/left)

Adjust the lateral shift from impact to observer target (OT) line in meters. Corrections of 20 meters or less will be ignored until firing for effect.

W = Rm W = Lateral shift correction in metersm = mils between burst and targetR = OT factor = target range (to nearest 1,000 meters)1,000

NOTE: If target range is less than 1,000 meters, round to nearest 100 meters.

Range correction (up/down)

Mechanical time fuze only. Initial range shift correction is used to bracket target (Table D-3).

Range deviation

Table D-3. Target bracketing.		
Distance (meters) to Target	Change	
Less than 1.000	+ /- 100 meters	
1.000 to 1.999	+ /- 200 meters	
2.000 or greater	+ /- 400 meters	

Target location examples

Grid Coordinates

"F6A15, THIS IS F6A27(FDC) and observer.	Call signs of the fire direction center
ADJUST FIRE, OVER."	Warning to alert the firing unit.
"GRID 135246, OVER."	Normally, a six-digit grid is best.
"2 MACHINE GUNS FIRING	Description of the target.

FM 3-7	Appendix	D
--------	----------	---

VT IN EFFECT, OVE	R"
-------------------	----

"DIRECTION 1650, OVER."

Adjustment is conducted with fuze quick. Fuze variable time (VT) will be used in fire for effect.

Must be sent before or with first correction.

Polar Coordinates

"F6A15, THIS IS F6A27	Call signs of the FDC and observer.
FIRE FOR EFFECT, POLAR, OVER."	Warning to alert the firing unit.
"DIRECTION 0250	Direction from the observer to the target.
DISTANCE 3500, OVER."	Distance from the observer to the target.
"25 INFANTRYMEN IN OPEN	Description of the target.
ICM, AT MY COMMAND, OVER."	Improved capabilities missile (ICM) rounds will be used. The observer will command FIRE at the appropriate time after the FDC informs the observer that the tiring unit is READY.

NOTE: Direction must be given before any subsequent corrections when adjusting fires.

Shift From A Known Point

"F6A1, THIS IS F6A FIRE FOR EFFECT, SHIFT	Call signs of the FDC and observer.
BG43, OVER. "	Warning to alert the firing unit.
"DIRECTION 5470	Direction from the observer to the target.
LEFT 400, OVER. "	The target is located 400 meters to the left of BG43 and at the same range. (Lateral shift or range changes can be omitted when not needed.)
"25 INFANTRYMEN IN SHALLOW	Description of the target.
FOXHOLES, VT IN EFFECT, OVER. "	Airbursts are most effective against protected personnel without overhead cover.

Fratricide Risk Assessment Matrix

Example of Unit Defense Perimeter TACSOP

A. Upon arrival to new site, ALL personnel:

(1) Position mission-essential vehicles for easy access to main avenue of approach.

FM 3-7 Appendix D

(2) Drape camouflage over all vehicles.

- (3) Prepare hasty fighting positions.
 - Range cards
 - Fields of tire
 - Concealment
 - Berms
 - Choose M60 positions
 - Choose primary line of fire
- (4) Choose secondary positions.
- (5) Run TA-1 wire to M60/Forward dismount point.
- B. If no enemy action is imminent, reduce security to 1/4, and:
 - (6) Improve vehicle camouflage.
 - (7) Download vehicles.
 - (8) Prepare biouvac:
 - CP first
 - 292 and PRC-77
 - Tentage
 - Camo systems
 - Latrine site
 - Garbage site
 - Concertina wire
 - Hasty minefield
 - (9) Perform daily PMCS on ALL equipment.
 - (10) Prepare duty rosters.
 - (11) Improve fighting positions:
 - Overhead cover
 - Concealment
 - Early warning devices
 - Pyrotechnics

What can a commander expect from his chemical staff?

TOC OPERATION CHECKLIST

Section I: Mission requirements.	YES	NO
1. All radios (AM/FM) are operational and manned by qualified personnel.		
2. Situation map is posted with the current operation(s) and updated with significant developments.		
3. The Staff Duty Journal (DA Form 1594) is opened as soon as TOC is operational, and all significant developments are entered on the form.		
Section II: Additional requirements that improve efficiency and survivability.		
Telephone nets are opened.		
5. Planning map and/or planning overlays are available to the commander.	<u> </u>	
TOC personnel are assigned defensive sectors, and hasty defensive positions are prepared.		<u> </u>
7. Access to TOC is controlled (e.g., concertina and sentries positioned and ID badges used).		
8. TOC duty shifts are designated.		
9. Vehicles, equipment, and positions are camouflaged.		
10. Facilities are blacked out.		
11. Generators are sandbagged.		
12. Fighting positions are improved.		



APPENDIX E

Conversions and Measurements

Conversion Factors

To Convert	То—	Multiply By—
Acres	Square Feet Square Yards Square Miles Square Meters Hectares	43,560 4,840 0.00156 4,046.856 0.40468
Barrels	Gallons Not-Petroleum Petroleum	31.5 42
Centimeters	Inches Feet	0.3937 0.0328
Cubic Centimeters	Cubic Inches	0.06102
Cubic Feet	Cubic Inches Cubic Meters Cubic Yards Gallons Liters	1,728 0.028317 0.037037 7.48 28.32
Cubic Feet of Water	Pounds at 60°F Gallons	62.37 7.481
Cubic Inches	Fluid Ounces Quarts Gallons	0.554113 0.017316 0.004329

	Mainiters	10.387004
Cubic Meters	Cubic Feet Cubic Yards	35.3145 1.30795
Cubic Yards	Cubic Feet Cubic Meters	27 0.76456
Cups	Teaspoons Tablespoons Ounces	48 16 8
Feet	Centimeters Miles Kilometers	30.48 0.00019 0.0003
Gallons	Milliliters Cubic Inches Cubic Feet Cubic Yards Cubic Meters Fluid Ounces	3.785 231 0.1337 0.00495 0.00379 128

To Convert—	To¤	Multiply By¤
Kilograms	Long Tons Metric Tons	0.00098 0.001
Kilometers	Feet Miles	3,280.8 0.62137
Liters	Fluid Ounces Quarts Gallons British Gallons Cubic Inches Cubic Feet	33.814 1.05669 0.2642 0.2198 61.02374 0.03531

file:///Cl/My Documents/Manuals/Military Field Manuals/FM 3-7 NBC Field Handbook/Appe.htm (2 of 7) [29/02/2004 3:55:12 AM]

	Cubic Meters	0.001
	Cubic Yards	0.00131
Meters	Inches	39.37
	Feet	3.2808
	Yards	1.094
Miles	Nautical Miles	0.869
	Feet	5,280
	Yards	1,760
	Meters	1,609.344
Miles (Nautical)	Statute Miles	1.1508
Milliliters	Fluid Minnnims	16.231
	Fluid Drams	0.2705
	Cubic Ounces	0.0338
	Inches	0.061
Millimeters	Inches	0.03937
Ounces	Grains	437.5
	Drams	16
	Pounds	0.0625
	Grams	28.34952
	Kilograms	0.02835
Ounces (Fluid)	Minims	480
	Pints	0.0625
	Quarts	0.03125
	Gallons	0.00781
	Cubic Inches	1.80469
	Cubic Feet	0.00104
	Milliliters	29.57353
	Liters	0.02957
	Teaspoons	6
	Tablespoons	2

Ounces (British Fluid)

To Convert—	To¤	Multiply By¤
Pounds	Ounces Grams Kilograms Short Tons Long Tons Metric Tons	16 453.6 0.453592 0.0005 0.0004466 0.0004536
Pounds of Water	Gallons	0.1198
Quarts (Dry)	Cubic Inches	67.2006
Quarts (Fluid)	Fluid Ounces Cubic Inches Cubic Feet Millimeters Liters	32 57.749 0.033421 946.358 0.946333
Square Centimeters	Square Inches Square Feet	0.115 0.00108
Square Feet	Square Inches Square Yards Square Centimeters Square Meters	144 0.111111 929 0.0929
Square Inches	Square Centimeters	6.452
Square Meters	Square Feet Square Yards	10.765 1.196
Square Miles	Acres Square Kilometers	640 2.589998

FM 3-7 Appendix E

Square Yards	Square Meters	0.836
Tons (Long)	Pounds Kilograms Short Tons Metric Tons	2,240 1,016.185 1.12 1.016
Tons (Short)	Pounds Kilograms Long Tons Metric Tons	2,000 907.185 0.89286 0.907185
Tons (Metric)	Pounds Kilograms Long Tons Short Tons	2,204.62 1.000 0.984206 1.10231
Yards	Centimeters Meters	91.44 0.9144

Celsius-Fahrenheit Conversions

°C	°F	°C	°F	°C	°F
-50 = -58		+10 =	+50	+70 =	+158
-45 = -49		+15 =	+59	+75 =	+167
-40 = -40		+ 20 =	+ 68	+ 80 =	+176
-35 = -31		+ 25 =	+77	+85 =	+185
-30 = -21		+ 30 =	+86	+90 =	+194
-25 = -13		+35 =	+95	+95 =	+ 203
-20 = -4		+40 =	+104	+100 =	+ 212
-15 = +5		+45 =	+113	+105 =	+ 221
-10 = -14		+50 =	+122	+110 =	+ 230
-5 = +23		+55 =	+131	+115 =	+ 239
0 =-32		+ 60 =	+140	+120 =	+ 248
+5 = +41		+65 =	+149		
°C = (°F-3	32) x .5	6	°F≕	(1.8 x °C) +32

Decontaminant Containers -Measurements and Weights

Containers	Measurement	Weights
Drum, 55-gallon, 16-gage (NSN 8110-00-597-2353)	Cubage —12 cubic feet Length —35 inches Width —27.5 inches	Empty, 70 pounds Filled with water, 526 pounds Filled with STB (slury), 600 pounds Filled with DS2, 507 pounds
Drum, 55-gallon, 18-gage (NSN 8110-00-292-9783)	Cubage — 12 cubic feet Length — 35 inches Width — 27.5 inches	Empty, 50 pounds Filled with water, 506 pounds Filled with STB (slury), 600 pounds Filled with DS2, 487 pounds
Ash and Garbage Can, 32-gallon (GL Can) (NSN 7240-00-160-0440)	Cubage —7 cubic feet Length —26.5 inches Width —20 inches	Empty, 33 pounds Filled with water, 300 pounds Filled with STB (slury), 353 pounds Filled with DS2, 288 pounds
Gasoline Can, 5-gallon (NSN 7240-00-178-8286)	Cubage — 1 cubic feet Length — 18.50 inches Width — 6.75 inches	Empty, 10.5 pounds Filled with water, 52 pounds Filled with STB (slury), 66 pounds Filled with DS2, 50 pounds
Pail, 5-gallon, DS2 (NSN 7240-00-575-2243)	Cubage — 1 cubic feet Length — 13.75 inches Width — 11.12 inches	Empty, 6 pounds Filled with water, 48 pounds Filled with STB (slury), 61 pounds Filled with DS2, 46 pounds
Drum, 8-gallon, STB, 16-gage (NSN 6850-00-297-6693)	Cubage —1.4 cubic feet Length —14 inches Width —14 inches	Empty, 11 pounds Filled with water, 78 pounds Filled with STB (slury), 91 pounds Filled with DS2, 71 pounds





References

Sources Used

These are the sources quoted in this publication.

FM 3-3. Chemical and Biological Contamination Avoidance. 16 November 1992

FM 3-3-1. Nuclear Contamination Avoidance.

FM 3-4. *NBC Protection*. 29 May 1992.

FM 3-5. NBC Decontamination. 17 November 1993.

FM 3-6. Field Behavior of NBC Agents (including Smoke and Incendiaries). 3 November 1986.

FM 3-9. Potential Military Chemical/Biological Agents and Compounds. 12 December 1990.

FM 3-11. Flame Field expedients. 19 September 1990.

FM 3-18. Special NBC reconnaissance (LB Team). 7 May 1993.

FM 3-19. NBC Reconnaissance. 19 November 1993.

FM 3-100. NBC Defense, Chemical Warfare, Smoke and Flame Operations. 23 May 1991.

FM 3-101. Chemical Staffs and Units. 19 November 1993.

FM 3-101-1. Smoke Squad/Platoon Operations.

FM 3-101-2. NBC Reconnaissance Platoons and Squads.

Documents Needed

These documents must be available to the intended users of this publication.

DA Form 2028. Recommended Changes to Publications and Blank Forms. February 1974.

CTA 50-900.





Glossary

В
BDO battle dress overgarment
BMNT beginning morning nautical twilight
С
CCelsius
CAMchemical agent monitor
CARCchemical agent resistant coating
CBchemical-biological
CDMchemical downwind message
CF correlation factor
cGycentigray(2)
cGyphcentigray per hour
CIcombat ineffective
COAcourses of action
CONUS continental United States
CPOG chemical protective overgarment
CPS Collective Protection Shelter
CUCVCommercial Utility Cargo Vehicle
D
DADdetailed aircraft decon
DAP decon apparatus, portable

```
FM 3-7 Glossary
DED--detailed equipment decon
deg--degree(s)
DGN--degrees grid north
DMN--degrees magnetic north
DTN--degrees true north
DGZ--desired ground zero
DKIE--decontamination kit, individual equipment
DS2--decontaminating solution No. 2
DTD--detailed troop decon
E
EDM--effective downwind message
EENT--early evening nautical twilight
est--estimated
ETO--ethylene oxide
F
F--Fahrenheit
G
gal--gallon(s)
GEOREF--World Geographic Reference System
GMT--Greenwich mean time
GN--grid north
GZ--ground zero
Η
H--high-test hypochlorite
HC--hexachloroethane
HMMWV--high-mobility, multi-wheeled vehicle
HOB--height of burst
hr--hour(s)
```

FM 3-7 Glossary

HTB--high-test bleach

hvy--heavy

Ι

IAW--in accordance with

ID--inside does rate

IPB--intelligence preparation of the battlefield

IPE--individual protective equipment

K

km--kilometers

kmph--kilometers per hour

KT--kiloton

L

lb--pound(s)

LDS--light decon system

LL--latent lethality

LSD--least separation distance

\mathbf{M}

m--meter(s)

MDWIID--maximum downwind hazard distance

mech--mechanized

met--meteorological

min--minute(s)

mm--millimeter(s)

MOGAS--motor gasoline

MOPP--mission-oriented protective posture

MGN--mils grid north

MMN--mils magnetic north

MTN--mils true north

FM 3-7 Glossary MRL--multiple rocker launcher **MSD--**minimum safe distance mtr--motorized Ν NATO--North Atlantic Treaty Organization NBC--nuclear, biological, and chemical **NBCC--**NBC center NBCWRS--NBC warning and reporting system **NF--**normalizing factor No.--number 0 octant--one of eight world areas **OD--**outside dose rate **OEG--**operation exposure guidance **OPLAN--**operation plan **OPORD--**operation order Р PAA--peracetic acid **PD--**performance decrement PDDE--power-driven decontaminating equipment POL--petroleum, oils, and lubricants Q qt--quart R **RES--**radiation exposure status **RP--**red phosphorous

S

S2--intelligence officer

FM 3-7 Glossary S3--operations and training officer SCPE--simplified collective-protective equipment SG--smoke generator **SITREP--**situation report **SOI--**signal operating instructions **SOF--**special operations forces **SOP--**standing operating procedures STANAG--NATO standardization agreement **STB--**supertropical bleach Т **TF--**transmission factor **TOC--**tactical operations center U unk--unknown **US--**United States of America **UT--**undemanding task UTM--universal transferse mercator W **WP--**white phosphorous